

Douglas County Surveyor's Record of
Government Corners Renewed

23 T. S. 3 R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 97196

7
Corner Common to Sections 21, 22, 27 and 28.
GLO Survey Record All evidence lost.
Found - Post & Witness Trees below, which are the accessories of
G. A. Gardner survey filed in the Surveyor's office.
24" Hemlock N.86°W. 29.7 ft. scribed S21 BT.
19" Hemlock S.74°E. 18.3 ft. scribed S27 BT.
20" Hemlock N.88°E. 16.5 ft. scribed S22 BT.
68" Cedar S.62°W. 12.3 ft. scribed S28 BT.
Set $\frac{1}{2}$ " x 30" galvanized iron pipe by the Cedar Post.
Referenced by M. D. Hale (plates and "W" nails only)
Declination 20°
28" Hemlock N.48°W. 70.2 ft.
68" Cedar S.62°W. 12.3 ft.
30" Fir S.06°E. 30.0 ft.
38" Hemlock N.07°E. 74.3 ft.
Fo. O.K. - Oct. 1967 V.R.T.

8
 $\frac{1}{4}$ Corner Common to Sections 28 & 29. O.S. 531107
GLO Survey Record Post, gone.
24" Hemlock S.40°W. 50 lks., found 34" Hem. stump
with part of old face. Partially destroyed by
logging.
24" Fir N.10°E. 75 lks., found 54" x 30" High
Fir Snag with BLM plate.
Set $\frac{1}{2}$ " x 34" galvanized iron pipe for corner from the above
34" Hemlock Stump using the record bearing & distance.
Referenced by M. D. Hale (plates and "W" nails only)
Declination 20°
39" Hemlock Stump S.70°E. 65.5 ft.
30" Cedar Stump N.75°W. 43.6 ft.
Fo. O.K. - Oct. 1967 V.R.T.

9
Corner common to Sections 20, 21, 28 and 29.
GLO Survey Record:
24" Fir for corner, found 14" x 2' high rotted &
broken Fir Snag Stump for corner with remains of
original scribing visible.
5" Hemlock N.30°E. 15 lks. Gone.
6" Hemlock S.60°E. 6 lks. Gone.
6" Hemlock S.45°W. 8 lks. Gone.
10" Hemlock N.15°W. 32 lks. Possible root holes.
Found the Witness Trees, below, which are the accessories of G.
G. A. Gardner survey filed in Surveyor's Office.
26" Fir N.35°E. 24.3 ft., scribed S21 BT.
23" Fir N.85°W. 24.6 ft. scribed S20 BT.
23" Fir S.34°W. 18.6 ft., scribed S29 BT.
20" Fir S.41°E. 28.0 ft., scribed S28 BT.
Set $\frac{1}{2}$ " x 35" galvanized iron pipe in center of the rotted
Fir Stump for corner.
Referenced by M.D. Hale (plates and "W" nails only)
20" Fir S.41°E. 28.0 ft.
23" Fir S.34°W. 18.6 ft.
40" Fir N.62°E. 64.3 ft.
26" Fir N.66°W. 51.4 ft.
Fo. O.K. Oct. 1967 V.R.T.

10
 $\frac{1}{4}$ Corner Common to Sections 21 and 28.
GLO Survey Record All evidence lost.
Set $\frac{1}{2}$ " x 35" galvanized iron pipe for corner by single
proportionate method.
Referenced by M. D. Hale (plates and "W" nails only)
Declination 20°
18" Fir S.75°W. 7.9 ft.
22" Fir N.29°W. 34.0 ft.

11
Corner for Center of Section 28. O.S. 531107 460
Set $\frac{1}{2}$ " x 35" glvnzd iron pipe in 42" Fir windfall for the
former by the inter-section method.
Referenced by M.D. Hale (plates & nails only. 36" Fir stump N.62°W. 14.1 ft.
65" Fir stump N.12°W. 57.7 ft.

Marion D. Hale
Witnesses: H. E. Case
W. W. Dixon
For Weyerhaeuser Timber Co.
Dates of survey, March 20, to April 1, 1959
Filed - June, 1959
C. S. File No. 51/25