

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 23 S. T. S. R. 3 W. R.W.W.M.

KOKE-CHARMAN CO., EUGENE, ORE. 21881

Milo E. Godfrey, Deputy Co. Surveyor  
Vernon Tracy and Mike Stone  
July 1963  
C. S. File No. 53/9

SW. Corner of Section 31, T23-3W. S31  
Found - Brass Cap set by Price in Mound of Rocks.  
30" Fir Stump (sawed high) N.21°E. 175.6 ft. All Scribng visible.  
82" Fir Stump N.63 $\frac{3}{4}$ °E. 169.6 ft., scribing visible "31 BT".  
2" Fir Snags mention by Price:  
22" Fir Stub S.57 $\frac{3}{4}$ °W. 24.4 ft., charred face.  
50" Fir Snag N.30°W. 59.4 ft., axe scar on bark (charred)  
New BT's: 28" D.Fir S.59°W. 55.1 ft. Mkd: T23S R3W S31 CS BT.  
7" Chinq. N.54°E. 35.8 ft. Mkd: T23S R3W S31 CS BT.  
No trees avail. to N. E.

12

Closing Cor. to Sec. 36, T23-4W. & Sec. 1, T24-4W. CC  $\frac{S\ 36}{S\ 1}$  | S 31  
Found - Brass Cap set by Price, 1950.  
9" Cedar Snag N.32 $\frac{3}{4}$ °W. 66.7 ft., all scrbing vis.  
36" Sawed Fir Stump S.77 $\frac{1}{4}$ °W. 120.1 ft., all scrbing. vis.  
New BT's: 6" Hemlock N.61°W. 27.4 ft. Mkd: T23S R4W S36 CC CS BT.  
6" D.Fir S.23°W. 29.2 ft. Mkd: T24S R4W S 1 CC CS BT.

13

Closing Cor. to Sec. 1, T24-4W. & Sec. 6, T24-3W. CC  $\frac{S\ 31}{R4W\ S\ 1/S\ 6\ R3W}$  T23S T24S  
Found - Brass Cap set by Price in 1950.  
9" Fir Snag S.48°E. 42.9 ft. All scribing visible on open face.  
7" Short Cedar Snag S.43 $\frac{1}{4}$ °W. 54.1 ft. All scribing visible on face.  
New BT's: 10" D.Fir S.58°E. 28.2 ft. Mkd: T24S R3W S6 CC CS BT.  
13" Red Cedar S.54 $\frac{1}{2}$ °W. 47.9 ft. Mkd: T24S R4W S1 CC CS BT.

14

Wilford N. Haines  
For Woolley-  
Whipple &  
Weyerhaeuser  
M 26 - 80

$\frac{1}{4}$  Corner to Section 7, T23-3W. and Sec. 12, T23-4W. 15  
Set - 1" x 1" x 36" T. Iron by prop. measurement.  
Scribed - 5" D. Fir S.31°E. 6.3 feet.  
6" D. Fir N.15°W. 6.4 feet.  
November 1963

Reset  $\frac{1}{4}$  Sec. Cor. on 5th. Stand. Parallel South Boundary Sec. 31, T22-3W. 16  
Found - Old Post Gone.  
Old BT., 48" Fir S. 14 lks., standing figures all gone on  
account of having been put in bark.  
Old BT., 30" Cedar N.35°E. 30 lks., standing spot rotten  
and parts of P S. barely visible.  
Set new Yew Post. and 12" Yew S.67°W. 25 lks.  
30" Cedar S.83°E. 63 lks. H. Taylor, Surv.  
Jan. 9, 1905

Sec. Cor. for Secs. 5 & 6, T23-3W. & Secs. 31 & 32, T22-3W. 17  
Chopped out SW BT., marked by Harvey Taylor, Feb., 1905.  
D. Fir 16" Diam. when scribed, now 26" in diam. bears S.55°W. 35.6 ft.  
Fir, 14" diam. when scribed, felled; stump now 26" diam., bears  
N.73°E. 51.5 feet scribing "C.S" in standing tree plainly visible.  
Set - 2" Iron Pipe 4' long in ground, leaving 3" above ground.  
Gilbert A. Gardner, Surv.  
Dec. 9, 1953

Lane County Records  
See C. S. File No. 53/1

$\frac{1}{4}$  Sec. Cor. to Sections 7 and 8. 18  
Found - Old Post standing with fig. visible.  
Old BT., a Fir N.73°E. 63 lks. standing with fig. " $\frac{1}{4}$ S" in poor cond.  
Old BT., A yew N.23°W. 41 lks., standing figures all gone,  
figures rotted away.  
Set - New Yew Post marked C.S. from which:  
12" Yew bears N.28°W. 65 lks.  
8" Yew bears N.23°E. 70 lks.

Harvey Taylor, Sp. Deputy  
August 12, 1915