

Douglas County Surveyor's Record of
Government Corners Renewed

T 23 S . T. S. R 3 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Corner Sec. 18, T23-3W. & Sec. 13, T23-4W. C.S. 53/107 27
4150
Found - GLO Survey Record, 1882.
50" Fir scribed W. face, fd. bark scribed "1/4" West face of 60" Fir.
8" Yew S.40°W. 25 lks., 16.5 ft, fd. 10" Yew, broken 4' high, dead,
scribing visible.
40" Fir N.10°E. 19.8 ft., now 46" Fir, axe marks not chopped,
possibly was bark scribed, flaked.
Set - 5/16 Iron Rod in West Root-Swell of 60" Corner Fir.
Base of Rod is 6" West of bark scribing.
S.18 1/2°W. 23.0 ft., Dist. & Bear. taken to scribing on W. face Corner Fir
to scribed Yew.
N. 6° W. 19.8 ft., From scribing on West face Corner Fir to 46" Fir. E.
(GLO bearing probably should be N.10°W., instead of N.10°
New BT's: 56" Fir N.22°E. 35.0 ft. : 48" Fir S.46°W. 31.0 ft.

Sec. Cor. to Secs. 7 & 18, T23-3W. & Secs. 12 & 13, T23-4W. C.S. 53/107 28
4150
Found - GLO Survey Record, 1855, Post, No trace.
15" Cedar N.50°W. 29.7 ft., 26" x 15' Stub, badly burned, no scribing.
8" Cedar S.68°W. 24.4 ft., No trace.
12" Cedar S.55°E. 7.9 ft., now 38" Cedar, faces not chopped. 51
80" Fir N.50°E. 12.5 ft. , now 86" Fir, bark scribing visible.
New BT's: 52" Fir Stump N. 5° E. 51.8 ft., "W" Nail & Plate.
86" Fir (Orig. BT) N.61°E. 12.0 ft., " "
38" Cedar (Orig. BT) S.54°E. 6.6 ft., " "
12" Cedar S.51°W. 32.0 ft. "W" Nail & Plate.

1/4 Corner to Section 18 and 7. 29
Found - GLO Survey Record, 1882 - 8" Vine Maple, No trace.
5" Maple N.60°W. 4.0 ft, No trace.
5" Hemlock S.8°E. 6.6 ft., 14" x 4' Stub scribed "1/4" visible.
Corner Set: Yew Post by GLO Dist. & Bear. from SE. BT.
New BT's: 64" Fir S.40°E. 21.0 ft., "W" Nail & Plate.
8" Hemlock N.64°E. 39.3 ft. " "

1/4 Corner to Sections 26 and 23. 30
Found - GLO Survey Records, 1882:
4" Chinquapin, now 7", leaning, no scribing visible, rotted off.
60" Fir S. 30° E. 15 lks., O. K., scribing on back.
40" Fir N.13°W. 55 lks., No trace.
Set - 1/2" x 35" G.I. Pipe in notch at base of leaning chinquapin for corner.
"W" nails, plates 20° decl.
New BT's: 58" Fir S.23°E. 9.2 ft., Orig. BT.
50" Fir N.67°E. 52.4 ft.

Section Corner common to Secs. 23 - 24 - 25 - 26. 31
GLO Survey Record: A cross (+) at exact corner point upon a large rock
8' high by 25' by 40'. A kind of ledge in small opening or prairie.
Found Rock Ledge but cross apparently eroded away.
24" Fir N.50°E. 150 lks., gone.
A mound of stone was erected by Mr. Woodard on the ledge for the corner
point. This point was referenced by Marion D. Hale in May, 1956 as follows:
26" Fir N. 38° E. 85.6 ft. Plates & "W" Nails only.
The following accessories were added by G. McChesney, May, 1958:
14" Inc. Cedar N. 09° W. 92.9 ft.
12" Fir S. 65° E. 36.1 ft.

1/4 Corner common to Sections 24 and 25. 32
GLO Survey Record, Post, gone.
50" Fir N.45°W. 35 lks., now stump, scribing visible.
40" Fir S.10°E. 40 lks., now stump, " "
Set 3/4" x 30 1/2" Monel Pipe & set a 2" x 10' Pipe alongside the monel pipe.
New BT's: 43" Fir Stump S. 4° W. 26.3 ft. (Orig. BT) "W" Plates & Nails
54" Fir Stump N.62° W. 19.8 ft. (Orig. BT.) "W" Nails & Plates.

Glen McChesney
Weyerhaeuser Co. 1958
Lane County Records
C. S. File No. 53/1