

Douglas County Surveyor's Record of
Government Corners Renewed

T. 23 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31881

50

U. S. B.L.M. - Dep. Resurvey
N. Bdry T23-3W.
June 10, 1959
Notes in C.S. File No. 54/16

The Standard Corner of Twp.s 22 & 23 S., Rs. 3 & 4 W.,
perpetuated with an aluminum pipe, $\frac{1}{2}$ " diam., firmly set, 12" above
ground, at record bearing & distance from the only remaining Orig. BT:
59" Fir bears N. 65° E. 39 lks. dist. with scribe marks "S",
& other illegible scribe marks visible on partially open blaze.
At the corner point, Set Iron Post, 28" long, $2\frac{1}{2}$ " diam., 24" in the
ground, with brass cap mkd:

| | |
|--------|-------|
| T 22 S | |
| R 4 W | R 3 W |
| S C | |
| S 36 | S 31 |
| S 1 | S 6 |
| T 23 S | |

1959

from which new bearing trees:
7" Madrone N. 52 $\frac{1}{2}$ ° E. 72 lks. mkd: T22S R3W S31 SC BT.
6" Chinq. S. 29 $\frac{3}{4}$ ° E. 38 lks. mkd: T23S R3W S6 SC BT.
6" Madrone S. 36° W. 60 lks. mkd: T23S R4W S 1 SC BT.
6" Madrone N. 82 $\frac{1}{2}$ ° W. 21 lks. mkd: T22S R4W S36 SC BT.
Deposit local corner marked alongside the Iron Post.

Vernon "Ray" Tracy
Mike Stone and J. Layne
November 1965
C. S. File No. 54/16

Sec. Cor. to Secs. 7 & 18, T23-3W. & Secs. 12 & 13, T23-4W.
Found - Orig. 80", now 86" Fir N. 61° E. 12.5 ft., recorded N. 50° E.,
shows "SRW" bark scribe & "W" Nail at Base. Alive.
Orig. 12", now 38" Cedar S. 55° E. 7.9 ft., several cruiser's
marks & "W" Nail. Do not open. Alive.
Orig. 15", now 26" Cedar N. 50° W. 29.7 ft., burned out snag. No Scribe.
52" Fir Stump N. 5° E. 51.8 ft. (Weyerhaeuser, Ren. #28) Not scribed.
12" Cedar S. 51° W. 32.0 ft., "W" Nail & Tag, not scribed. Alive.
Set - Brass Cap at Cor. Mkd: Doug. Co. Surv. T23S S 12 | S 7
Office, 1965 R4W S 13 | S 18 R3W
New BT: 9" Hemlock N. 24° W. 70.4 ft. Mkd: T23S R4W S12 DCS BT.

Sec. Cor. to Secs. 18 & 19, T23-3W. & Sec. 13 & 24, T23-4W.
Found - Orig. 6", now 8" Vine Maple Corner Tree, bark scribed "T23SR4W"
on S.W. Side, other scribe fragmentary.
Orig. BT's., now stumps, with only S.E. in position.
Orig. 30", now 44" Fir Stump S. 65° E. 21.8 ft., shows "S" on bark.
Weyerhaeuser BT's, See Ren. #26, now stumps except S.W.
17" Hemlock S. 34° W. 32.7 ft. "W" nail & plate, not scribed.
Creek calls out of corner fit reasonably well. Corner Tree in very poor
condition, we tip out & Set:
Set - Brass Cap at Cor. Mkd: Doug. Co. Surv. T23S S 13 | S 18
Office, 1965 R4W S 24 | S 19 R3W
New BT's: 15" Hemlock S. 5° E. 40.6 ft. mkd: T23S R3W S19 DCS BT.
9" Hemlock S. 67° W. 17.9 ft. mkd: T23S R4W S24 DCS BT.
13" Hemlock N. 68° E. 43.2 ft. Mkd: T23S R3W S18 DCS BT.
No tree suitable to N. W.

8-8-69 FOUND OK. L.L.

Vernon "Ray" Tracy
Jack Heritage
Sept. 25, 1967
C. S. File No. 54/16

Section Corner to Sections 32 & 33, T23-3W. and
Sections 5 & 4, T24-3W.
Found - 1950 GLO Brass Cap, firmly set & properly marked.
8", now 16" Hemlock, alive, N. 53 $\frac{1}{4}$ ° E. 19.8 ft., scribe visible
on unhealed blaze.
8", now 14" Hemlock S. 18 $\frac{1}{4}$ ° E. 20.5 ft., alive, healed blaze.
12" Hemlock, now stump, S. 70° 45' E. 37.0 ft., scribe mks. visible.
18" Yew, now stump, N. 49 $\frac{1}{2}$ ° W. 64.0 ft., scribe marks visible.
Orig. Fir to S.W., now stump, find no bark scribe.
No trace Orig. BT. to S.E.
New BT's: 8" Hemlock S. 38° W. 18.4 ft. mkd. T24S R3W S5 CS BT.
9" Chinq. N. 34° W. 12.8 ft. mkd. T23S R3W S32 CS BT.
Note - This corner lies 150 ft. N. of small creek, dry, in cut off area.

MICROFILM TO HERE 10/67