

Douglas County Surveyor's Record of
Government Corners Renewed

T. 23 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21601

54

Section Corner to Sections 25 - 26 - 35 - 36.
Found - Orig. 24" now 38" Fir Stump, N.37°E. 39.6 ft. (Record N.47°E.)
fragmentary bark scribes. "W" Nail & Tag.
Orig. 30" Fir, now 48" Burned stump, S.30°E. 56.1 ft.,
no scribe or scar. "W" nail & tag.
Orig. 28" Fir, now 42" burned stump, S.60°W. 31.0 ft., no
scribe or scar. "W" Nail & Tag.
No trace of Corner Stone or N.W. BT.
42" Fir Stump bears N. 78° W. 78.0 ft., "W" Nail & Tag.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 23 S R 3 W
(Set Cap in Mound of Office S 26 | S 25
(Stone at base of rock 1967 S 35 | S 36
(ledge 6 ft. high in bluff area)
No new BT's. marked due to logging, no stumps other than originals.
Corner is on southerly slope of ridge sloping west.

55

1/4 Corner to Sections 25 and 26.
Found - Squared Cedar Post bears S.28°E. 4.0 ft., Ren. #33.
Orig. 14" now 26" Cedar, alive, S.40°W. 7.9 ft., prev.
opened & shows scribe.
Orig. 20" Cedar, now 36" Stump, N.20°W. 27.0 ft. (Record 16.5')
fragmentary scribe marks on decayed blaze.
Set - Brass Cap at Cor. Mkd: Doug. County T 23 S R 3 W
Surveyor's Office 1/4 S 26 | S 25
1967
New BT's: 11" Cedar N.74 1/4°E. 33.1 ft. mkd. "1/4 S25 DCS BT."
(Ren. #33 BT. with "W" Nail)
10" Hemlock N. 85° W. 33.3 ft. mkd. "1/4 S26 DCS BT."
Note - This corner lies on northerly slope on Lane-Douglas County Line.

56

Section Corner to Sections 29 - 30 - 31 - 32.
Found - Orig. 28" Cedar, now 53" Stump, N.40°E. 29.7 ft., reverse
face & axe notch visible on top of stump.
(Possib-Orig. 6" now 18" Hemlock, S.49°E. (Record S.55°E.) 22.4 ft.,
alive, no scar shown. (We scribe "T23SR3WS32 CS BT")
Orig. 40" Hemlock, now 50" Stump, S.3°W. 42.9 ft., "S31"
visible. Open lower & find "BT" scribe.
Orig. 30" Hemlock, now 42" Stump, N.25°W. 26.4 ft.,
shows scar.
Ren. #23 BT's: 32" Cedar S.32°E. (not S.28°W.) 65.0 ft., now stump, "S32BT".
20" Cedar, N.27°E. 81.7 ft. (not 80.5') "S29BT".
Gardiner's N.W. BT. gone completely & S.W. BT. down. This corner
lies on East slope approx. 150 ft. W. of small ravine, course N.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 23 S R 3 W
(Set 6' Steel Fence Post) Office S 30 | S 29
(alongside Brass Cap) 1967 S 31 | S 32

57

Closing Corner Sections 30 and 31, T23-2W.
Found - Weyerhaeuser Corner with evidence of Original Corner.
1 1/2" I. P. for corner & 10 ft. high marked pipe.
Orig. 36" Fir, now 40" Stump, N.50°E. 24.4 ft., cut open
& face burned. No scribe.
Orig. 16" Fir, now 17" Stump, S.40°E. 29.0 ft., cut open,
scribe visible.
Orig. 24" Fir, now 30" Stump, N.18°W. (Record N.31°W.) 12.5 ft.,
shows good scar. Do not open.
Weyerhaeuser BT: 50" Fir Stump N.32°E. 4.3 ft. "W" Nail & Tag.
Note - This corner lies 75 ft. E. of spur, sloping south approx.
730 ft. N. of corner of Sections 25 & 36, T23-3W.

11/3/67

Vernon "Ray" Tracy
 Jack Heritage & V. Perron
 November, 1967
 C. S. File No. 54/16