Douglas County Surveyor's Record of Government Corners Renewed

23 T. S. 4 R. W. W. M.

H. I. Epstein H. I. Epstein H. C. McHenry
C. S. Geo. Sperr Wolford, P.
H. E. Richardson A. Wolford F. J. Frear N. Richardson
B. A. Lane Witness Witnesses
Witnesses Aug. 28, 1928 Sept. 1921
8/4/32 Old Vol 1 Renewed Cors. Old Vol 1 Renewed Cors.

1 COR. SEC. 4-5-8-9
Re-Est. by 4" x 4" x 36" Cedar Stake, from which
A 14" W. Oak, bears S.20°E., 89.4 feet dist.
A 18" W. Oak, bears S.24°E., 54.5 feet dist.
A 12" W. Fir, bears N.68°E., 24.5 feet dist.
A 15" W. Oak, bears N.68½°E., 33.0 feet dist.
RE-RENEWED, SEE CORNER NO. 32

2 COR. SEC. 15-16-21-22
Set corner from 2 old Oaks B. T. scribe mark on 20" bears N.W. Set Ford Axle for corner. Mark new trees as follows
Fir 36", S.34°E. 102 lks. dist.
W. Oak 12", N.45°30'W. 103 lks.
Fir 24" N.39°30'E. 27 lks.
No tree near in Sec 22
RE-RENEWED, SEE CORNER NO. 112

3 ¼ CORNER BETWEEN 28-29
Set corner from one old B.T. which had been blown down & the top off. Scribe marks in bark. Set post for corner marking bew B.T.
15" Fir, S.20°30'W. 16.5 feet
5" Fir, S.69°30'E. 27.0 feet
RE-RENEWED, SEE CORNER NO. 24

4 COR. SEC. 28-29-32-33
Set cor. from one old B. T. reset with iron bar 7/8" x 30" from which
18" W. Oak, bears N.9°E. 90'
30" Cedar, bears S.28°E. 240.7 feet
RE-RENEWED, SEE CORNER NO. #77

5 ¼ COR. BET 4 & 9
Set from stumps of old trees. Set 3" x 3" sq. post, from which
12" W. Fir, bears S.60°W. 13.3 feet
10" W. Fir, bears N.3°W. 20.2 feet
RE-RENEWED, SEE CORNER NO. 68

6 SEC. COR. 8-9-16-17
Found original post at fence corner, set another 4" x 4" sq. post for cor. from which
15" Doug. Fir, bears N.50°W. 50.8 feet
14" D. Fir, bears N.45°W. 11.2 feet
36" Doug. Fir, bears S.81°E. 64.0 feet
24" D. Fir, bears N.3½°W. 30.2 feet.
RE-RENEWED, SEE CORNER NO. 30 + 72

7 ¼ COR. BET. 9 & 16
Set from laurel clump for orig. B. T. to S. and stump hole to N. Set 4" x 4" Cor. Post, from which
23" Fir, bears N.43°E.
33" Fir, bears S.71°E.
RE-RENEWED, SEE CORNER NO. 74

8 ¼ COR. BET. 8 & 9
Set at fence cor. which has always been used as corner, it checks 0.7 from N. & Cor. Sec. 9 and 0.4 from dist. S. of creek bank. Set post sq. for cor. from which
30" Doug. Fir, bears N.85°W. 26 feet dist.
33" Fir, bears S.40°E. 28.3 feet dist.
RE-RENEWED, SEE CORNER NO. 31

9 ¼ COR. BET. SECS. 9 & 10
Set from Orig. stump which shows scribe mark (to S.W.) set 3" x 3" post, from which
24" Doug. Fir, bears S.67°E. 25.4 feet
10" W. Fir, bears S.77°W. 40.4 feet dist.
RE-RENEWED, SEE CORNER NO. 67 + 73

10 S.W. COR. NW¼SW¼ Sec. 18
Set by prop. mmt. Set Auto Top Bow, for cor. from which
18" Doug. Fir (on N. & S. Fence) bears N.74°E. 17.88 feet dist.

Arthur Boyer D. C. S.
J. H. Wittmeyer, Chas Neel, Witnesses
Dec. 30 and Jan 1, 1937 and 1938
from Old Vol 1 Renewed Corners
E.C.S. File 30/32 - - - - - Mr. Payne - - -
Mr. Payne, - - Wit.

11 ¼ Section between Sections 6 and 7.
Set a sandstone 12 x 10 x 10 from which a Fir 36" in diam. bears S. 43° E. 80 lks. distant.
A Fir 40" diam. bears N. 59°E. 50 lks. distant.
June 28, 1899. In presence of Robert Cook and Joe Turpin, stubs of original B. T. are standing, badly decayed letters partly visibly
RE-RENEWED, SEE CORNER NO. 28 + 17

C.S. Vol 2 Pg 261