

Douglas County Surveyor's Record of
Government Corners Renewed

23 T.S. 4 R. W. W. M.

CORNER SEC. 9

Set 4" x 4" Ced. post for cor. from
14" Cedar bears S. 34° W. 12 feet
15" Cedar bears S. 33° W. 38 feet dist.

RE-RENEWED, SEE CORNER NO. #160

12

SEC. COR. BET. 23 - 26 *SHOULD BE IN T23S. R.5W. OK'd By B.R.I. & F.D. J.R.*

Location identified from an original bearing tree, 30" Alder N. 21° E. 22 lks. This tree was dead & quite rotten but still standing on the bank of Pollock Creek, where chopped out, scribe marks were visible in the fungus film between the surface of the original blaze. Drove a 1" iron pine 48" long, 46" in ground for the corner & set a Cedar post 4" sq. 60 ins. long along side, scribed S. 23 1/2° 2326. C.S. from which a Fir 14 ins. diam. bears N. 21° W. 46.8 ft. blazed & scribed 1/4 S. 23 C.S. B.T. & Fir 20" diam., bears 2.22 1/2° E. 64.1 ft. blazed & scribed 1/4 S. 26 C.S. B.T.

13

COR. BET. SECS. 20 & 21

Set 4" x 4" x 36" sq. Fir post, for corner from B.T.s namely:

14

Fir 3.25° E. 25 lks. in good condition & O.K. rescribed on bark 1/4 S. 21 T. 233. R. 4W. & also from other B.T.s. Fir 15 lks. which is down in the approach to the O.K. (found scribe marks on it) Marked New tree 36" Fir, 3.62° W. 60 feet (on slope) Marked 1/4 S. 20 T. 233. R. 4W. C.S. B.T.

RE-RENEWED, SEE CORNER NO. 26A

CORNER TO SEC. 20-21-28-29

Set 4" x 40" Cedar Post marked 320 321 328 329 T. 233. R. 4W. from one old B.T. only a W. Oak N. 18 1/2° W. 878. lks. which is sound & standing. Marked New B.T.s as follows

15

36" Wye Cedar, N. 14° E. 85.3 feet (on slope)

Marked S. 21 T. 233. R. 4W. C.S. B.T.

20" Marked Ash 3.54° E. 290.3 ft. (on slope)

Marked S. 28 T. 233. R. 4W. C.S. B.T.

12" Cedar 3.81 1/2° W. 205.2 ft. (on slope)

Marked S. 29, T. 233. R. 4W. C.S. B.T.

143

CORNER TO SECS. 1, 2, 11, 12

I established this corner from the S.E. & S.W. bearing trees both dead, cut in S.W. tree & found old B.T. & N.W. trees gone. Set a stone 24" x 16" x 12" in mound of stones 12" in ground marked x C.S. from which I marked.

16

A Fir 10" in diam. bears N. 53° E. 30.7 feet, Marked T. 233. R. 4W. Sec 1, C.S.

A Fir 14" in diam., bears N. 80° W., 9.6 feet., Marked T. 233. R. 4W., Sec 2 C.S.

A Fir 20" in diam., bears S. 51° W. 42 ft., Marked T. 233. R. 4W. Sec 11. C.S.

A Fir 28" in diam., bears S. 66° E. 15.8 ft., Marked T. 233. R. 4W. Sec 12 C.S.

COR. BET. SEC. 6 & 7

Location identified from old B.T.s S. E. 10 lks. good condition & scribed. Marks plain. Stump of O.B.T. N. 59° E. 50 lks. scribe marks visible. Corner Rock set by Thiel 1899

17

Set a stone 24" x 12" x 24" in mound of rock 30" diam. & 18" high, from which

A tree bears N. 63° E. 40 lks. marked 1/4 S. 6 C.S. B.T.

Jan 21, 1938
A. Poyer, D.C.S.
J. H. Wittmeyer
Chas Neel
Witnesses
C.S. 32/52

R.P. Irvine D.C.S.
W.E. Richardson
J.H. Dougherty
Ceri Johnson
Witnesses
Jan. 28, 1940

Arthur Poyer, D. C. S.
Rosale Howard
Merlin E. Allen
Joe Pinkston
Witnesses
C.S. 16/60

C.S. 16/60
March 6, 1940

O. T. Thiel
Floyd Durrett
R. Telson
1940
From old 1611
Renewed Corners
Pt. 35
(copy pages 21/6)

B. P. Irving D. C. S.
E. E. Richardson
Loren Weber
Witnesses
2/9/1940
V. 16 E. 55

#11