

Douglas County Surveyor's Record of  
Government Corners Renewed

23 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

38

Sections 33 & 34, T.23 S. R4W. and T24S R4W, Sec. 3.  
Found - 1" T. Iron with "Haines" Cap at Corner. (F.B. N-225)  
Now 30" Maple S.67°W. 38.0 ft. (Record S.67°W. 20.5 ft.)  
Show real old axe marks & old but rotted face, No scribing.  
Find base of rotted Hemlock Stump that checks bearing & distance  
for Original S. E. BT.  
No other Orig. BT's Found.  
Haines rescribed 30" Maple "R4W".  
I do not set Brass Cap.  
New BT's: 7" Hemlock bears N.25°W. 5.5 ft. scribed S33 CS BT.  
7" Hemlock bears N.61°E. 26.4 ft. scribed S34 T23S R4W CS BT.

James W. Byron, Deputy  
Milo Godfrey  
Clebe Putnam  
August 27, 1959  
C. S. File No. 49/124

RE-RENEWED CORNER NO.

39

5/81 Fnd. OK. R. Quimby M 79-77  
1/4 Section Corner to Sec. 31, T23S R4W, & Sec. 36, T23S R5W.  
Found - Orig. 18", now section of Chinquipin Snag, S.80°E.  
15.8 ft., no scribing.  
Orig. 30", now 50" Fir Stump, center burned, I open  
from inside & find good scribing "Bl"., S.15°W. 17.2 ft.  
Large Fir Snag North 50 ft. which is record line tree.  
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959  
1/4 S36/S31 T23S  
R5W R4W  
Note - Fence 50 ft. West of corner.  
No live trees near.  
New BT's: 60" R. Fir Stump bears S.49°E. 53.0 ft. scribed 1/4 S31 CS BT.  
70" R. Fir snag bears S.72°W. 34.3 ft. scribed 1/4 S36 CS BT.  
scribed on root section, faces to N.E.

James W. Byron  
Milo Godfrey  
Clebe Putnam  
Dec. 3, 1959  
C.S. File No. 49/42

40

Standard Sec. Cor. to Sec. 6, T23S R4W, Sec. 1, T23S R5W.  
Found = Orig. 14", now 34" W. Oak N.80°W. 1091.0 ft. Theil  
rescribed this BT. years ago. I open back of his  
scribing & find Orig. scribing "WR".  
Also find 2" iron pipe at corner. Turpin says Theil  
set this pipe for corner.  
Closing corner 4.59 chains west, not found.  
New BT: 26" Maple bears N.80 1/2°W. 475.0 ft. scribed S36 T22S R5W CS BT.  
No other Trees near.  
2" Iron Rod with 4" x 4" White Post bears S.55°E. 88.2 ft., Post  
marked SHRW L PT 722 = 72.44.

James W. Byron  
Milo Godfrey  
Clebe Putnam  
Jan. 25, 1960  
C. S. File No. 49/42

SEE ALSO  
REN #27

41

1/4 Section Corner to Sections 27 and 34.  
Found - Orig. 40", now 48" Fir N.67°E. 54.1 ft., shows orig.  
bark scribing "AS", also new bark scribing "AS".  
Orig. Chinquipin BT., now snag.  
6" R. Fir, new scribing bears N.57°E. 20.9 ft.  
Find also, Haines angle iron & cap at corner.  
I do not set Brass Cap at Corner.  
New BT.: 16" R. Fir bears S.41 1/2°E. 46.1 ft. scribed 1/4 S34 CS BT.  
Note - This corner probably renewed by Haines within the past year  
but not recorded.

Surveyor's Office  
March 15, 1960  
C.S. File No. 49/42

129

42

Corner common to Secs. 1 & 2, 23S-4W, & Secs. 35 & 36, 22S-4W.  
GLO Survey Record, All evidence gone.  
County Survey Record, All evidence gone.  
By careful retracement of the Twp. Line to the East & West, the  
Orig. Line Trees were found and the corner was re-established at  
the prop. dist. between the following identified Orig. Line Trees:  
Nailed a 3" x 3" piece of aluminum to a 12" Fir log for corner  
at prop. dist. between the following identified Orig. Line Trees:  
48" Fir East 166 feet - 2 notches on E. & W. sides.  
42" Fir Stmp. West 166 feet.  
Referenced by Glen McChesney (Weyerhaeuser Method) Dec. 20°  
12" R. Cedar N. 23°E. 22.0 ft.  
50" Fir S. 79°E. 39.9 ft.  
2" R. Cedar Stp. S. 02°W. 31.4 ft.  
3" R. Cedar N. 45°W. 28.6 ft.  
Note - More information in file, if needed.

Weyerhaeuser Timber Co.  
Lester B. Calder  
Glen McChesney  
April 14, 1960  
C. S. File No. 51/87

#192  
SEE ALSO  
C.S. 11/5  
1/15/61  
C.S. 44/61  
C.S. 44/61  
C.S. 44/61

Nov. 1965 -  
CORNER QUESTIONED  
BY TRACY & CREW.  
NOT SUFFICIENT EVIDENCE

RE-RENEWED CORNER NO.

Fd ok  
10/79  
C.S.  
12/63

Fd ok  
Dec 1960  
CS  
53/101