

Douglas County Surveyor's Record of
Government Corners Renewed

23 T. S. 4 R. W. W. M.

KORE-CHAPMAN CO. EUGENE, ORE. 97881

Weyerhaeuser Timber Co.
Lester E. Calder
G. McChesney
April, 1960
C. S. File No. 51/87
53/108

1/4 Corner Common to Sec. 1, 23S-4W, & Sec. 36, 22S-4W. 43
GLO Survey Record: Post - Gone. 120
17" Fir N.22°E. 26 lks., now 38" Fir Windfall, faces are up,
filled with dirt & upper face rotted.
28" Fir S.57 1/2°W. 70 lks., remains of roots of large Fir,
S.58°W. - 46.2 ft.
Found 1" I.P. 6" out of ground for corner, good for dist. & bear.
for GLO BT's. Drove 1" x 30" aluminum pipe beside this iron pipe.
Referenced by Glen McChesney (Plates & "W" Nails only) Dec. 20°
26" Fir N.71°W. 11.9 ft.
50" Fir S.75°W. 15.6 ft.

Corner common to Sections 1, 2, 11 and 12. 44
Note - See C. S. File No. 51/87 for GLO Survey Record found and
County Survey Record found.
Referenced by Glen McChesney (Plates & "W" nails only) Dec. 20°. 125
12" Fir N.24°E. 39.5 ft.
32" Fir S.69°E. 15.1 ft. CSBT
22" Fir S.50°W. 41.5 ft. CSBT
36" Fir N.79°W. 8.7 ft. CS BT. REN # 16

Wilford N. Haines
For Yoncalla Lumber Co.
May 1960
C. S. File No. 51/102

Section Corner to Sections 5 - 6 - 7 - 8. 45
Found - Scribed Stake at old fence Corner.
1 chain North to 70" Fir, Line Tree.
N. 40°W. 26 lks. to rotted Fir Stump
S. 50°E. 29 lks. to rotted Fir Stump
40.8 ft. East to Creek.
Set 1" x 1" x 36" T. Iron by Stake.
Found scribed R. cedar, 18", S.11°E. 12.0 feet. #153
NOT SEE O.F. THIEL RECORD BOOK C.S. 64/48 P.9

1/4 Section Corner to Section 7 and 8. 46
Found - Orig. B.T.'S., both standing: CORNER NO. 116
30" Pine S.36°E. 17 lks.
36" Fir S.14°W. 42 lks.
Set 1" x 1" x 36" T. Iron.

By Wilford N. Haines
For Dave Rust
July 1960
Map File
M 19 - 38

1/4 Section Corner to Sections 33 and 34. 47
Found - 20" Cedar, now a rotted Stump, S.63°E. 38 lks.
Set 1" x 1" T. Iron in East Edge of Road.
Scribed - 5" W. Fir S.40 1/2°E. 79.5 feet.
7" R. Cedar N.72 1/2°W. 126.6 feet. 130

Weyerhaeuser Timber Co.
Lester E. Calder
By Glen McChesney
June 1960
C.S. File 51/87

1/4 Corner common to Section 4 - 23S-4W 48
Section 33 - 22S-4W
GLO Survey Record
Post No Trace
12" Laurel S.38°E. 10.6 ft. 18" Laurel, down, rotted, & hollow,
but scribing visible.
8" Fir N.18°W. 39.6 ft. 28" Fir - scribing visible.
Found 1" Iron Rod for corner, good for dist. & bear. from GLO BT's.
Referenced by G. McChesney (Plates & "W" nails only) Decl. 20°
28" Fir N.17°W. 38.2 ft. Orig. BT.
44" Fir S. 5°W. 45.6 ft. #166