

Douglas County Surveyor's Record of
Government Corners Renewed

23 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31801

59

~~RENEWED SEE CORNER NO. 122~~
 $\frac{1}{4}$ Corner to Section 11 and 12.
 Found - 8" W. Fir N.38°W. 37 lks.
 Set - 1" x 1" x 36" T. Iron & Scribed:
 10" Cedar N.40°W. 15.2 ft.
 12" Maple S.28°E. 13.7 ft.

60

Section Corner to Sections 11 - 12 - 13 - 14.
 Found - N. W. BT. - Set, 1" x 1" x 36" T. Iron & Scribed:
 10" Fir N.27°E. 101.2 ft.
 12" I. Cedar S. 6°E. 88.9 ft.
 8" Fir S.62°W. 57.7 ft.
 18" Fir N.20°W. 75.2 ft.

END DK 1297, Roberts, M 127-80

61

$\frac{1}{4}$ Corner to Sections 12 and 13.
 Found - Stub of Orig. Fir BT. S.14°W. 17 lks.
 1 $\frac{1}{2}$ " I. Pipe in place for Corner.
 Set - 1" x 1" x 36" T. Iron by Pipe & Scribed:
 26" Fir S.11 $\frac{1}{2}$ °E. 62.1 ft.
 20" I. Cedar N.23°W. 47.4 ft.

~~RENEWED SEE CORNER NO. 127~~
 $\frac{1}{4}$ Corner to Section 11 and 14.
 Found - $\frac{3}{4}$ " Iron Pipe & Stump Hole for 70" Fir N.75°W. 22 lks.
 Set - 1" x 1" x 36" T. Iron by Pipe & Scribed:
 26" Fir S.25°W. 26.4 ft.

62

Center $\frac{1}{4}$ Corner to Section 11.
 Set - 1" x 1" x 36" T. Iron & Scribed:
 12" Fir N.21°W. 7.3 ft.
 8" E. Cedar N.30°E. 16.3 ft.

63

Section Corner to Sections 10 - 11 - 14 - 15.
 Found - Rock in South Track of Road.
 10" W. Oak, 26", N. 2°E. 68 lks.
 Stump Hole N.75°W. 44 lks.
 Set - 1" x 1" x 36" T. Iron 2 ft. South of Corner & Scribed:
 28" 22" Oak N.88°W. 12.5 ft.
 36" Oak S.84°E. 93.6 ft.

64

South Boundary T23-4W. Cor. to Sections 3 and 2 only, T24-4W.
 Found - Rock set by Nicklin, 1896, 2 notches on East face and
 4 notches on West face.
 Burned Remnant of old Fir Snag S.32°E. 56.8 ft., reverse
 scribing plainly visible on charred face inside snag.
 Dead Fir Snag S.81°W. 52.1 ft., very plain axe scar vis. Didn't open.
 22" Madrone, alive, N.64°W. 23.8 ft., center badly rotted, no scrbing.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T24S R4W
 Office, 1962 S 3/S 2
 New BT's: 17" D. Fir S.47°W. 43.7 ft. Mkd: T24S R4W S3 CS BT.
 12" D. Fir S.65°E. 38.0 ft. Mkd: T24S R4W S2 CS BT.
 Haines" "T" Iron & Cap bears North 5.0 ft. from corner.

65

Sec. Cor. to Secs. 31 & 32, T23-4W. & Secs. 6 & 5, T24-4W. ^{5/81} Fnd. O.K. ^{R. Quimby M 79-77}
 Found - 24" Maple S.45°E. 87.1 ft., cut open & fd. good scribing, "BT".
 30" Dead W. Oak N.70°W. 103.0 ft., cut open & fd. good scribing.
 (Tree was approx. 24" diam. when scribed, not 16")
 Rotten Oak Log to S.W.; impossible to tell exactly where it stood,
 but would have been close to S.57°W. 15 lks. Remnant of old
 rotted face, no scribing, at approx. 20" Diam., not 2".
 No trace of N. E. Bearing Tree.
 Set - Brass Cap at Cor. Mkd: County Surveyor's S31 | S32 T23S
 Office, 1963 S 6 | S 5 T24S R4W
 New BT's: 20" I. Cedar S.39°W. 21.4 ft. Mkd: T24S R4W S6 CS BT.
 16" D. Fir S.10°E. 35.6 ft. Mkd: T24S R4W S5 CS BT.
 9" I. Cedar N.63°E. 87.2 ft. Mkd: T23S R4W S32 CS BT.
 8" E. Cedar N.48°W. 131.0 ft. Mkd: T23S R4W S31 CS BT.

66

By Wilford N. Haines
 For Whipple Mill, Drain, Oregon
 June 1961
 Map File M 22 - 6

Milo E. Godfrey, Deputy
 Vernon Tracy and Mike Stone
 September 24, 1962
 C. S. File No. 49/124

Corner Set 2/26/63

206