

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 23 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

99

1/4 Corner Sec. 13, T23-4W. & Sec. 18, T23-3W.  
Found - GLO Survey Record, 1882.  
50" Fir scribed W. face, found bark scribed "1/4" W. face of 60" Fir.  
8" Yew S.40°W. 25 lks., 16.5 ft., now 10" Yew, broken 4' high,  
dead, scribing visible.  
40" Fir N.10°E. 19.8 ft., now 46" Fir, axe marks not chopped,  
possibly was bark scribed and flaked off.  
Set - 5/16 Iron Rod in west root-swell of 60" Corner Fir.  
Base of Rod is 6" West of bark scribing.  
S.18 1/2°W. 23.0 ft., dist. & bear. taken to scribing on W. face corner  
Fir to scribed Yew.  
N. 6° W. 19.8 ft., from scribing on W. face corner Fir to 46" Fir.  
(GLO bearing probably should be N.10°W., instead of N.10°E.)  
New BT's: 56" Fir N.22°E. 35.0 ft., - 48" Fir S.46°W. 31.0 ft.

Glen McChesney - Weyerhaeuser Co.  
Lane County Records  
C. S. File No. 53/1

100

Sec. Cor. to Secs. 12 & 13, T23-4W. & Secs. 7 & 18, T23-3W.  
Found - GLO Survey Record, 1855, - Post, no trace.  
15" Cedar N.50°W. 29.7 ft., now 26" x 15' Stub, badly burned,  
No scribing.  
8" Cedar S.68°W. 24.4 ft., No trace. 138  
12" Cedar S.55°E. 7.9 ft., now 38" Cedar, faces not chopped.  
80" Fir N.50°E. 12.5 ft., now 86" Fir, bark scribing visible.  
New BT's: 52" Fir Stump N.5°E. 51.8 ft., "W" Nails & Plate.  
86" Fir(Orig.BT) N.61°E. 12.0 ft. " "  
38" Cedar(Orig.BT) S.54°E. 6.6 ft. " "  
12" Cedar S.5 1/2°W. 32.0 ft. " " "

Bruce R. Rogers,  
Deputy & Crew  
Jan. 1965  
C.S. File  
No. 53/101

101

Section Corner to Secs. 4 & 5, T23-4W. & Secs. 32 & 33, T22-4W.  
Found - 1" Plum Pipe at Corner, (not recorded)  
40" Fir, now burned stump, S.20°E. 30.4 ft. F D O K  
16" Fir, now stump, S.30°W. 51.5 ft., good scar. Les Roberts  
18" Fir N.10°W. 50.8 ft., open shows scribing "BT". M125-48  
16" Fir N.54°E. 11.9 ft., not found. 7/96  
New BT's: 9" Fir S.80°E. 25.0 ft. scribed T23S R4W S4 CS BT.  
8" Fir N.52°E. 40.4 ft. Mkd: T22S R4W S33 CS BT.  
19" B.Oak N.12°W. 15.6 ft. Mkd: T22S R4W S32 CS BT.  
Note - Fence N. & S. 4.4 ft. West.

102

Section Corner to Secs. 23 - 24 - 25 - 26.  
Found - Stone, not found, but corner is under large windfall.  
8" Cedar N.22°E. 31.0 ft., face open & good scribing visible.  
36" Fir S.53°E. 41.6 ft., stump hole of large, rotted fir windfall.  
36" Fir S.15°W. 35.6 ft., rotted, broken stump.  
50" Fir N.25°W. 4.6 ft., 56" Snag, no scribing found, possibly  
bark scribed where recent windfall scraped this face of tree.  
Wilford Haines' "T" Iron Stake.  
BT's.-14" Cedar N.21°E. 30.0 ft. (Orig.BT) "W" Nail & plate added.  
26" Cedar S.27°E. 10.5 ft. (Haines scribed), "W" Nail & plate added.  
6" Cedar S.44°W. 20.0 ft. " " " " " " " " " "  
12" Cedar N.68°W. 48.7 ft. " " " " " " " " " "

103

1/4 Corner to Sections 25 and 26.  
Found - 1884 Stone in place.  
50" Fir N.37°E. 7.9 ft., high stump, face deeply burned out.  
12" Yew S.37°W. 9.9 ft., burned stump, portions of orig. scribing.  
Haines' "T" Iron Stake in good cond. alongside stone.  
Haines 16" Cedar BT., scribe face still open.  
Haines 16" Fir BT., " " " " " " " " " " " "  
BT's.- 16" Cedar S.57°E. 22.7 ft. "W" Nail & Plate added. #184  
16" Fir N.60°W. 56.4 ft., " " " " " " " " " "

Weyerhaeuser Co.  
1963  
C. S. File No. 53/108