

Douglas County Surveyor's Record of
Government Corners Renewed

T. 23 S. T. S. R. 4 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued) Weyerhaeuser BT's, recorded in Ren. #98, how
Stumps, except S. W.
17" Hemlock S. 34° W. 32.7 ft., "W" Nail & plate, not scrbd.
Corner tree in very poor condition, we tip out &
Set - Brass Cap at Cor. Mkd: Doug. Co. Surv. T23S R4W S 13 | S 18 R3W
Office, 1965 S 24 | S 19
New BT's: 15" Hemlock S. 5° E. 40.6 ft. Mkd: T23S R3W S19 DCSBT.
9" Hemlock S. 67° W. 17.9 ft. Mkd: T23S R4W S24 DCS BT.
13" Hemlock N. 68° E. 43.2 ft. Mkd: T23S R3W S18 DCS BT.
No tree suitable to N. W.

Vernon "Ray"
Tracy & Crew
Nov. 1965
C. S. File
No. 54/16

140

1/4 Corner to Sections 27 and 26.
24" Fir N. 85° W. 27.72 ft. - Found 24" Fir with bark scribe.
Came back later & scribe was chopped out.
Found Stump of 40" Fir S. 45° E. 1.98 ft.
Rescribed; bark, 24", now 36" Fir N. 85° W. 27.7 ft. SEE REN. #145
Scribed: 12" I. Cedar S. 69° E. 23.5 ft.
Nov. 8, 1965 - Found Haines' "T" Iron at this corner & BT's.
as described above. Signed V.R. Tracy.

Willford N. Haines
Approx. 1960
Filed Dec. 1965
C. S. File No. 54/16

141

Sec. Corner to Sections 25 - 26 - 35 - 36.
Found - Stumps of all Orig. BT's.
12" Madrone S. 36° E. 63.1 ft.
12" Fir N. 74° E. 22.1 ft. These BT's not FD used
14" Fir N. 8° W. 61.5 ft. by Haines'. By D. Peel
36" I. Cedar S. 71° W. 94.7 ft. 3-93 M 1175
Oct. 20, 1965 - Found Haines' "T" Iron & one BT:
12" Fir N. 74° E. 22.1 ft. Signed, V.R. Tracy.

RE-RENEWED CORNER NO. #186

(F.B. H-237 for info. in this area)

142

Sec. Corner to Sections 22 - 23 - 26 - 27.
Found - 60" Fir S. 25° E. 92 lks.
6" Fir Stub S. 17° W. 25 lks., scribing visible on stub.
Scribed: 14" Fir N. 60° W. 50.0 ft. - SEE REN. #144
36" Fir S. 89° W. 44.5 ft.
60" Fir S. 25° E. 60.72 ft. (bark scribed)
Nov. 8, 1965 - Found Haines' "T" Iron & following BT's:
14" Fir N. 60° W. 50.0 ft.
60" Fir Snag S. 25° E. 60.72 ft. Signed, V.R. Tracy

143

Sec. Cor. to Sections 20 - 21 - 28 - 29.
Found - 3" sq. cedar post burned off at ground level, with scribed.
Boyer's BT's, as recorded in Ren. #15 & Originals:
Orig. 10", now 17" W. Oak N. 18 3/4° W. 576.7 ft., prev. opened &
shows scribe. Alive, face rotting.
36", now 39" I. Cedar N. 14° E. 85.3 ft., scribe visible. Alive.
20", now 36" forked Ash, S. 54° E. 290.3 ft., shows faint scar, lies
in blackberry brush.
12", now 32" I. Cedar S. 81 1/2° W. 205.2 ft., rescribed by Cad. Eng.
Set - Brass Cap in N.-S. fence. mkd. County Surveyor's T 23 S R 4 W
Office S 20 | S 21
1966 S 29 | S 30
Note - While digging for brass cap, we find remnants of
cedar post with marks. Cad. Brass Cap bears N. 57 1/2° W.
31.5 ft. (to be removed in future.)
New BT: 9" I. Cedar N. 40° W. 40.2 ft. mkd. T23S R7W S20 CS BT.

Fd. Br. Cap.
R. L. Dolan
M100-32

Vernon "Ray" Tracy
Jack Heritage
Sept. 26, 1966
C. S. File No. 54/16

144

Sec. Cor. to Sections 22 - 23 - 26 - 27.
Found - Haines' "T" Iron & 3/4" I.P. at Cor. See Ren. #142.
Orig. 60", now 64" Fir S. 25° E. 60.7 ft. rebark scribed, Now Snag.
14", now 20" D. Fir N. 60° W. 50.0 ft., bark scribed, button on face.
36", now Stump, S. 89° W. 44.5 ft., bark scribed.
New BT's: 8" Hemlock N. 35° W. 22.8 ft. mkd. T23S R4W S22 CS BT.
14" Hemlock N. 14° E. 44.1 ft. mkd. T23S R4W S23 CS BT.
9" Hemlock S. 62° E. 63.7 ft. mkd. T23S R4W S26 CS BT.
DO NOT SET BRASS CAP. - Corner lies in corner of cut off unit in Sec. 27.