

Douglas County Surveyor's Record of
Government Corners Renewed

T 23 T. S. R 4 R.W.W.M.

MOSE-CHAPMAN CO., EUGENE, ORE. 21991

172

South
1/16 Corner for Secs. 8 and 9
Found - Old Ford top bow frame set by Boyer, C.S. 30/52, firmly set flush with the ground.
18" fir in N & S fence now 21" stump with good scar also scribed "SB" visible in small unhealed blaze, bears N.74°E., 18.5 ft. (Rec. 17.8 ft.)
Found no trace of blazed 12" tree 3 ft. south & 1 ft. west, however I did find badly rotted 14" fir stump N.18°E., 4.0 ft. No axe marks evident.
Set - At the location of fd. bow frame I set 1" x 30" I.P. with brass cap attached protruding 10" out of ground. Bow frame flush with ground at north edge of brass cap. Cap marked: "Douglas Co. Surveyor T23S S 1/16 S8 S9 R4W 1982".
New BTs - 14" fir scribed "S 1/16 S8 CS BT" in double blaze bears S.37 1/2°W., 44.4 ft.
13" fir scribed "S 1/16 S8 CS BT" in double blaze bears N.44°W., 12.0 ft.
9" fir scribed "S 1/16 S9 CS BT" in double blaze bears N.1°E., 22.0 ft.
8" fir scribed "S 1/16 S9 CS BT" in double blaze bears S.38°E., 9.7 ft.
Old fence cor. with fences running N-S-E and W bears East 17.7 ft. (note fences running North & West extend only a short dist.)
New BT tags on all trees. Sketch in C.S. file.

8/5/82

173

Section corner for Secs. 6 and 7; and Secs. 1 & 12, T.23-5
Found - County brass cap, properly marked, leaning to the west and protruding 14" out of the ground. Ren. #20 (measurements taken from the point the pipe enters the ground.)
Orig. 18" fir, now 27" windfall with scribed "R5 T23 S" visible in previously opened blaze bears west 83.7 ft. (rec. N.83°W., 101.0 ft.)
Orig. 12" fir, now 22" stump which had grown together with 56" fir (also stump) has scribed "S7 BT" visible on bark, bears S.58°E., 33.7 ft. (rec. S.68°E., 33.0 ft.) I open blaze and find scribed "23 BT" on partially rotted face.
Orig. 10" fir now 19" windfall with scribed "R 5W T 3" visible in previously opened blaze, bears S.49°W., 83.3 ft. (rec. S.62 1/2°W., 82.5 ft.)
8" fir now 16" with good scar bears N.72°W., 39.0 ft. (Rec. 42.7 ft.) Ren. #20
8" fir now 18" with good scar bears S.22°W., 28.4 ft. (rec. S.29°W 27.6 ft.) Ren. #20
12" fir now 22" with good scar bears N.82°E., 72.3 ft. (Rec. N.80 1/2°E.) Ren. #20
8" fir per Ren. #20 now 12" with good scar bears S.17°E., 47.2 ft. (Rec. S.15°E., 46.0 ft.)
Set - As per details outlined in attached narrative by Francis L. Ingram I set a 1" x 30" I.P. with brass cap attached marked "Douglas County Surveyor T23S R5W S1 S12 S6 S7 R4W 1982". Pipe protrudes 6" out of ground. Bearings & dists. to orig. BTs are as follows:
18" now 27" fir windfall bears N.83°W., 100.9 ft.
10" now 19" fir windfall bears S.62°W., 89.7 ft.
12" now 22" fir stump bears S.66 1/2°E., 46.6 ft.
I straighten monument set by Byron, Ren. #20, I also cut off brass cap and drove yellow plastic cap marked "Doug. Co. Surveyor" into top of the I.P. This monument bears N.52 1/2°W., 20.6 ft. from new brass cap.
New BTs - 8" fir per Ren. #20 now 16" with good scar bears N.65°W., 58.6 ft.
8" fir per Ren. #20 now 18" with good scar bears S.63°W., 30.0 ft.
12" fir, Ren. #20, now 22" with good scar bears N.62°E., 61.2 ft.
8" fir, Ren. #20, now 12" with good scar bears S.5°W., 33.2 ft. (note: this tree now stands in section 12 but is still scribed "R4W S7 CS BT" under healed over blaze.)
New BT tags put on all trees. Sketch and narrative in C.S. file.

8/5/82

Gregory Quibell
Deputy Doug. Co.
Surveyors Office
Karen Reed; John
Powell
Aug. 5, 1982
C.S. 62/1

Gregory Quibell, Deputy, Doug. Co. Surveyors Off.
Karen Reed
John Powell
August 5, 1982
C.S. 62/1