

Douglas County Surveyor's Record of
Government Corners Renewed

T 23

T. S. R 4

R. W. W. M.

FOX-CHAPMAN CO., EUGENE, ORE. 97401

184

1/4 Corner for Sections 25 and 26 See Ren. #103
 Found - Wilford Haines 3/4" T-iron with identification button on top of bar adjacent to original 1884 12" by 18" buried stone with faint markings on west face and the following accessories:
 Orig. 12" yew bears S.37°W., 10 ft. This is a 10 ft. tall burned decayed snag, no visible scribe.
 Orig. 50" DF bears N.44°E., 11.0 ft. Heavily decayed 4 ft. tall snag, no visible scribe.
 20" cedar stump, bears S.57°E., 22.7 ft. Well healed scar cut through with Weyco tag and "W" spike.
 16" D. fir stump bears N.60°W., 56.0 ft. Very low cut stump with no evidence remaining.
 10" Hemlock, bears S.27°W., 11.3 ft. I tagged this tree.
 Corner lies on a steep west facing slope, 30 ft. north of creek which flows northwest and approx. 100 ft. east of end of old logging road.

185

West 1/4 Corner Section 26
CORNER REPORT

Found - 1976 2 1/2" BLM brass cap with Wilford Haines 3/4" T-iron and identification button on top of bar and a 3/4" iron pipe and the following accessories: Ren. #145
 Orig. 24" D. fir, now a 42" bears N.85°W., 28.0 ft. Scribe marks on bark blaze, nearly grown over open blaze visible.
 Orig. 40" D. fir badly decayed and burned remains and stump hole bears S.45°E., 2.0 ft.
 27" incense cedar bears S.50°E., 26.5 ft. Well healed face and BLM tag.
 10" incense cedar bears N.55°W., 40.4 ft. visible scribing and BLM tag.
 12" incense cedar bears N.68°W., 23.1 ft. (Rec. Ren. #140 and 145 is S.68°E.) visible scribing and BLM tag

Corner lies on south facing ridge approx. 70 ft. below a wide flat bench and approx. 1150 ft. south of BLM gravel road.

186

Southeast Section Corner Sec. 26 Ren. #141

Found - 4x4" old burned, decayed cedar post lying next to point. Wilford Haines 3/4" T-iron and identification button on top of bar bears west 8.45 ft. I find the following accessories:
 Orig. 6" D. fir is now badly decayed, 20" root remains, bears S.40°E., 76.1 ft.
 Orig. 36" D. fir is now badly decayed, 40" root remains bears N.19°E., 104.5 ft.
 Orig. 48" D. fir is now badly decayed 50" 3 ft. tall snag remains, no marks visible, bears S.75°W., 115.1 ft.
 Orig. 36" D. fir is a burned decayed 34" IC stump, no marks visible bears N.5°W., 222.5 ft.
 Set - 5/8" x 36" iron rod with alum. cap 0.7 ft. above ground.
 New BTs - 10" hemlock bears N.64°W., 46.0 ft. Wyeco tag and "W" nail in base, I scribe S 26 BT and Tag.
 21" D. fir high stump bears N.52°E., 15.0 ft. Well healed scribe and old BT tag.
 29" D. fir bears N.19°W., 64.0 ft. to alum. nail in mid-base. I drive a 6" iron spike into well healed face and tag tree.
 10" hemlock bears S.65°W., 52.3 ft. Weyco tag and "W" nail, I scribe S 35 BT and tag tree.
 25" WRC bears S.62°E., 61.3 ft. to alum. nail at DBH I drive 6" spike in face and scribe S 36 BT and tag tree.

Corner lies on the edge of large bench, steep to the south with timber to the Southeast only.

187

South 1/4 Corner for Section 26
Set - 5/8" x 36" iron rod with alum. cap 0.5 ft. above ground and mark the following accessories:

Orig. 36" D. fir is a burned and decayed 16 ft. tall 36" snag with burned out face. Bears N.65°W., 39.6 ft.
 11.5" D. fir bears S.19°E., 4.57 ft. to alum. nail in mid-base. I scribe 1/4 S35 BT, drive a 6" spike in face and tag tree.
 14" D. fir bears N.38°E., 20.15 ft. to alum. nail in mid-base. I scribe 1/4 S36 BT, drive a 6" iron spike in face and tag tree

Ken Hoffine LS #2291
 For: Lone Rock Timber Company
 January, 1990
 M 109 - 56
 C.S. 63/106

5-21-93
 CONFLICT IN
 COUS SEE
 PEELS SURVEY
 M117-5