

Douglas County Surveyor's Record of
Government Corners Renewed

T 23

T. S.

R 4

R. W. W. M.

FORE-CHAPMAN CO., EUGENE, ORE., 21991

192

Sec. Cor. for 1 and 2; & 35 and 36 of T.22-4
Found - 12" R.Cedar, now a 12" stump 7 ft. high with Weyerhaeuser ;nail
& tag bears N.35°E., (Rec. N.32°E) 22.0 ft. Ren. No. 42
50" Fir now a 38" stump 5 ft. high with Weyerhaeuser nail and tag
bears S.77°E., 41.6 ft. (Rec. S.79°E., 39.9 ft.)
32" Cedar stump 4 ft. high with Weyerhaeuser nail < tag bears
S.1°E., 32.2 ft. (Rec. S.2°W., 31.4 ft.)
66" Fir now a stump 6 ft. high with Weyerhaeuser nail and tag bears
N.43½°W., 28.6 ft. (Rec. N.45°W.)

Set - A 1" x 36" Iron Pipe with brass cap marked "Douglas County Surveyor
T 22 S R 4 W

S 35	S 36
S 2	S 1
T 23 S	

1991

New Accessories:

- 4" Fir marked "X BT" on double blaze bears N.77°E., 40.5 ft.
- 5" I.Cedar marked "X BT" on double blaze bears S.3½°E., 43.6 ft.
- 7" Post, fence corner, fence runs south and West bears
S.68°W., 4.8 ft.

Monument set along northerly edge of power pole service road.

7/30/91

1/4 Corner for Sections 5 & 8. *FD OK BY D Edwards
7-96 M125-58*

Set - 5/8" iron rod with yellow plastic cap marked "Steven P. Ness
RPLS 811"

New Accessories -

- 13" D.Fir, S.69°05'E., 14.6 ft. scribed "¼ S8 BT"
- 13" D.Fir, S.24°12'E., 10.7 ft. scribed "¼ S8 BT"
- 11" D.Fir, N.61°12'W., 25.3 ft. scribed "¼ S8 BT"
- 13" D.Fir, N.26°23'W., 28.0 ft. scribed "¼ S8 BT"

8/12/92

1/4 Corner for Secs. 14 and 15

Found - 6" Fir, S.21°30'W., 14.32 ft.
1976 Brass cap.

Set 3 points on line:

- P.O.L. #1, hub and tack, N.89°01'30"W., 42.41 ft.
- P.O.L. #2, hub and tack, N.89°01.30"W., 61.24 ft.
- P.O.O. #3, hub and tack, N.89°01'30"W., 90.36 ft.

Removed brass cap for logging. After logging operation:

Reset original brass cap in its original position 42.41 ft. from P.O.L. #1.

No new BTs were set.

See sketch in C.S. File.

10/9/92

Center 1/4 Corner Sec. 6

Set - A sawed yew post (6" square), from which;
A Cedar, 18", bears S73½°W., 33 lks.
A Fir, 30", bears N.45°W., 42 lks.

Pg-11

1/4 Corner Secs. 6|5

Set a stone in place of old post.

Page 9

12/93

West 1/4 Corner for Section 24. CONDITION REPORT ONLY

Found - Haines T-Iron 0.7 ft. above ground. See renewal # 178
8" Hemlock bears N.88°E., 11.1 ft. 'x' carved in face, we tagged.
58" Fir stump bears N.65°E., 17.2 ft. has Haines button, no tag.
13" down and broken hemlock bears N.46°E. (tag shows N.52°E) 14.7
ft. scribing visible on standing base.
10" Yew bears N.24°W., 34.2 ft. vis. scribing in face with BLM tag.
36" Fir stump covered with tin cap bears S.88°W., 46.2 ft. to the
face, has Haines button. Bark scribed. We tag tree.

Note - Corner lies in gentle ground among reprod to the west and young
trees to the east.

Douglas County
Surveyors Office
Larry E. Monrean,
Deputy
S. Flause
T. Franssen
July 30, 1991
C.S. File 64/17

*FD.B.C.
10/92 D.Peck
M115-78*

Steven P. Ness
For: Springfield
Forest Prod.
August 12, 1992
C.S. 63/144

Larry Dolan L.S. 1076
For: swanson-Superior
Forest Products
Oct. 9, 1992
C.S. File 63/138

O.F. Thiel
1901/1909
C.S File 64/48

Ken Hoffine
For: Juniper Properties
August 1994
M120-66

193

194

195

196

197