

**Douglas County Surveyor's Record of
Government Corners Renewed**

23 T. S. 4 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 21881

203

1/4 Corner for Sections 28 & 33. See renewal # 156
 Found - 2 1/2" U.S.B.L.M. brass cap dated 1976.
 52" Fir snag, N.21°E., 34.1 ft. - closed face.
 record: N.15°E., 50 lks. - 1855 GLO
 10" Madrone, WEST 21.0 ft. to "W" nail - 1976 Weyerhaeuser Co.
 Set - 9" Fir, N.6°W., 39.8 ft. to "W" nail - scribed "1/4 S28 BT"
 6" Fir, N.77°W., 19.3 ft. to "W" nail - scribed "1/4 S28 BT"
 6" Fir, S.47°W., 9.5 ft. to "W" nail - scribed "1/4 S33 BT"

204

C 1/4 Sec. 32
 Set - 2 1/4" x 36" I.P. with 2 1/2" Brass cap dated 1994
 6" gate post, S.3°E., 11.8' to "W" nail - scribed "C1/4 B0"
 Power Pole, N.13°E., 173.1' to "W" nail
 14" Fir Stump, S.82 1/2°E., 138.5' to "W" nail - scribed "C1/4 T23S R4W S32 BT"
 12" Fir, N.84°W., 173.8' to "W" nail - scribed "C1/4 T23S R4W S32 BT"
 Metal Fence Post 1' North

205

1/4 Cor. Secs. 29 & 32
 Found - 2 1/2" U.S.B.L.M. Brass Cap dated 1976
 6" rotten fir stub, N.43°E., 22.1'. Rec. N.39 1/2°E., 43 lks, BLM
 8" Fir, S.6°W., 23.5', closed face. Rec. S.4 3/4°W., 36 lks, BLM
 Set - 15" Fir, N.42°E., 46.0' to "W" nail - scribed "1/4 S29 BT"
 12" W.Fir, S.83°E., 19.1' to "W" nail - scribed "1/4 S32 BT"
 9" Fir, N.4°W., 19.6' to "W" nail - scribed "1/4 S29 BT"

206

Secs. 31 & 32; 5 & 6 T24-4
 Found - DC Brass cap dated 1963 (Ren # 66)
 30" W.Oak log, N.70°W., 103.0'. - Down & out - Rec. N.70°W., 156
 lks, - 1855 GLO
 26" I.Cedar, S.41°W., 21.2' - Closed face - Rec. S.39°W., 21.4' -
 1963 Douglas Co.
 26" Fir, S.10°E., 34.9' - Closed face - Rec. S.10°E., 34.9' - 1963
 Douglas Co.
 Set - 15" Alder (in clump), N.5°E., 18.1' to "W" nail - bark scribed
 "T23S R4W S32 BT"
 10" Fir, N.73°W., 68.0' to "W" nail - scribed "T23S R4W S31 BT"

207

Center 1/4 Cor. Sec. 4
 Set - 5/8"x30" iron pin w/yellow plastic cap stamped "ROBERTS PLS 1039"
 6" Fir, N.25°E., 16.0' (scribed/painted red)
 6" Fir, S.62°W., 20.7' (scribed/painted red)
 8" Fir, N.86°W., 25.1' (scribed/painted red)
 12" Cedar, S.11°E., 9.7' (scribed/painted red)

208

Center 1/4 sec. 12
 Mon. Fd.- Haines "T" iron as per survey M26-80
 Bt's Fd.- 20" downed Fir, N.69°W., 17.5' (scar visible), 1963 B.T.
 New Bt's- 4" Fir, N.14°W., 21' (scribed/metal washer/painted red)
 5" Fir, N.42°E., 13.7' (scribed/metal washer/painted red)

see previous ren. #167

209

1/4 Cor. Secs. 4 & 9
 Found - See previous renewal #174 (C.S. File # 62/16-5) for found monuments & BTs
 Changes- 16" now 24" dia. D.Fir with a 5 ft. high fully healed single blaze and bark
 scribing "9 BT". Rec. S.60°W., 13.2 ft. (1928).
 14" now 22" dia. D.Fir with a 5 ft. high fully healed single blaze and 6 ft. high

Daniel Baker
 For: Weyerhaeuser Co.
 Sept. 1994
 M119-38

Dan Baker
 For: Weyerhaeuser Co.
 9/94
 M 119-40

Les Roberts
 June 1996
 M 125-29

Les Roberts
 Dec. 1997
 M 128-1

Douglas Co. Surveyor
 Office - Larry E.
 Monrean - Randall
 W. Smith - Stephen
 J. Flaue 12/15/97
 C.S File 64/78-44