

Douglas County Surveyor's Record of  
Government Corners Renewed

23 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

D.F. Thiel  
Co Surv.  
VOL 2 Pg 262

1/4 sec. cor. bet. secs. 5 and 8  
Set a bl. oak post from which;  
A fir 16 ins. diam. bears N 67 1/2° W 40 lks. distant  
A fir 20 ins. diam. bears S 36° E. 50 lks. distant. The S.W.  
bearing tree, is dead and very badly decayed but the  
original marks and plain by cutting. The W tree has  
been down years ago and stump badly decayed.  
June 29 1900 Present. Peterson and O D Thiel

16

1/4 Cor. 4 and 5  
Set 4" x 8" x 10" Rock. New witness tree  
Old witness tree  
S E tree, standing - S W tree stump  
A. W. Oak 8" S 19 1/4° W 8.36 chains.

17

1/16 Corner Section 16  
Set Iron Pipe N 89° 36' E 45.56' for 1/16 witness corner  
set by proportional measurement marked 20" Cedar bears S 42° W 54.6'  
4 1/2" Fir bears S 11° E 34.8 bark blazed

NOT IN T23/R5

Br 995  
June 18, 1885  
VOL 1 PG 61

James W. Byron, Deputy  
County Surveyor  
May 7, 1956.  
C. S. File 47/80.

Section corner to secs. 5, 6, 7 and 8.  
Found original Southeast BT down and badly burned. Near base found  
what appeared to be bottom of old blaze. No evidence of any other old oak  
near. Found base of old oak stump for Northeast bearing tree. I used  
these BTs to set corner as they check for bearings, distance and size.  
Set and iron pipe with Brass Cap at corner point marked 6 1/2 T 23 S.,  
R 5 W, County Surveyors office 1956.  
Blazed and scribed:  
18 inch R. Fir, S. 11° E., 46.0 feet, S 8 T23S, R5W, CS BT.  
18 inch W. Oak, S. 11 1/2° W., 79.0 feet, S 7 T23S, R5W, CS BT.  
14 inch B. Oak, N. 25° E., 72.9 feet, S 5, CS BT.  
No other trees near.

18

fd. 3/90  
C.S. 63/104  
FDOE  
3C 23 BT 19A  
Baker, Vol 100  
M 121-16  
V.R.T.

FOUND O.K 9/69 - C.S. 54/16

Section corner to secs. 9, 10, 15 and 16.  
Found original B. T. and chopped out scribe, a 24 inch Oak, S. 46° E., 71.60  
feet.  
Two other Oaks appear to fit for old B. T.s but show no sign of scars:  
30 inch Oak, N. 48 1/2° W., 81.2 feet. (O. B. T.)  
30 inch Oak, N. 75° E., 70.8 feet. (O. B. T.)  
At corner point set 3/4 inch x 30 inch iron rod from which:  
12 inch Fir bears N. 53° 30' W., 15.3 feet, scribed T 23 S, R 5 W., S 9  
R. E. 3561 B. T.  
18 inch B. Oak bears N. 37° 45' E., 11.7 feet scribed T 23 S, R 5 W., S 10  
R. E. 3561 B. T.  
7 inch Fir, bears S. 60° 30' E., 19.6 feet scribed T 23 S R 5 W., S 15  
R. E. 3561 B. T.  
5 inch W. Oak bears S. 9° 30' W., 31.2 feet scribed T 23 S, R 5 W., S 16  
R. E. 3561 B. T.

19

63

Gene E. Johnson  
January, 1957  
C. S. File No. 42/218.  
MAP FILE MS 70

Southeast corner D. L. C. No. 39.  
Found old Oak stump N. 68° E., 103 lks. and chopped out B.T. at butt.  
At corner point set 3/4 inch x 36 inch galvanized iron pipe,  
from which:  
7 inch Black Oak bears S. 86° 15' E., 36.0 feet, blazed and scribed  
D. L. C. 39, R. E. 3561 B. T. (new B. T.)

20

FD. PIPE  
7/79  
W. HAINES  
M 78-24

Northwest corner D. L. C. No. 45  
Found concrete block 5 inches x 8 inches x 12 inches buried 12 inches.  
Found Fir stump 24 inch, S. 20° W., 46 lks.  
Found Fir stump 22 inch, S. 48 1/2° E., 59 lks.  
Marked 6 inch Fir, S. 55° 30' E., 14.0 feet from concrete block, blazed and  
scribed D. L. C. 45 R.E. 3561 B.T.

21

FD. CONC. BLOCK  
7/79  
W. HAINES  
M 78-24

REN. #1