

Douglas County Surveyor's Record of
Government Corners Renewed

23 T. S. 5 R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 97106

Southwest corner D. L. C. No. 41.

22

Found:

O. B. T. stump N.52°E., 1 1/4 links.

Stump of line tree, West 13 lks. from corner.

Found Rock 8 inches x 10 inches x 12 inches, buried 16 inches.

Marked 2 new B. T.s:

9 inch Fir, N.48°W., 21.0 feet.

12 inch Fir, N.7°45'W., 33.1 feet.

Both of above trees blazed and scribed; D. L. C. 41, R. E. 3561 BT.

Gene E. Johnson
January, 1957
C. S. File No.
42/218.

MAP FILE MS-40

1/4 Corner between Section 20 & 29.

47

23

Volume 2
Page 264

Set Cedar post 4x4x3 ft. from which: R. Fir 12" bears N 16°12'E 39 lks.
(Old BTs. in evidence) R. Fir 18" bears S 23°14'W 73 lks.

Section Corner to Section 6, T23S R5W, and Secs. 31 & 32 T22S R5W.

24

Found - 8" now 19" R. Fir N.75°20'E. 228.4 ft. I open upper scar & find good scribing "W S". This recorded as renewed, 1901, by ring count. It was scribed about 1928. Also the tree was 12" when scribed (Record 8").

Also find rotted base of Fir that checks bearings & distance for N.W. BT. Find upper section of old rotted & scribed stake on ground.

No trace of Original BT's found.

Set Brass Cap at corner marked: S31/S32 T22S R5W County Surveyor's Office, 1958.
S6 T23S

New BT's: 10" R. Fir bears N.11°W. 8.5 ft. scribed S31 T22S R5W CS BT.

20" R. Fir bears N.74°E. 47.5 ft. scribed S32 T22S R5W CS BT.

10" R. Fir bears S.44°E. 36.0 ft. scribed S 6 T23S R5W CS BT.

Note - See Sketch in file for location of Brass Cap.

James W. Byron, Deputy County Surveyor
M. Godfrey
S. Blilow
March 4, 1958
C. S. File No. 49/59

North 1/4 Corner Section 6.

25

Found - Both Original Bearing Trees:

Orig. 16" now 34" B. O. S.89 1/2°E. 387.2 ft. This BT. rescribed about 25 years ago, I open back of this face & find good scribing on Original face.

Orig. 36" Fir now 40" rotted stump S.22 1/2°E. 708.4 ft. , good scribing visible on section of old face.

Set Brass Cap Marked: County Surveyor's Office, 1958. N. 1/4 S6 T23S R5W

New Bearing Tree: 3" W. O. Bears S.65°E. 49.2 ft. scribed 1/4 S6 CS BT.

No other trees near.

Found O.K. Feb. 1965 - BBR

Section Corner to Sections 17, 18, 19, & 20.

26

Found Old Bearing Trees:

40" Fir N.14°W. 11 lks. (dead)

16" Fir S.65°W. 100 lks. (gone)

12" Fir N.66 1/2°E. 8 1/2 lks. (down)

18" Fir S.84°E. 36 lks.

Set 1" x 1" x 36" T Iron with Brass Cap inscribed - Survey Point Wilford N. Haines #239.

Section Corner to Sections 16, 17, 20, & 21.

27

Found Old Bearing Trees:

30" Fir N.40°W. 18 lks. (Stump)

18" Fir S.55°W. 3 lks.

28" Fir N.50°E. 58 lks. (Stump)

20" Fir S.82 1/2°E. 20 lks.

Set 1" x 1" x 36" T Iron with Brass Cap inscribed - Survey Point Wilford N. Haines #239.

C.S. FILE NO. 48-8

FOR: WESTERN LIND & TIMBER CO.
FEB. 1959