

Douglas County Surveyor's Record of
Government Corners Renewed

23 T. S. 5 R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881


34

1/4 Section Corner to Sections 19
30

Found - 1 1/2" U Bar at Corner. No Orig. BT's. found.
Find Stump Holes that check species, bearing & distance for Orig. BT's. *For research 12/2/93 D.C. 50(30)*
Find now 30" Fir bears S59°E. 17.6 ft., I open & find good scribing "30", scribed 50 yrs. ago. *BT scribed by D.F. THIEL 1938 see C.S. 64/48 Pg 17*

Corner checks call top of ridge and is West of Sec. Cor. 19 | 20
New BT's: 30 | 29

20" R. Fir bears N.38°W. 47.1 ft. scribed 1/4 S19 CS BT.



35

1/4 Section Corner to Sections 17 and 20.

Found - Orig. 18", now 36" Fir Stump N.20°E. 68.6 ft., I open & find good scribing " "

Orig. 11", now 24" W. Oak S.24°W. 139.3 ft. I fall tree & look for scribing, none found, center rotted.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959

1/4 S17 T23S R5W
S20

New BT's: 15" R. Fir bears S.51 1/2°W. 45.0 ft. scribed 1/4 S20 CS BT.

26" R. Fir bears N. 2°W. 98.4 ft. scribed 1/4 S17 CS BT.

James W. Byron, Deputy County Surveyor
Milo Godfrey
Clete Putnam
November 3, 1959
C. S. File No. 49/42

36

Section Corner to Sections 18 | 17
19 | 20

Found - Original 40", now 50" Fir N.14°W. 7.3 ft., shows scribing "S" on old face.

Orig. 18", now 32" Fir S.84°E. 23.8 ft., shows old scars. I do not open. *Fd. 12/89 C.S. 63/04 #141 FD. OK 4/91 M 111-76*

Stump Holes that check bearings & distance for Orig. SW & NE BT's.

Also find Haines' angle Iron & Cap at Corner. *REN. #26*

New BT's: 8" W. Fir bears N.39 1/2°E. 13.9 ft. scribed S17 T23S R5W CS BT.

40" R. Fir bears S.84°W. 34.4 ft. scribed S19 T23S R5W CS BT.

37

Section Corner to Sections 8 | 9
17 | 16

Found - 3 Orig. BT's.:

Orig. 22", now 36" B. Oak N.46 1/4°W. 212.5 ft., shows good scar. I do not open.

Orig. 24", now 36" Y. Oak S.46 1/2°E. I find should be S.44 1/2°E. 279.2 ft. I open & find good scribing "16".

Orig. 18", now 36" W. Oak N.31 1/2°E. 101.0 ft., shows good scars. I do not open.


Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959 T23S S8 | S9 S17 | S16 R5W

New BT's: 12" R. Fir bears S. 31 1/2°E. 60.0 ft. scribed S16 T23S R5W CS BT.

12" R. Fir bears S.56 1/2°W. 103.8 ft. scribed S17 T23S R5W CS BT.

6" W. Oak bears N. 7°W. 72.0 ft. scribed S8 T23S R5W CS BT.

36" W. Oak (Orig.) N.31 1/2°E. 101.0 ft. scribed S9 T23S R5W CS BT.



38

Section Corner to Sections 19, 20, 29 and 30.

Found - Orig. 18", now 30" W. Oak S.56 1/4°E. 429.0 ft. Remains of Oak Tree checks record bearing from Cor. I find dist. to be 191.0 ft., record 221.1 ft. No scribing found.

Find 13"x9"x4" Stone with Cross on Top at Corner.

Set Brass Cap alongside Corner Stone Mkd: S19 | S20 T23S R5W
County Surveyor's Office, 1959 S30 | S29

New BT's: 18" R. Fir bears S.85°E. 64.6 ft. scribed S29 T23S R5W CS BT.

20" W. Oak bears N.80°E. 83.6 ft. scribed S20 T23S R5W CS BT.

8" W. Oak bears N.60°W. 140.0 ft. scribed S19 T23S R5W CS BT.

No trees near to S.W.

FD. OK 7/51
B. Shawar
M 90-1

