

Douglas County Surveyor's Record of
Government Corners Renewed

T 23 T. S. R 5 R.W.W.M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

(see Ren# 145)

99

L.E. Monrean
A.V. Cangie
4/22/75
C.S. 57/21

Section Corner for Sec. 31; and Sec. 36, T23-6; Sec. 1, T24-6
Sec. 6; T24-5

Found - USGLO brass cap properly marked and dated 1943.
From which:

- A 50" Fir stump with good scar bears N. 58°E., 43.0 ft.
(rec. N. 57 1/2°E., 39.6 ft.)
- A 38" Fir stump blazed, scribe rotted bears S. 59°E.,
83.8 ft. (rec. S. 62 1/2°E., 83.8 ft.)
- A 36" Fir stump blazed-some scribing visible, blazed
area mainly rotted. Bears S. 18°W., 119.8 ft.
(rec. S. 18 1/2°W., 116.8 ft.)
- A 48" Fir blown down blazed, bears N. 84 1/2°W., ft.
(rec. N. 83 1/2°W., 184.8) (distance indeterminate)

New BT's

- A 9" Fir bears N. 66°W., 30.3 ft. scribed T23S R6W
S36 CS BT
- A 30" Fir bears N. 85°E., 30.7 ft. scribed T23S R5W
S 31 CS BT
- A 16" Fir bears S. 7 1/2°E., 66.2 ft. scribed T24S R5W.,
S6 CS BT
Dist 67.50 @ -13° =
- A 10" Fir bears S. 57°W., 27.1 ft. scribed T24S R6W
S1 CS BT

Corner lies in wooded area (Madrone & Fir) is
located at intersection of fences running
Southerly, Easterly, and Westerly.

4/22/75

Section corner for Sections 4 and 5 only. North boundary

100

Found - 1959 County brass cap, out of ground, on edge of road stamped
County Surveyors Office, T22S R5W S5 S4 T23S 1959. Ren. #54

Orig. 18" now 38" Fir stump bears S. 58°E., 33.0 ft. scribed "R5W
T23S 4".

12" now 16" Red Fir, bears S. 45°E., 68.4 ft. (Rec. 89.4 ft) Tree
has good blaze, tagged

8" now 11" Red Fir, bears S. 16 1/2°W., 14.0 ft. (Rec. S19°W.) Tree
has good blaze, tagged.

Re-Set - Brass cap at section corner, cap stamped as noted. Corner lies on
edge of road. Set fence post and sign beside monument.

Mag. Dec. 20°E.

2/18/76

SE Corner DLC 46

101

Found - 1969 County Brass cap properly marked. Ren. #87

Cap is firmly in place.

Orig. 6" now 42" Black Oak, bears S. 4°E., 26.4 ft. (Rec. S. 7°E.)
Tree has good blaze, scribing visible "SE DLC 46 CS BT". Tree
is leaning southwesterly.

Orig. 40" Pine, now burned & rotted stump, bears S. 58°E., 41.6 ft.
No scribing found.

New BT - A White Oak, 32", bears N. 64°E., 181.0 ft. Tree double blazed and
scribed "SE DLC 46 CS BT".

Mag. Dec. 20°

2/19/76

Witness Corner for 1/4 Cor. Secs. 23 and 26.

102

Found - A 1" Iron pipe, firmly set in a N-S fence line, with brass cap
attached mkd: COUNTY SURVEYORS OFFICE W S23 T23S
1959 C S26 R5W

50' South to
1/4 Corner

From which: A 20" now 24" D. Fir, bears S. 71°W., 17.9 ft. well-healed.

This tree is dead and at the landowner's request, we fall this
tree leaving a four foot high stump. This tree is also the NW
bearing tree mkd. by Ben Irving in 1940 referring to the true
corner location. We do not find Irving's cor. monument or his
SW BT. REN #48

New BT - A 16" D. Fir, bears S. 66°W., 80.0 ft. scribed "WC 1/4 S23 CS BT"
in a double blaze. This tree has been girdled by beavers on the
NW and NE sides. Our lower blaze begins one foot above the ground.

8/25/76

L. E. Monrean, Surveyors Office

J. H. Cook
February, 1976
C.S. 59/8

Gary L. Langlitz
Mike Tompkins, Doug. Co. Surveyors
Witness: George White
Aug. 25, 1976
C.S. 59/18

3/77