

Douglas County Surveyor's Record of  
Government Corners Renewed

T 23 T. S. R 5 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97102

Karen Reed  
Frank C. Silagy  
Doug. Co. Surveyors  
Office  
July 17, 1979  
C.S. 60/34

SW Corner DLC #40 108  
Found - 5/8" I. Rod and large stone alongside. Stone measures  
12" x 14" x 24" (Orig.), 5/8" I. Rod set by Haines M34-46  
Yoncalla Cemetery. Ren. #106  
A 26" D. Fir, now 20" bears N.42°W., 14.7 ft. dist. visible scribing  
"BT" pitched over in a double blaze.  
A 32" D. Fir, now 24" stump, 3 ft. high, bears N.74°E., 11.4 ft.  
visible scribing "SWC DLC 40 BT" in double blaze.  
No New monument set.  
New BT - A 14" Madrone, scribed "SWC DLC 40 CS BT" in bark scribe bears  
N.34°W., 46.1 ft.  
Corner lies at SWC of cemetery and in North fence line of large clear pasture  
to the south.

RE-RECEIVED #123

7/17/79

Wilford Haines  
For: Mrs. Bertha  
Vance  
July 1979 M 78-24

SW Corner DLC #41 109  
Found - Rock 1 ft. under ground. Ren. #22  
Set - 5/8" Rebar alongside.

7/79

L.E. Monrean, Doug. County Surveyor Office  
Karen Reed - Stephen Flauser, Deputies  
Terrie Plouff - M. Shawn Means - Teresa Buley  
December 18, 1979  
C.S. 60/34


Section corner for Secs. 12 and 13; and 7 \* 18 of T.23-4 110  
Found - A 3/4" Iron rod protruding 10 in. above ground. Ren. #14  
An orig. 8" Redwood now a 22" diam., 2 ft. stump, bears S.84°W.,  
12.5 ft.  
An orig. 12" Fir, now a 32" diam., stump bears N.65°W., 27.1 ft. I  
chop out scar to find visible scribe "S12".  
An orig. 12" Fir, now a 26" stump, bears N.20°E., 16.5 ft.  
An orig. 12" Fir, now tipped out bears S.69°E., 25.1 ft.  
A 12" R. Fir, now a 12" diam., 35 ft. high snag, bears N.44°E.,  
27.7 ft. with visible scribe "T23S R4W S7 CS BT" in an unhealed  
double blaze. Ren. #30  
An 11" Cedar, now a 12" diam., 10 ft. high snag, bears N.78 1/2°W.,  
32.7 ft. with visible scribe "T23S R5W S12 CS BT" in an  
unhealed double blaze. Ren. #30  
(The two BT's from Ren. #30 were rec. as scribed "1/4 S7 CS BT  
and 1/4 S12 CS BT").  
A 7" W. Fir, now 13" with healed over double blaze bears N.33°W.,  
42.3 ft. Ren. #77  
A 7" W. Fir now 15" with healed over double blaze bears S.24°W.,  
50.3 ft. (Rec. 51.2 ft.) Ren. #77  
An 8" Fir, now 12" with well healed double blaze bears S.21°E.,  
101.6 ft. (Rec. S22°E., 102.5 ft.) Ren. #77  
Set - 1" x 36" I.P. with brass cap marked "Douglas County Surveyor"  
with 3/4" I.R. inside pipe. At  
same position as rod. T 23 S  
R S12 S 7 R  
5 S13 S18 4  
W 1979 W  
New BT - A 7" D. Fir scribed "T23S R4W S7 CS BT" in a double blaze bears  
N.71 1/2°E., 117.0 ft. dist.  
Located at fence corner Fence S & E.

12/18/79

Ron Quimby  
For: O.E. Kingzette  
May, 1981  
M 79 - 77

Section Cor. for Sec. 36; & S.31 T.23S R.4W, & S.6 T.24S R.4W, &  
S.1 T.24S R.5W. 111  
Set - 2 1/2 " Brass Cap on a 30" I.P. at proportionate distance  
marked as shown:

*Fd OK 11/2/80  
DCSO  
es. 6/11*



New Accessories:  
26" Alder bears N30°E, 75.3-ft., scribed "T 23 S R 4 W  
S 31 BT".  
14" W. Fir bears N16°W, 68.7-ft., scribed "T 23 S R 5 W  
S 36 BT".  
B.O. - 5/8" Iron Rod bears S45°E, 20.0-ft.  
B.O. - 5/8" Iron Rod bears S45°W, 20.0-ft.  
\* Note: Sec. Cor. bears 26.0-ft. South & 4.0-ft. West of fenceline