

Douglas County Surveyor's Record of
Government Corners Renewed

T 23 S T. S. R 5 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

O.F. Thiel
1901/1909
C.S. File 64/48 Pg 14

Cor. secs. 23, 24, 25, & 26
Set - Yew Post, along side of old one, from which;
A Fir, 30", bears N.62°E., 26 lks.

147

12/93

Daniel Baker Lg 1978
For: Weyerhaeuser Co.
12/28/93
M 118-43

Center 1/4 Cor. Sec. 7
Set - 2"x42" Iron pipe with Brass cap.
9" Madrone, M.28°E., 53.0'.
28" Cedar, S.13°E., 27.2'.
19" Fir, S.34°W., 35.6'.
20" Fir, N.29°W., 37.5'.

148

Daniel Baker
For: Weyerhaeuser Co.
3/15/94
M 118-60

1/4 Corner for Sections 18 & 19
Set - 2" x 42" Iron pipe with Brass cap marked: "T23S R5W 1/4
S18,S19 PLS 1978 1993"
BTs - 29" Fir, N.61°E., 18.6 ft.
28" Fir, N.39°E., 16.2 ft.
69" Fir, S.49°W., 26.5 ft.
11" Maple, S.74°W., 56.0 ft.
Note - 1" iron pipe with aluminum tag marked "for B.L.M. use only"
wrapped around it bears S.14°39'26"E., 10.14 ft.

149

FO OK 11/28/94 M119-51

Corner for Sections 17,18,19 & 20. See Renewal # 141.
Found - W. Haines "T" Bar and disk.
BTs found -
23" W.Fir, N.38½°E., 14.4 ft.(closed face).
23" Fir, S.34½°E., 26.5 ft. (Lone Rock tag, record S.34°W)
52" Fir, S.82½°W., 34.4 ft. (closed face, B.L.M. tag)
57" Fir, N.21-¾°W., 7.8 ft. (vis. scribe, B.L.M. tag)

150

Ken W. Hoffine
for Lone Rock Timber
Feb. 1994
M118-66

North 1/4 corner section 4
Fd. - BLM aluminum cap .2' above ground
BT's Fd-9", Douglas Fir high stump, bears S.35°E., 69.5', well healed
scar and BLM tag
10", Cedar, bears S.80°W., 58.0', destroyed by logging
New BT - 11", Cedar, bears S.30°W., 29.6', I scribe SC 1/4 S4 BT
corner lies on southwest slope, a south flowing creek bears west 10',
an old fence line bears east 10'.

151

Daniel Baker
For: Weyco
Nov. 1994
M 121-16

1/4 Corner Secs. 7 & 8
Set - 1½"x36" I.P. with 2½" Brass cap dated 1994, stamped:
T23S R5W
¼
S7|S8
PLS 1978
1994
11" Fir, N.50°W., 24.3', scribed "¼ S7 BT"
9" Fir, N.33°E., 23.5', scribed "¼ S8 BT"
12" Fir, S.66°E., 35.9', scribed "¼ S8 BT"
15" Fir, S.54°W., 7.1', scribed "¼ S7 BT"
6' aluminum post 1' north
Note - The following Douglas Co. Rd. #24 R/W monuments are provided
to assist in locating the corner position:
¾" rebar, N.39°W., 365' - "CRW PC"
5/8" rebar, N.37°W., 340' - "CRW PT"

152