

Douglas County Surveyor's Record of
Government Corners Renewed

23 T. S. 6 R. W. W. M.

J. W. Cole, C. S.
T. C. Sefton
W. MacFarlane
Witnesses
C.S. File 1/21

Ben P. Irvins, Deputy Co. Surveyor
N. E. Richardson
Fred Southwick
Witnesses
Sept. 18-19, 1930
C.S. File 37/1

Ben P. Irvins Deputy C. S.
N. E. Richardson
Fred Southwick
Witnesses
Oct. 4 1930
C.S. File 37/31

Wilford N. Haines - No. 239.
1954 and 1955.
Surveyed for Irvin Rice and The
Whipple Mill.
C. S. File No. 42/13.

1 COR. BETWEEN SECS 3 & 4
Renewed this corner from the original P.T. called for in Gov't field notes as N. 13° E. 23 lks. the other tree was missing but there was a hole in proper position where the tree had burned out. I irrected a mound of rocks for corner and marked new trees as follows:
A Red Fir 40" in dia., S. 79° W. 22.5 ft.
A Red Fir 40" in dia., S. 37½° E. 42.5 ft.

2 S. E. CORNER NORTH SIDE SEC. 6
Location identified from orig. P.T.s as follows:
RE-RENEWED, SEE CORNER NO. 11
14" Fir snag, S. 47° E. 22 lks. both scribed S. C. 3 S. P. T.
30" Fir S. 37° W. 75 lks.
Replaced 30" Fir, S. 3. 43. 6 C. S. P. T. Blazed and scribed
30" Fir S. 47° E. 29 lks. S. C. 3 S. P. T. Blazed and scribed
Set 4' x 36" Cedar post for corner.

3 S. E. BETWEEN SECS. 5 & 6
Location identified from orig. P.T.s as follows:
Scrip of C. B. T. S. 32° W. 27 lks. and 54" Fir S. 25° E. 8 lks.
RE-RENEWED, SEE CORNER NO. 12
Set 4' x 36" Cedar post for corner with cedar post 4" x 6" x 36"
Replaced and scribed orig. P.T. 54" Fir, S. 25° E. 8 lks. dist.
S. C. T. 233. R. 67. 55 C. S. P. T. Blazed and scribed 12"
doubt Hemlock S. 50° W. 119 lks. S. C. T. 233. R. 67. W. 356 C. S. P. T.

4 N. W. CORNER SEC. 6 Angle at East of NW cor.
Location identified from both orig. P.T.s as recorded in Govt. field notes dated 1887 as follows:
RE-RENEWED, SEE CORNER NO. 10
12" Fir (new) dia. 3.52° W. 35 lks.
Set a Cedar post 4" x 6" for corner
12" Fir, S. 60° W. 32 lks. blazed and scribed
S. T. 233. R. 77. S. 1 C. S. P. T.
20" Fir S. 65½° E. 60 lks. blazed and scribed
S. T. 233. R. 67. S. 6 C. S. P. T.

5 S. E. CORNER SEC. 6
Location identified from 4 original P.T.s as follows:
90" Fir, N. 12° E. 14 lks. scribed T. 233. R. 67. 55 C. S. P. T.
24" Fir, S. 70° E. 36 lks. scribed T. 233. R. 67. 55 C. S. P. T.
48" Fir S. 65° E. 89 lks. scribed T. 233. R. 67. 55 C. S. P. T.
RE-RENEWED, SEE CORNER NO. 14
Original notes describe this corner as
16" Fir, N. 12° E. 14 lks. 24" Fir, S. 33° W. 50 lks.
24" Fir, S. 20° E. 36 lks. 18" Fir, N. 30° W. 43 lks.
Set a Fir limb for corner 4" square 48" long. Scribed T. 233
38 on S. E. face R. 67. S. 7 on S. W. face S. 6 C. S. on N. W. face
& N. E. face
Reblazed all original P.T.s except snag. which I replaced
48" Fir, S. 65° E. 89 lks.

6 ¼ Section corner to secs. 6, T23S, R 6 W., and 1, T23S, R 7 W.
At point for corner I set a brass cap inscribed - Survey point - Wilford
N. Haines No. 239. (Set by proportional measurement).
From which
RE-RENEWED, SEE CORNER NO. #88
A 42" D. Fir, S. W., 139.5 feet.
A 42" D. Fir, N. E., 113.0 feet.

7 FD. OK 3-91 M 111-72
Section corner to Secs. 6 & 7, T23S, R6W., and 1 & 12, T23S, R7W.
Found old bearing trees.
Set and angle iron with brass cap at corner point inscribed - Survey point -
Wilford N. Haines # 239.

8 Closing corner to Sec. 6, T23S, R6W., and 1, T23S, R7W. on north
boundary of township.
RE-RENEWED, SEE CORNER NO. #89
At corner point I set an angle iron with brass cap inscribed - Survey
point - Wilford N. Haines - # 239.
(Corner set by proportionate measurement).
1956 Blm # CS 63/127 10/90