

Douglas County Surveyor's Record of  
Government Corners Renewed

T 23 T. S. R 6 R. W. W. M.

Center Corner to Section 18.  
Set 1"X 36" Angle Iron with Brass Cap.  
8" Fir N.15°E. 12.2 ft.  
6" Fir S.65°W. 26.3 ft.

29

1/4 Section Corner to Section 7 & 18.  
Set 1"X 36" Angle Iron with Brass Cap.  
Bearing Trees: 26" Fir N.06°E. 16.4 ft.  
20" Fir N.27°W. 45.0 ft.

30

Section Corner to Section 7,8,17,& 18.  
Set 1"X 36" Angle Iron with Brass Cap.  
Bearing Trees: 10" Fir N.34°30'W. 49.0 ft.  
16" Fir S.60°30'W. 20.0 ft.  
24" Fir S.52°E. 15.0 ft.  
14" Fir N.52°E. 11.5 ft.

31

see 1957 Blm Resurvey  
& CS 63/104

Wilford N. Haines  
Harold Woolley & F.G. Whipple  
Yoncalla Lumber Co.  
April, 1957  
R. M. 1 - 17

Center of Section 22.  
Set 1" x 1" x 36" T. Iron  
Scribed: 22" Fir N.57°E. 10.5 feet.  
26" Fir S.27°E. 16.5 feet.

32

FOR WOOLLEY  
LOGGING  
By W. Haines  
March 1961  
M 20 - 29

1/4 Corner to Sections 34 and 35.  
Found - Gov't Pipe, 2", with Brass Cap, out of ground,  
position for corner falls in fire trail.  
8" Fir Snag S.13°E. 31.0 ft. B.T. tag on snag.  
Snag faced off but never scribed.  
10" Fir Snag S.72°W. 79.9 ft. B.T. tag on snag.  
Snag faced off but never scribed.  
Reset -Brass Cap in Original Position. Pile Mound of Rocks  
around it.  
New BT's: 51" D. Fir S.40°E. 74.0 ft. Mkd: 1/4 S35 CS BT.  
8" W.Fir N.15°W. 96.0 ft. Mkd: 1/4 S34 CS BT.

33

Milo E.  
Godfrey &  
Crew  
Jan. 29, 1962  
C.S. File  
No. 52/102

1/4 Corner to Sections 13 and 24.  
Found - G.L.O. Brass Cap, Set in 1943  
45" Fir N.45°E. 82 lks. (down)  
18" Fir S.70°W. 65 lks. (down)  
Scribed new Trees: 10" Fir S.66°E. 6.5 ft.  
14" I.Cedar N.65°W. 122.8 ft. This tree  
on top of ridge on West side of cat road.

34

1/4 Corner to Sections 19 and 24.  
Found - G.L.O. Brass Cap, Set 1943.  
40" Fir S.33°E. 67 lks, down.  
36" Fir N.70°W. 144 lks. Pa. stump.  
Scribed New Trees: 14" Fir N.70°E. 40.6 ft.  
10" I. Cedar N. 2°W. 49.2 ft.

35

Wilford N. Haines  
For Yoncalla Lumber Co.  
August 1961  
Map File M 23 - 33

Center 1/4 Corner to Section 24.  
Drove Nail in a windfall.  
Scribed: 16" Fir S.68°E. 30.5 ft.  
5" Fir S. 9°W. 22.2 ft.  
Drove 1" x 1" x 36" T. Iron 1.0 ft. N.1°01'W. of Nail.  
Note: E. & W. Centerline calculation from transit & chain travers.  
S. Centerline by triangulation.  
No closure was made to either line.

36

RE-RENEWED

CORNER NO. #85

RE-RENEWED CORNER NO. #84

RE-RENEWED CORNER NO. #40