

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 23 S. T. S. R. 6 W. R. W. W. M.

KOIKE-CHAPMAN CO., EUGENE, ORE. 97501

50

Bruce R. Rogers  
Wm. Stoffel & M. Stone  
Feb. 1965  
C. S. File No. 51/101

Section Corner T 23 S | T 23 S  
R6W | R5W  
S 1/ S 6 SC 1943

Found - GLO Brass Cap at Corner as marked above:  
9" Fir, now stump, S. 29° E. 68.9 ft. - No trace of S. W. Tree.  
New BT's: 14" W. Fir S. 84° E. 93.0 ft. Mkd: T23S R5W S6 CS BT.  
7" D. Fir S. 70° W. 34.4 ft. Mkd: T23S R6W S1 CS BT.  
Note - Corner is at East-West-South Fence Corner.

CC

Section Corner T 22 S R6W | T22S R5W  
S 36 | S 31

Found - GLO Brass Cap at Corner Marked as above: 1943  
20" Fir, now stump, N. 56 1/2° W. 156.4 ft., scribing visible.  
Corner is 2 ft. south of E-W Fence.  
New BT's: 7" D. Fir N. 4° W. 26.0 ft. Mkd: CC T22S R6W S36 CS BT.  
6" Madrone N. 62° E. 22.5 ft. Mkd: CC T22S R5W S31 CS BT.

*Fd OK  
E. Bloom  
M100-25*

51

February 1965

Wilford N. Haines  
for Woolley Logging Co.  
Nov. 1964  
Map File M 30 - 51

1/4 Corner to Sections 14 and 15.  
Found - GLO Brass Cap in bed of Stream.  
S. E. BT. down.  
BT. N. 61° W. 35.6 ft. dead.  
Scribed: 22" D. Fir S. 74° W. 26.2 feet.  
22" D. Fir S. 06° E. 39.5 feet.

52

Center Section <sup>14</sup>  
Set - 1" x 1" x 36" T- Iron.  
Scribed - 15" D. Fir N. 86° W. 42.7 feet.  
22" D. Fir S. 58° E. 84.0 feet.

53

S. Center 1/16 Section 14.  
Set - 1" x 1" x 36" "T" Iron.  
Scribed : 40" D. Fir N. 66° W. 29.0 feet.  
26" D. Fir S. 21° E. 7.8 feet.

54

November 1964

Vernon "Ray"  
Tracy  
&  
Crew  
C.S. File  
No. 52/102

1/4 Corner to Sec. 32, T23-6W. & Sec. 5, T24-6W.  
Found - GLO Brass Cap mkd. 1957.  
16", now 18" W. Fir, S. 61° W. 52.8 ft., nearly healed blazes,  
partial scribe, marks visible.  
Orig. N. E. BT. is now stump.  
Orig. S. E. BT., turned out - Also 1957 N.W. BT.  
New BT's: 9" Hemlock S. 40 1/2° E. 30.8 ft. mkd. 1/4 S 5 CS BT.  
10" D. Fir N. 38° W. 86.5 ft. mkd. 1/4 S 32 CS BT.  
Note - Corner lies in old, logged-off unit.

55

Sept. 1, 1966

*Sept. 68*

MICROFILM TO HERE 10/67

56

Vernon "Ray" Tracy  
Jack Heritage & V. Perron  
C. S. File No. 49/143

Closing Corner to Sections 31 and 32, T.22S. R.6W.  
Found - 1955 Cadastral Brass Cap, nearly out of ground, properly  
marked with Haines' "T" Iron alongside. See Ren. #39,  
We Reset Brass Cap.  
Haines' BT's: 18" Fir N. 36 1/2° W. 45.4 ft. now dead-scribe visible -  
overgrowth of 9 rings.  
24" Fir stump N. 20° E. 48.1 ft. scribe visible.  
Orig. Cedar BT gone- stump hole & turned out tree to  
N.W. still in evidence-  
New BT: 12" Hemlock N. 6° W. 47.8 ft. mkd "T22S R6W S31 CC CS BT"  
No trees close to NE- This corner lies on very steep Northerly slope  
about 350 ft. South of Squaw Creek.  
12/23/69

**RE-REMOVED CORNER NO. #87**