

Douglas County Surveyor's Record of
Government Corners Renewed

T 23 T. S. R 6 R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

Wm. Eimstad for
Weyerhaeuser Co.
Woolley Logging
Whipple & Bovassa
M 53 - 35 *JAN 75*

Center 1/4 Sec. 2
Set - 5/8" Rebar
BT's - 6" Fir, N.2°W., 43.6 ft. scribed C 1/4 S2 BT
16" Fir, S.72°E., 45.5 ft. scribed C 1/4 S2 BT.

63
April 1974

L.E. Monrean
A.V. Cangie
4/22/75
C.S. 57/21

Section Corner for Secs. 35&36; and Secs. 1&2 of T24-6.
Found- 1943 USGLO Brass Cap properly marked.
From which;

- A 22" now 25" Fir bears N.62 1/2°E., 64.2ft.
- A (Rec 64.7) Good Blaze
- A 20" now 24" Fir bears S43 1/2°E., 17.2ft, good Blaze.
- A 30" Fir Stump bears S33 1/2°W., 20.2ft (rec. 21.1)
Part of Blaze remains
- A 30" now 35" Fir bears N24 1/2°W., 48.8ft (Rec N223°W.,
48.8ft) Good Blaze.

New BT - A D. Fir 11" Dia. bears S.68°W., 11.0ft. scribed T24S
R6W S2 CS BT.

April 22 1975

Section Corner for Sec. 36; and Sec. 31, T23-5; Sec. 1, T24-6;
Sec. 6, T24-5.

Found - USGLO Brass cap properly marked and dated 1943.

From Which:

- 50" Fir stump with good scar bears N.58°E., ft.
(rec. N.57 1/2E., 39.6 ft.)
- 38" Fir Stump Blazed, scribe rotted. Bears S.59°E.,
ft/ (Rec. S.62 1/2E., 83.8 ft.)
- 36" Fir Stump Blazed - Some scribing visible, blazed
area mainly rotted. Bears S.18°W., ft.
(rec. S 18 1/2°W., 116.8 ft.)
- 48" Fir Blown Down Blazed , Bears N.84 1/2°W., ft.
(rec. N.83 1/2°W., 184.8)

New BT's

- A 9" Fir bears N.66°W., 30.3 ft. scribed T23S R6W
S36 CS BT
- A 30" Fir bears N.85°E., 30.7 ft. scribed T23S R5W
S31 CS BT
- A 16" Fir bears S.71 1/2°E., 66.2 ft. scribed T24S R5W.,
S6 CS BT
Dist 67.50 @ -13°=
- A 10" Fir bears S.57°W., 27.1 ft. scribed T24S R6W
S1 CS BT

Corner Lies in wooded area (Madrone & Fir) is located
at intersection of fences running southerly, easterly,
and Westerly.

4/22/75

Gary L Langlitz
A Vic Cangie
James H. Cook
CS 57/39
12/31/75

1/4 Corn. Sec. 22 and 23
Found- Brass cap out of ground marked as described in 1957 resurvey.
8" now 13" d. fir bears S65°E., 19.8 ft. alive & blaze well healed. We open and
find scribe marks. N.W. BT destroyed by logging
N. BT's - 7" D fir which bears N45°W., 30.3ft. marked 1/4 S22 CSBT on a double
blaze. We reset cap as per 8" now 13" D fir BT and Stamped "CS 1975"
on cap. Compass declination 20° East 12/31/75

S 1/16 Sec. 22 and 23
Found- 2" IP firmly (1957 properly marked government resurvey) firmly set.
Orig. - 9" D. fir alive with scribing visible on unhealed blaze, bears N54°E.,
62.0 ft. (rec. N67 1/2°E., 62.) ft)
Orig. - 12" D. fir, now a 5 ft. tall snag, bears S 12°W., 50.9ft. (rec. S12°W.,
49.5 ft) Scribing visible.
New BT - 18" D. Fir bears N25°W., 79.3 ft., Scribed "S 1/16 S22 CS BT" on a double
blaze. Compass declination setting 20° East 12/31/75

65
66
67