

Douglas County Surveyor's Record of
Government Corners Renewed

T 23 T. S. R 6 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97501

78

C O N T - - -

(Sec. Cor. 26, 27, 34, 35)
Found - 46" dia. cedar snag. BT is burnt and no blazes or marks found bears S.34 3/4° W., 91.1 ft. (1957 BLM BT. agrees w/rec.)
29" now 36" dia. D. fir with a fully healed single blaze bears N.47 1/2° W., 208.6 ft. (1957 BLM BT. agrees w/rec)
34" now 48" dia. maple with a partially healed single blaze, scribing visible "6W S34" bears S.89° W., 128.8 ft. Ren. #41
34" now 28" dia. cedar with a fully healed double blaze bears S.30° E., 92.3 ft. Ren. #41
Witness post and sign along NE side of BC/IP per C.S. 57/17.
New BT - 8" alder double blazed and scribed "T23S R6W S26 CS BT" bears N.14° E., 16.3 ft.
Corner lies in creek bottom on south side of Yellow Creek approx. 175 ft.

4/13/87

1/4 Corner for Sec. 12; and Sec. 7 of T.23-5

79

Found - 2 1/2" dia. 1943 GLO brass cap on a 1" O.D. x 36" long iron pipe found loose at bottom of creek. 1943 D. resurvey.
8" now 14" dia. cedar with illegible scribe marks visible on a partially healed rotted blaze, we open further. No other marks found, ring count indicates blaze dates back to about 1943 GLO Dep. resurvey BT bears N.43° E., 21.2 ft. (Rec. N.44° E., 21.7 ft.)
14" fir bearing S.23° W., 34.3 ft. NOT FOUND.
Set - GLO BC/IP reset at record bearing and distance from 14" dia. cedar (S.44° W., 21.7 ft.) BC/IP now protrudes 7" above creek bottom. The marks "RESET 1990" are added to brass cap.
New BTs - 25" dia. D. fir double blazed and scribed "1/4 S12 CS BT" bears S.74 1/2° W., 29.3 ft.
13" dia. hemlock double blazed and scribed "1/4 S12 CS BT" bears N.32 1/2° W., 44.1 ft.
9" dia. Hemlock double blazed and scribed "1/4 S7 CS BT" bears S.83° E., 37.8 ft. Tree has a pistol butt; bearing and distance go to center of tree at bottom blaze.

4/24/90

80

1/4 Corner for Sections 16 and 21

Set - 2" alum. cap 0.7 ft. above ground on a 5/8" x 36" iron rod.
From which:

A Haines T-bar bears N.2° E., 5.16 ft. (Ren. No. 21)
BLM brass cap bears N.5° W., 22.14 ft.
55" D. fir bears S.46° E., 25.89 ft. with BLM tag referencing Haines T-bar, bark scribed, 1/4 S21. I tag with reference to my corner.
43" D. fir bears N.37° E., 32.44 ft. with BLM tag referencing Haines T-bar, bark scribed 1/4 S16 BT. I tag with reference to my corner.
9" D. fir bears N.62° W., 13.79 ft., I scribe 1/4 S16 BT and tag BT.
10" D. fir bears S.44° W., 25.71 ft. I scribe 1/4 S16 BT and tag tree.

Corner lies on small west sloping spur ridge on steep side slope approx. 40 ft. below flat bench in roots on downhill side of 5 ft D. fir which I put a location tag on.

8/90

~~S. 11/4~~
1/4 Corner for Section 1; and Section 6 of T.23-5

81

Found - Corner is a 1 1/2" iron post with brass cap. (1986 BLM, No record)
14" cedar bears N.52° W., 6.3 ft. well healed face and BLM BT tags. See Haines map M 48-3
32" cedar bears N.19 1/2° E., 25.3 ft. well healed face and BLM BT tag.

We paint faces and wrote BT on trunk of all BTs with flourescent orange paint. Corner sits on steep westerly slope 2 chaines west of bald knob. There is a BLM blazed line running south, and BLM boundary tags running west from corner.

6/90

Douglas County
Surveyors Office
Randall W. Smith
Terrie Franssen
April 13, 1987
C.S. 62/40

Book by
Laniel Baker
for water house
12/93 4118-43

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
April 24, 1990
C.S. 64/9

Ken Hoffine
L.S. #2291
For: Lone Rock
Timber Co.
M 110 - 53
August, 1990

Ken Hoffine LS.
#2291
Gary Angiolet
For: Lone Rock Timber
Co.
June 1990
C.S. 63/104