

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 23 S. T. S. R. 6 W. R. W. W. M.

PORE-CHAPMAN CO., EUGENE, ORE. 21891

Ken Hoffine  
For: Lone Rock  
Timber  
Aug. 1994  
M 120-79

N 1/4 Cor. Sec. 1 Only 105  
Found - GLO Brass Cap set in 1943  
Orig. D.Fir, now a 48" rotten stump, bears S.68°E., 42.0', no  
visible scribing.  
28" D.Fir stump, bears S.66°W., 24.4', with visible scribing.  
24" D.Fir, decayed stump, bears S.68°E., 70.0', no visible scribing  
8" D.Fir, bears S.20°W., 35.0', w/tag.  
Corner lies on flat approximately 50' East from foot of steep hill.

S 1/4 Cor. Sec. 36 only, T22-6 106  
Found - 2 1/2" GLO Brass Cap 2' below ground. Brass Cap is bent approximately  
0.3' NE.  
1 1/2" I.P. bears N.49°E., 1.9'. Orig. BT to I.P. bears N.10°E., 2.0',  
to chopped out face.  
46" D.Fir, stump, bears N.27°E., 4.8', to face chopped out,  
scribing visible.  
20" D.Fir, stump, bears N.54°W., 68.0', scribing visible.  
18" D.Fir, bears S.69°E., 18.5', I tagged & scribed 1/4 S36 BT.  
Corner lies on east edge of road grade fill slope.

Daniel Baker  
for Weyerhaeuser  
11/28/94  
M 119 - 51

sec. corner 12, 13, 7, & 18 T23 -5 107  
Monuments Fd. - 2" I.P. with GLO brass cap dated 1943  
Accessories Fd. - 30" fir, S.37 1/2°W. 70.4' - closed face  
rec: S.42°W. 109 lks. - 1943 GLO  
24" fir stump, N.46°W. 33.2' - closed face  
rec: N.50°W. 61 lks. - 1943 GLO  
10" fir, N.18°E. 43.5' - scribing visible  
rec: N.18°E. 67 lks. - 1994 BLM  
12" fir, S.10°E. 15.2' - scribing visible  
rec: S.10°E. 24 lks. - 1994 BLM  
6' metal fence post 1' north.