

Douglas County Surveyor's Record of  
Government Corners Renewed

23 T. S. 7 R. W. W. M.

ROBERT CHAPMAN CO., EUGENE, ORE. - BROS.

Set by  
GEO. C. BAKER  
Myrtle Creek  
Oregon.

Nov. 9-10 1925  
W. H. Woods, Dep Sur.  
W. S. Crear  
Chas. Smith  
J. Mode  
S. J. Anderson  
See Survey No. 3-26

Nov. 11 1925  
Survey No. 3-25  
Vol. 3 P. 233

July 25, 23 C.S. 8/29

July 24, 23 Feb. 29, 21  
C.S. Vol. 3, P. 895-90  
P. 820, P. 828

J. W. Cole, Dep. Surveyor  
J. W. Cole, C. S.  
C. Springer  
A. Mode  
J. Mode  
J. W. Woods, Dep.  
W. S. Crear  
Chas. Smith  
S. J. Anderson

Witnesses  
Alfred Haines  
Warren Cheever  
Arthur Mode  
July 24, 23  
Feb. 29, 21  
C.S. Vol. 3, P. 895-90  
P. 820, P. 828

1. **W. CORNER OF GEO. PAINE D.L.C. NO. 53**  
Reestablish corner from an original Oak B. T. 30" dia. chopped out scar and found scribe marks. Run N.65°W. 308.9 feet and set an iron binder shaft 1" x 50" also an oak post. An Ash down and rotten bears S.80°W. 132 ft. Mark a new tree an oak 12" S.86°30'W. 38.3 feet.  
*Should be D.L.C. No. 39, T 23-8 W. SEE CORNERS #26 + 27-T23-8*
2. **N.W. COR. OF GEO. PAINE D.L.C. NO. 53**  
Set this corner from tie given to sec cor. Put in an iron plow coulter also an Oak post and marked and Oak  
An Oak 24" dia. S.14°E. 104.5 ft.  
An Oak 24" dia. S.73°20'E. 112.5 ft.
3. **N.E. COR. PAINE CL. #53 - 12/1965 - NOT FOUND - TRACE 5/25/68**  
Set an iron bar 1" x 40" and a rock for cor. no trees near. Could find no trace of original tree. Located corner by measurements.
4. **Wit. Cor. to S.E. Cor. Paine Cl.**  
Set witness corner N.8°W. 100 ft. of true corner. Set iron pipe and 4" x 4" x 40" Oak stake from which  
An Oak 10" dia., bears S.66°E. 41 ft. *27 ft. 12/22/65 WAT*  
An Oak 12" dia., bears S.23°30'W. 40.0 ft. *125*
5. **SEC. COR. B.T. SEC. 16 & 17**  
Renewed ~~from~~ original B.T.s standing. *Tree* bearing scribe marks. Other trees not chopped open.  
Set 5/8" x 36" iron rod for corner. *56*
6. **SEC. COR. TO SEC'S 16-17-20-21**  
Renewed from fir. S.W. still standing but dead. Found stump of Oak N.W. and hole where Oak in N.E. other tree missing. Set cal. Iron pipe 5/8" x 48" from cor. Trees all dead nearby.
7. **CORNER BETWEEN SEC. 17-20**  
Set 3" x 24" Iron pipe. *SEE CORNER NO. 57*  
Find B.T.s in perishing condition, *one found and marks on other gone.* Set 4" x 4" x 15" oak stake flush with ground in school yard scribed 17-20 C. S. an mark  
A 12" Maple, bears S.11°W. 37 lks. S. 20 C.S. B.T.  
A 15" W. Oak, Bears N.11°W. 291 lks., S. 17 C.S. B.T.
8. **SEC. COR. 16-22-28-27**  
Set from old B.T.s See 3-26 for notes  
Red Fir 12", N.80°30'W. 79 lks. B.T. S.21 C.S. *FD 7/55 M 9/31*  
Oak 36", in dia., bears S.71°W. 149 lks. B.T. S.28 C.S.  
Oak 36" dia. S.75°E. 21 lks. B.T. S.27 C. S.  
Oak 30 dia. N.65°E. 77 lks. old tree
9. **CORNER SEC. 21-22**  
Stone 4" x 4" x 20" marked 1 sec. 21-22  
Red Fir 15" N.24°30'E. 39 lks. B.T. S.21 C.S.  
Oak 15" N.45°W. 39 lks. S. 21 C.S.
10. **MENADER COR. SEC. 21-22** *Left bank of river*  
Stone 4" x 4" x 20" marked 1 sec. 21-22  
Red Fir 10" S.7°15'W. 52 lks. B.T. S. 22 C.S.  
Red Fir 18", S.89°W. 39 lks. old tree
11. **SECTION CORNER COMMON TO SECTIONS 3-4-9-10.**  
Set a 2"x50" iron axle with gear on top 36" in ground. Found the original bearing trees as follows.  
24" W.Oak S.8°E. 75 lks.  
W.Oak N.75°E. 153 lks. (Down and rotting)  
W.Oak S.32°W. 64 lks. (Down and rotting)  
Marked new bearing trees as follows.  
24" Fir N.15°E. 39.2 ft. 10" Cedar N, 34°34'W. 42.0 ft.  
8" Fir S.67°15'E. 8.2 ft. 28" Fir S.48°40'W. 9.6 ft.