

Douglas County Surveyor's Record of  
Government Corners Renewed

23 T.S. 7 R.W.W.M.

MEANDER COR. P.E.T. 32-33 Left bank of river  
Reset per old B.T.s  
Set stake from which  
S. Fir 6" in dia. bears S. 35° W. 15 ft.  
R. Fir 5" in dia. bears N15° 30' E. 27.6 ft.

1-27-86  
Witnesses  
James Wolford  
P. D. Wolford  
A. Boyer  
Gene Richardson  
Edgar Madison

SEC. COR. 7-8-17-18  
Location identified from snag of original B.T. chopped out,  
scribe marks legible.  
Set 4" x 4" x 48" Fir post for corner from which  
S. Fir 15" diam., bears N. 48° E. 13.0 ft.  
S. Fir 12" diam., bears S. 75° W. 26.2 ft.  
S. Fir 8" diam., bears S. 40° W. 41.0 ft. (slope)  
S. Fir 14" diam., bears S. 15° E. 21.0 ft. (slope)

Witnesses  
M. T. Irvine  
D. S. S.  
N. E. Richardson  
Loren Weber  
Feb. 1940  
7.16 E. 55

SEC. COR. 22/27  
Location identified from old hub in fence corner and stump  
of O.P.T. as recorded in orig. field notes N. 65° W. 55 lks.  
bearing scribe marks. Set sandstone 3" x 6" x 18" long for  
corner chisled X on top and 1/3 on E. face C.S. on West face.  
New B.T.s W. Oak 14" dia., bears S. 85° W. 117 lks. dist.  
blazed & scribed 1/3. 27 C.S. B.T.  
S. Fir 36" in dia., bears N. 70° W. 130 lks. dist., blazed  
& scribed 1/3. 22 C.S. B.T.

Witnesses  
M. T. Irvine  
W. E. Holcomb  
Kenische  
Sept. 9, 1929

W. 1/163 22/27  
Drove 1 1/2" x 48" pipe 44" in ground midway between 1/4 cor 22/27  
and sec. cor 21-22-28-27 post along side scribed W. 1/163.  
C.S. 3.27 - 322  
28" fir, bears N. 2° E. 23 lks. dist., scribed & blazed  
W. 1/163. 223. 22 C.S. B.T.  
24" fir, bears S. 82 1/2° W. 12 lks. dist., blazed &  
scribed W. 1/163. 27 C.S. B.T.

Witnesses  
M. T. Irvine  
W. E. Holcomb  
Kenische  
Sept. 9, 1929

S.E. EXT COR. D.L.C. #46  
A 60" Oak tree - probably orig. corner at it check bearing a  
and distance from Sec. Pine and int. cor. Drove pipe along-  
side to N.T.  
New B.T.s 28" fir, bears N. 55° W. 59 lks. Blazed & scribed  
Cl 46, C.S. B.T.  
60" Fir, N. 35° E. 16 lks., Blazed & Scribed C. 46 C.S.  
B.T.

Witnesses  
M. T. Irvine  
W. E. Holcomb  
Kenische  
Sept. 9, 1929

N.E. COR. D.L.C. #46  
Set this corner from S.E. Ext. Cor. Cl. 46 & Sec. Cor. Drove  
2" x 42" pipe 32" in ground for corner Set 3" sq. post along  
side scribed N.E. Cl. 46 C.S.  
New B.T.s 36" fir, S. 30° W. 87 lks. Blazed & scribed N.E. cl.  
46 C.S. B.T.  
30" Fir, S. 40° E. 33 lks. Blazed & scribed N.E. Cl. 46  
C.S. B.T.

Witnesses  
M. T. Irvine  
W. E. Holcomb  
Kenische  
Sept. 9, 1929

INT. COR. D.L.C. #46  
Set 6" x 6" x 18" sandstone chisled Cl. 46 C.S. on N.W. face  
12" in ground for corner from orig. B.T.s As they are in  
good condition reblazed and scribe Cl. 46 C.S. B.T.

Witnesses  
M. T. Irvine  
W. E. Holcomb  
Kenische  
Sept. 9, 1929

C.C. SEC. 4 and 5 on Twp Line PIPE IN N. 45. FENCE 21 FT. S. OF FENCE COR. E. W. 45.  
Determined by O.B.T. - A. B. O. Stump hole bears S 13° E, 94.0 ft. dist.  
At corner point set 1" x 24" iron pipe from which  
A B. O. 7 ins. diam. bears S 46° W 23.0 ft. dist. marked S 5, B. T.  
A Laurel 9 ins. diam. bears N 87° E, 63.5 ft. dist. marked S 4, B.T.

Witnesses  
M. T. Irvine  
W. E. Holcomb  
Kenische  
Sept. 9, 1929

STANDARD CORNER  
SEC. 3 and 4 on Twp line (SEE M18-33)  
Determined by O. B. T. - A Fir 36 ins. diam. bears S 28° W 18.0 ft. dist.;  
I chopped out this B. T. and found scribe  
At corner point set 1" x 24" iron pipe, from which  
A Laurel 24" diam. bears S 47° W, 63.0 ft. dist. marked S 4, B. T.  
A Fir 20" diam. bears S 26° E, 55.0 ft. dist. marked S 3, 2880, B. T.

Witnesses  
M. T. Irvine  
W. E. Holcomb  
Kenische  
Sept. 9, 1929

1-27-86  
Witnesses  
James Wolford  
P. D. Wolford  
A. Boyer  
Gene Richardson  
Edgar Madison  
M. T. Irvine  
D. S. S.  
N. E. Richardson  
Loren Weber  
Feb. 1940  
7.16 E. 55  
Sept. 9, 1929  
John H. Markham, Jr. - Engineer  
Witnesses: Geo. & Wm. Vaughn  
Bob Blair  
March 31, 1951