

Douglas County Surveyor's Record of  
Government Corners Renewed

23 T. S. 7 R. W. W. M.

Ben P. Irving  
Dec. 12, 1913  
Frank Ceira  
D.S.S.  
H. E. Richardson  
V. K. Polcomb  
Kensche  
8-9-25  
Vol. 3, Pg. 299

July 9, 1938  
P. E. Irving  
M. E. Richardson  
S. A. Wade  
C. C. Sparke  
Witnesses  
Cs 15/11

R. C. Grant  
Sur.  
G. E. Johnson  
E. J. Madison  
Wit.  
Oct. 13, 1952  
Drawer 41  
Envelope 109

F. B. 33  
Pg. 22  
F. B. 33  
Pg. 23

COR. 27/28  
Location identified from Oak B.T. dead and rotting. Scribe  
marked in good condition.  
Set 4" x 4" x 24" sandstone 12" in ground for corner. Chisled  
X on top 28 on W. Face & 27 on E. face.  
New B.T.s 24" white Fir, N. 16° E. 24 lks. Blazed and scribed  
27 27° 00' S. P.T.  
24" Red Fir, N. 67° W. 37 lks., blazed and scribed  
28 28° 00' S. P.T.

**RE-NEWED SEE CORNER NO. #131**

COR. SECS. 34-35-2-3 T. 23&24 S.R. 7W. 1961 Govt. BRASS CAP  
Sandstone 6" x 13" x 21" marked with X on top  
B. Oak 20" marked C.S. Sec. 35. N. 49° E. 176 lks.  
Fir 30" marked C.S. Sec. 35. N. 83° E. 130 lks.  
No other trees N. Book 33

SEE VOL. 31  
Pg. 130/11  
FD 04-52  
7180

N.E. COR. D.L.C. 38 J. B. Goff - SET POST JAN. 1966  
20" B. Oak N. 30° W. 470 lks.  
4" W. Oak N. 43° 17' W. 438 lks.

SEARCHED FOR  
NOT FOUND

S.N. COR. D.L.C. 38  
Fir 30" N. 53° 20' W. 38 lks.  
Fir 20" S. 15° E. 35 lks.  
Sandstone 2" x 10" x 24" marked X.

VRToney  
Jef  
a.s. 52/125

N.E. CORNER OF ZIRA DIMICK D.L.C. # 45  
Location identified from both original P.T. as described in  
the original Govt. field notes Trees dead & deteriorating  
rapidly.  
Drove 1" x 24" drift pin flush with ground for corner &  
1" x 20" pipe 10" in ground alongside for mark., from which  
B. O. 16", bears E 15 lks. & W.O. 15", bears S. 45° W.  
57 lks. both blazed & scribed D.L.C. 45, C.S. P.T.

**RE-NEWED SEE CORNER NO. 124**

Sec. 32  
set 3/4" I.P., 3' long, set from stump of O. B. T. (Fir with scribes  
visible) S 45° W, 50 lk's  
Marked new B.T., a 9" Oak N 8° W, 136.2'. There was no other trees  
available.

**RE-NEWED SEE CORNER NO. #74**

1/4 Corner on North Side Section 5.  
Reset Stone 5x8x16 inches from which B. Oak 12" bears S 71° 43' W 13 lks.  
(Old B.T's in evidence) B. Oak 10" bears S 72° 27' E 24 lks.

**RE-NEWED SEE CORNER NO. #183**

1/4 Corner North Boundary Section 6.  
Set Post 4x4x3 from which: W. Oak 16" bears S 7° 00' W 120 lks.  
W. Oak 8" bears S 20° 05' E 197 lks.

**RE-NEWED SEE CORNER NO. #100**

Volume 2  
Page 265

3/97  
JAN 75

27-A