

Douglas County Surveyor's Record of
Government Corners Renewed

23 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97195

35

SW COR. SEC. 36

Found 16" Fir snag with scribe visible.
" 31" W. Fir with old BT bears
Set a 4" x 4" cedar stake for corner

RE-RENEWED SEE CORNER NO. 34

1/4 COR. 35-36

Found 28" Fir scribe markings burned off
" Cedar windfall with scribe visible
Set 3" x 4" Fir limb for corner stake

36

SEC. COR. 25-26-35-36 ??

Found Fir BT (now 36") S 55° E 39 lks.
" 18" Windfall Fir with old marks
" Rest destroyed by old fire
Set 4" x 4" Cedar stake for the corner.

37

1/4 COR. 25-36

Found both BT's.
" Fir, South 6 lks. has 2s inscribed on bark
" Fir, North 20° E for 36 lks is a windfall, scribe found
Set 3" x 4" Fir stake for 1/4 cor.

RE-RENEWED SEE CORNER NO. 181 38

SOUTH 1/4 COR. SEC. 36 SEE VOL 51 Pg. 19543 FOR ERRONEOUS POSITION INFORMATION

Found Fir BT marked 1/4 S B T on bark
Set 3" x 3 1/2" Cedar stake for 1/4 cor.

39

SEC. COR. 26-27-34-35

Found the Cedar B T scribe visible.
Set 3" x 4" yew post for corner.

40

1/4 COR. 35-26

Found both Fir B T 'S.
Set 3" x 4" Fir stake for corner

41

1/4 COR. 25-26

Found both BT's.
" Maple with grown over face
" Dogwood marked 1/4 S
Set 3" x 4" White Fir stake

RE-RENEWED SEE CORNER NO. #111 42

1/4 COR. 23-26

Found the 20" Fir and the scribe
Set 2" x 2" Hazel stake for 1/4 corner

RE-RENEWED SEE CORNER NO. 88 43

SEC. COR. 23-24-25-26

Two standing Fir BT's found, one with scribe visible
The large 48" Fir BT is now a windfall
Set a 2" x 4" Stake for Sec. Corner.

44

Section corner to secs. 20, 21, 28 & 29.

Found: Stump of the original NW BT now 26" bearing N.18°W., 59.4 feet. The lower part of the blaze after sawing out plainly showing the marks B. T. The upper part of the blaze is rotted away.

Set 5/8 inch iron rod and a treated 2 x 4 post scribed S21 on NE face and S20 on NW face.

Mark new a White Oak, 10" (South one of twins), N.11°W., 10.5 feet, scribed S20 on upper blaze and BT on lower blaze.

A White Oak, 10" diam., bears (S.88°W), 72 feet scribed S28 on upper blaze and BT on lower blaze.

RE-RENEWED SEE CORNER NO. #163
MAP SHOWS SE - PD TO BE SE - SEE BLM NOTES 5/11/50 SUPPLY 1" ED. REPORT IN C.S. 61/6-1/16/80

1/4 sec. corner to secs. 21 and 28.

After long and diligent search, no trace of corner or BTs can be found. At proportionate distance, I set stone marked 1/4 and 5/8" iron rod and treated 2" x 4" post scribed S21 on North and S28 on S faces, from which I mark new trees:

Fir, 6 inches, S.6 1/2°E., 24.5 feet mkd. S28 BT, one blaze.
Fir, 30 inches, N.1°W., 46.0 feet, S21 BT, one low blaze.

RE-RENEWED SEE CORNER NO. #169 46

Corners found and recorded by Claude Kerr, Regn. Engr. 2125
Recorded in Surv. Office March 1949

See File 40/190
40/190

Francis E. Waggoner
For Puget Timber Co. of Oregon.
July 6, 1955. (Date Completed)
C. S. File No. 42/L. M 9-31