

Douglas County Surveyor's Record of  
Government Corners Renewed

23 T. S. 7 R. W. W. M.

Francis E. Waggoner  
For Puget Timber Co.  
Completed July 6, 1955.  
C.S. File 42/1.

$\frac{1}{4}$  section corner to secs. 20 and 21.  
After diligent search, I am unable to find any trace of  $\frac{1}{4}$  corner or BTs,  
at proportionate point:  
Set  $\frac{5}{8}$  inch iron rod, treated 2"x4"x4' post  $\frac{1}{4}$ S from which:  
10 inch Fir bears N.47°10'E., 59.7 ft.  $\frac{1}{4}$  S21 BT on blaze.

47

Wilford N. Haines  
Survey for Irvin Rice and The Whipple Mill  
1954 and 1955.  
C. S. File No. 42/13.

Closing corner to Sec. 1, T 23 S, R 7 W., and Sec. 6, T 23 S, R 6 W.  
Corner set by proportionate measurement.  
At point for corner I set an angle iron with brass cap inscribed - Survey point - Wilford N. Haines No. 239.  
1956 Blm # C.S. 43/127 10/90

48

$\frac{1}{4}$  sec. corner to sec. 1, T 23 S, R 7 W., and sec. 6, T 23 S, R 6 W.  
At point for corner I set a brass cap on an angle iron inscribed - Survey point - Wilford N. Haines. (Corner set by proportionate measurement).  
From which marked two trees:  
A 42 inch D. Fir, S. W., 139.5 feet.  
A 42 inch D. Fir, N. E., 113.0 feet.

49

Section corner to Secs. 1 & 12, T 23 S, R 7 W., and Secs. 6 & 7, T23 S, R6W.  
Found old bearing trees.  
At point for corner set an angle iron with brass cap inscribed - Survey point - Wilford N. Haines No. 239.  
FD. OK 3-91 M 111-72

50

James W. Byron, Deputy  
County Surveyor.  
April 23, 1956.  
C. S. File No. 47/142.

$\frac{1}{4}$  corner to sec. 31, T23S, R7W., and sec. 36, T23S, R8W.  
Found old sq. stake on ground under 3 foot log-checks bearings and distance to original BT, S.60°E., 16.5 feet, now snag & rotted-found "BT" scribed at base. The West BT is down and partly burned-no scribing visible-checks bearing and distance to stump.  
Set an iron pipe with brass cap at north edge of log mkd. County Surveyors Office, 1956,  $\frac{1}{4}$  S R8 R7 T23S.  
36 | 31  
From which:  
12 inch Fir bears N.37°W., 18.0 feet scribed  $\frac{1}{4}$  S 36 CS BT.  
6 inch Fir bears S.52°E., 16.8 feet scribed  $\frac{1}{4}$  S 31 CS BT.

51

Wilford N. Haines  
December, 1955.  
C. S. File No. 42/84.

$\frac{1}{4}$  corner to secs. 3 and 4.  
Location of corner established by proportional measurement.  
Set a 36 inch angle iron with a brass cap marked: Survey point - Wilford N. Haines.  
From which:  
A 16 inch Fir, S.32°35'W., 43.2 feet.  
A 14 inch Fir, N.73°30'E., 44.6 feet.

52

James W. Byron, Dep. Co. Surv.  
M. Godfrey  
S. Bilow  
Dec. 19, 1957  
C. S. File No. 49/49

Section Corner to Sections 30 & 31, T23S R7W, & Secs. 25 & 36, T23S R8W.  
Found: Original 10", now 24" Fir Snag N.67°W. 64.7 ft. Open face, good scribing.  
Orig. 10", now 24" Fir Snag S.50°W. 85.8 ft. I open & find good scribing.  
Find what may be Orig. 12" now 30" Fir N.4°E. 104.3 ft. Shows old scar. I do not open. I Find Rotted Stump for Orig. S.E. BT.  
Set Brass Cap at Corner marked S25 | S30 T23S County Surveyor's Office, 1957  
R8W | S36 | S31 R7W  
New BTs: 7"R. Fir bears S45°E. 16.6 ft. scribed T23S R7W S31 CS BT.  
8"R. Fir bears S32°W. 9.2 ft. scribed T23S R7W S30 CS BT.  
10"R. Fir bears N.43 $\frac{1}{2}$ °E. 13.6 ft. scribed T23S R7W S30 CS BT.  
6"R. Fir bears N.67°W. 11.2 ft. scribed T23S R8W S25 CS BT.

53

(Also see earlier establishment by J. Phillips)

Fd. by: DON BEATZ  
3/83

M 90-38  
AEB