

Douglas County Surveyor's Record of  
Government Corners Renewed

23 T. S. 7 R. W. W. M.

Section Corner to Sections 3, 4, 9, & 10. 54  
 Found- 1" Iron Axle Gear on top at Corner. REN.#11  
 24" W. Oak, Orig., now shows old face, now rotted, no  
 scribing visible N.8°E 49.5 ft.  
 All of Baker's BT's now snags or stumps. All check for  
 bearing & distance & all show scribing.  
 New BT's: 14" W.Fir bears N.69°W. 45.0 ft. scribed S4 T23S R7W CS BT.  
 12" Myrtle " N.24°E. 73.3 ft. scribed S3 T23S R7W CS BT.  
 16" R.Fir bears S51½°W. 48.0 ft. scribed S9 T23S R7W CS BT.  
 36" W.Oak bears S. 8°E. 50.5 ft. scribed S10 T23S R7W CS BT.

James W. Byron  
 M. Godfrey  
 S. Blow  
 June 4, 1958  
 C. S. File No. 49/49

Corner of Section 1 & 2 on North boundary. 55  
 Set from Original B.T.'s.  
 Set 1"x 1"x 36" Iron Rod with Brass Cap inscribed,  
 "Wilford N. Haines #239 Survey Point"  
 -----  
 Corner of Sections 2 & 3 on North Boundary. 55-A  
 Set 1"x 1"x 36" Iron Rod with Brass Cap inscribed,  
 "Wilford N. Haines #239 Survey Point".  
 Found S. W. BT.  
 10" Fir S.65°E. 29.5 ft.

Wilford N. Haines  
 For E. G. Whipple  
 October, 1957  
 Map File M 1 - 59  
 C.S. File # 42/309

¼ Section Corner to Sections 16, & 17. 56  
 Found - 5/8" Iron Rod at Corner. REN.#5  
 Original 23", now 36" W. Oak N.51°E. 87.1 ft. I open &  
 find good scribing "½S".  
 Parts of rotted Stump that checks Orig. N. W. BT.  
 Set Brass Cap alongside of Iron Rod Mkd: ¼ S17/S16 County Surveyor's  
 T23S R7W Office, 1958  
 New BT's: 42" R.Fir bears S.30°W. 28.6 ft. scribed ¼ S17 CS BT.  
 24" R.Fir bears S.35½°E. 22.0 ft. scribed ¼ S16 CS BT.

James W. Byron, Deputy  
 Milo Godfrey  
 S. A. Blow  
 September, 1958  
 C.S. File No. 49/49

¼ Section Corner to Sections 17 & 20. 57  
 Found - Both BT's as recorded by B.B.I. 1938 & also 3" Iron  
 Pipe at Corner. REN.#7  
 12", now 24" Maple shows good scar. I do not open. S11°W. 24.4'.  
 15", now 22" Dead Oak N.11°W. 192.1 ft. I open & find  
 good scribing.  
 Set Brass Cap alongside ¼" Iron Pipe & Mark Cap ¼ S17 T23S R7W  
 County Surveyor's Office, 1958 S20  
 New BT: 27" W.Oak bears N.82½°E. 113.0 ft. scribed ¼ S17 CS BT.

Section Corner to Sections 14, 15, 22, & 23. 58  
 Found - 24" B. Oak N.33°W. 114 lks. Lot Markers for this  
 Set Lot Marker & Scribed: cor. & ones following:  
 20" Fir N.48°E. 13.8 ft. 1"x1"x36" Iron with cap  
 6" W. Oak N. 08°W 5.7 ft. inscribed, survey pt.,  
 Wilford N. Haines #239.

¼ Section Corner to Sections 14 & 23. 59  
 Set Lot Marker as described above.  
 Scribed - 36" Fir S.33°E. 16.8 ft.  
 20" Fir N.33°W. 8.6 ft.

Haines field Book  
 says N33°20'E 8.6 FT  
 (MAP says NW)  
 5/100 OR

Section Corner to Sections 13, 14, 23, & 24. 60  
 Set Lot Marker as described above, from old BT's.  
 Scribed new BT's: 12" Fir N.12°30'W. 19.8 ft.  
 7" Fir N.82°15'E. 17.2 ft.

Wilford N. Haines  
 For E. G. Whipple Mill  
 Filed Jan. 15, 1959  
 Map File M 13 - 64

¼ Section Corner to Sections 13 & 14. 61  
 Found - Old BT's.(down) - Set Lot Marker as described above. -  
 Scribed - Yew Tree S. W.  
 Hemlock S. E.

RE-RENEWED, SEE CORNER NO. 144

RE-RENEWED, SEE CORNER NO. 176

RE-RENEWED, SEE CORNER NO. 143