

Douglas County Surveyor's Record of
Government Corners Renewed

T. 23 S. T. S. R. 7 W. R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 21881

123

S. W. Corner D. L. C. No. 51.
Found - BT's, as recorded Ren. #30.
10", now 22" B.Oak S.72 $\frac{1}{2}$ °W. 14.8 ft., shows good scars,
alive & in good condition. Did not open.
8" W.Oak N.61°W. 15.8 ft., recorded as 14.5 ft.
Open & shows "CS" scribe & face is split.
Set - Brass Cap at Cor. Mkd: County Surveyor's T23S R7W
Office, 1965 SW. DLC 51
New Bt: 10" W.Oak N. 33° W. 20.8 ft. Mkd: SW DLC 51 CS BT.
This corner lies at fence corner, course E. - N. & S.
Dec. 15, 1965

124

N. E. Corner D. L. C. No. 45.
Found - 1" I. Rod & $\frac{3}{4}$ " I. Pipe, see Cain's Ren. #25.
16" B.Oak, now snag, East 9.9 ft., open & find scribe.
15" W. Oak S. 45° W. 37.6 ft., not healed, rotted inside.
DID NOT SET BRASS CAP.
New BT's: 13" D.Fir N. 15° E. 61.8 ft. Mkd: N.E. DLC 45 CS BT.
10" W.Oak S.15° E. 24.3 ft. Mkd: N.E. DLC 45 CS BT.

FO. OK 9/92 BY BECKLEY M 119-80 - SURVEY TIES BRG. TREES TO
Wit Cor. to S. E. Cor. DLC #53. *ACTUAL CORNER.* 125
Found - No trace of I.P. as called for in Cole's Ren. # 4.
10", now 16" W.Oak S. 66° E. 27.0 ft. Open & find "CS".
Set - Brass Cap for Wit.Cor.Mkd: County Surveyor's Office, 1965
Set $\frac{3}{4}$ " I.R. at Actual Cor. T23S R7W W.C. DLC 53 /
Corner 100 ft. S. and E.
New BT's: 20" B.Oak N. 5° W. 28.1 ft. Mkd: W.C. DLC 53 CS BT.
10" B.Oak N.62°E. 16.7 ft. Mkd: W.C.DLC 53 CS BT.
This Witness Corner lies 3.0 ft. West of fence, course N. 8° W.

126

Wit.Co. to Secs. 6 & 7, T23-7W. & Sec.s 1 & 12, T23-8W.
Found - Orig. 20", now 30" W.Oak N. 70° E. 52.8 ft., chopped open
approx. 40 years ago. Hollow, down, no scribe found.
10", now 15" W.Oak N.53°W. 29.0 ft. Open & find "CS".
BT mkd. by Cole, 1921, Recorded in Vol.3 $\frac{1}{2}$, Pg. 89.
No trace of other Orig. BT. now 1" I.P. set by Cole.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T23S R8W S 1 | S 6 R7W
(Set $\frac{3}{4}$ " I.R. for Cor. W.C. S 12 | S 7
in creek bottom) Wit.Cor. 20 ft. North.
New BT's: 11" W.Oak N. 64° W. 22.0 ft. Mkd: WC T23S R8W S1 CS BT.
10" W.Oak N. 33° E. 21.3 ft. Mkd: W.C. T23S R7W S6 CS BT.
24" B.Oak S. 7° E. 40.5 ft. Mkd: W.C. T23S R7W S7 CS BT.
14" W.Oak S. 65° W. 44.6 ft. Mkd: W.C. T23S R8W S12 CS BT.

*FO. + 2/5/60
2/1/68
L. Roberts
M 103-73
C.S. 63/46*

127

N. N. E. Corner D. L. C. No. 38.
Found - 8", now 36" Fir Stump N. 79° E. 15.8 ft. Open & find "C" scribe.
No trace of N. W. BT. See Ren. #29.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
T 23 S R7W / N. NE DLC 38
New BT's: 10" D.Fir S. 5° W. 38.2 ft. Mkd: N.NE DLC 38 CS BT.
13" D.Fir N. 25° W. 21.7 ft. Mkd: N NE DLC 38 CS BT.

128

$\frac{1}{4}$ Corner to Sections 22 and 27. See Ren. #14
Found - Sandstone mkd. "X" on top $\frac{1}{4}$ " on E. face & "CS" on W. face.
14" Oak, down & rotted, S.85°W. 77.2 ft., face gone, no scribe.
36", now 48" Fir N. 70°W. 85.8 ft., now badly rotted stump.
Set - Brass Cap at Cor. Mkd: County Surveyor's T23S R7W $\frac{1}{4}$ S 22
Set Stone alongside. Office, 1966 S 27
New BT: 10" D.Fir S. 82° W. 63.7 ft. Mkd: $\frac{1}{4}$ S27 CS BT.
No other tree available. - Corner lies at fence
corner, fences running E. - W. & N.
Jan. 1966

Vernon "Ray" Tracy
Mike Stone & J. Brady
Dec. and January 1966
C. S. File No. 52/125