

Douglas County Surveyor's Record of
Government Corners Renewed

T. 23 S. T. S. R. 7 W. R. W. W. M.

ROSE-CHAPMAN CO., EUGENE, ORE. 97601

129

Interior "L" D.L.C. No. 46.

Found - Piece of Sandstone Mkd: "Cl 4" as recorded Ren. #18.

Both Orig. BT's., down & burned, no scribe found on these BT's.

18" B.Oak N. 30° W. 43.3 ft., opened prev. & shows "Int L DLC 46",
lower scar shows up good. (unrecorded BT)

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
T23S R7W Int. L DLC 46

New BT's: 24" B.Oak S. 15° E. 65.0 ft. Mkd: "Int. L DLC 46 CS BT".

26" B.Oak S.69°W. 92.1 ft. Mkd: "Int. L DLC 46 CS BT".

This corner lies at fence corner with fence running N.-S. & E.

130

Wit. Point of Sections 28 and 27.

Found - BLM Brass Cap on 2 1/2" I.P. as recorded in 1961 resurvey notes.

We mark Bearing Trees for corner as none were marked in 1961.

New BT's: 12" D.Fir S. 12° W. 52.0 ft. Mkd: WP S28 CS BT.

16" Myrtle S. 26° E. 65.8 ft. Mkd: W.P. S27 CSBT.

This corner lies on right bank of river approx. 85.0 ft. North of
road, course E. and W.

131

1/4 Corner to Sections 28 and 27.

Found - BLM Brass Cap, 1961, Also Sandstone as recorded Ren. #21.

12" W.Oak S. 58° E. 52.8 ft., alive & in good condition,
scribe visible on mostly healed face.

10" Fir S. 7° W. 34.3 ft., alive but burned. May die.

New BT: 7" W.Oak N. 86° W. 72.0 ft. Mkd: 1/4 S28 CS BT.

Note - This corner falls in a generally N. - S. fence approximately
60 feet west of creek, course south.

New B.O.-Chisled 4"x4"+ on W.Face of 5'x5' rock outcropping bears S.44E. 8.0 ft.

132

Witness Point of Sections 27 and 26.

Found - 1961 BLM Brass Cap washed out of place & down stream.

Reset - Brass Cap at proper location from N. E. BT.

22", now 23" Myrtle N. 71° E. 56.1 ft. shows "X BT" on unhealed faces.
No trace of other BT.

New BT: 9" Myrtle S. 1° W. 56.9 ft. Mkd: "W.P. S27 CS BT.

Note - This corner lies approx. 60 ft. N. of road, course NE. & SW.

133

N. E. Corner D. L. C. No. 46.

Found - 2" I.P., as recorded in Ren. #17.

36", now 40" Fir Stump S.30°W. 57.4 ft. shows "E 46 BT", bark scribe.
30", now 34" Fir Stump S.40°E. 21.8 ft., cut short & partially
Buried under logs.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
T23S R7W NE DLC 46 / alongside I.P.

Rescribe in bark, SW. BT., 40" Fir Stump S.30°W. 57.4 ft. Mkd:NE DLC46 CS BT.
No live trees in this area so marked snag:

24" D.Fir Snag S. 11° W. 55.2 ft. Mkd: NE DLC 46 CS BT.

134

East S. E. Corner D.L.C. No. 46.

Found - 2" I.P. 33" long on N.W. side of 60" burned Oak Stump. Ren. #16.

60" Fir N. 35° E. 10.6 ft., shows "BT" bark scribe in very poor
condition. Now Stump.

28", now 36" Fir N. 55° W. 38.9 ft., shows "B", bark scribe, now stump

Since Corner Stump is hollow, we set: Brass Cap in ground in center of Stump,
Mkd: County Surveyor's Office, 1966
T23S R7W E SE DLC 46 /

New BT's: 14" W.Oak N. 81°W. 43.8 ft. Mkd: E SE DLC 46 CS BT.

15" W.Oak N. 30°W. 70.7 ft. Mkd: E SE DLC 46 CS BT.

Note - 2" I.P. bears N. 28°W. 1.8 feet.

Vernon "Ray" Tracy
Mike Stone & Terry Layne
January 1966
C. S. File No. 52/125

(8/6/69)