

Douglas County Surveyor's Record of
Government Corners Renewed

T 23 S. T. S. R. 7 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 97101

Closing Cor. to Sec. 6, T24-7W. & Sec. 1, T24-8W. 135
Found - Co. Brass Cap, properly mkd., See Ren. #80. SEE ALSO REN. # 152
All BT's., down & dead, or gone completely.
New BT's: 8" W. Fir East 32.8 ft. Mkd: "CC T24 S R7W S6 CS BT".
6" D. Fir S. 53° W. 74.2 ft. Mkd: "CC S 1 CS BT".
Note - This corner lies 30 ft. south of old logging road.

Vernon "Ray"
Tracy & Crew
April 18,
1966
C.S. File
No. 49/41

N. W. Corner D. L. C. No. 38.
Found - 12" x 12" Sandstone, from which:
New BT: 28" Fir bears N. 45° E. 7.0 ft. scribed N.W. Cl. 38.
April 15, 1966

Don E.
Garrett
Map File
M 33 - 1

$\frac{1}{4}$ Corner to Section 2 only.
Found - Haines' "T" Iron as recorded in Ren. #73. 136
Orig. 12", now 46" Fir N. 11° E. 8.6 ft. now shattered
stump, prev. opened & shows "18". Approx. 75 years old.
Other Orig. BT. & Haines' BT now gone.
Do not find 1" I.P. called for by Haines.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
T23S $\frac{1}{4}$ S 2 R 7W
New BT's: 7" W. Fir S. 20° E. 7.2 ft. Mkd: $\frac{1}{4}$ S 2 CS BT.
7" W. Fir N. 21° E. 25.2 ft. Mkd: $\frac{1}{4}$ S 2 CS BT.
Note - Corner lies on N.E. Slope of hill approx. 300 ft.
South of Ravine, course S. W.

Vernon "Ray"
Tracy &
Crew
C.S. File
No. 52/125

June 22, 1966

MICROFILM TO HERE 10/67

East 1/4 Corner to Section 15.
Set - 1" Pipe with Brass Cap.

June, 1959

Haines, Wilford N
For: Whipple
Map File
M 22 - 4

Center 1/4 Corner Section 14.
Scribed: 32" Fir N. 11° W. 24.0 feet
16" Fir S. 9° E. 25.2 feet.

1958

Haines, Wilford N
For: Whipple
Map File
M 13 - 64

Section Corner to Secs. 35 & 36, T22-7W. 139
Set From Orig. Bearing Trees
Set - 1"x1"x36" Iron Rod with Brass Cap,
inscribed "Wilford N. Haines #239 Survey Point."

1/4 Corner to Section 35 only, T22-7W. (S. Bdry) 140
Set - 1"x1"x36" Iron Rod with Brass Cap inscribed:
"Wilford N. Haines #239 Survey Point".
18" Fir N. 17° W. 16.2 ft.
30" Fir N. 11° E. 23.0 ft.

WILFORD N. HAINES
For E. G. Whipple
October, 1957
M 1 - 59 C.S. 42/309

Sec. Cor. to Sections 34 & 35, T22-7W. 141
Set - 1" x 1" x 36" Iron Rod with Brass Cap inscribed:
"Wilford N. Haines #239 Survey Point"
12" Fir N. 17° W. 37.5 feet
14" Fir N. 64° E. 28.1 feet

1/4 Corner for Secs. 24 and 25.

WE DO NOT RENEW

Found - Small, squared wood stake near two large trees which
were not cut in logging operations. These trees have
apparently been used as original bearing trees in the
past. We find no scribing on the apparent NW OBT; an
approx. 52" D. Fir snag. The apparent SE OBT an approx.
52" D. Fir, now down, has a very clear bark scribe "1/4
S BT" with the scribe pivot point hole still

143

JAN 1972

(See Also #105)