

Douglas County Surveyor's Record of
Government Corners Renewed

23 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97581

Les Roberts
Triangle Eng. Co.
For: International
Paper Co.
July 1979
M 80 - 17

Closing Cor. to Sec. 6, T.24S. R.7W. and Sec. 1, T.24S. R.8W.
Set - 1 1/2" I. pipe and Brass Cap at true intersection
BT's - 12" Fir bears S.62°W., 64.1 ft.
8" Fir bears S.55°E., 11.2 ft.
Note - See also Renewal #135.
Corner lies 2.28' S. of Co. Renewal #135.

(See 1984 County
Renewal #135 in
T. 23-8)

152

Les Roberts
Triangle Eng. Co.
For: International
Paper Co. 7 - 79
M 80 - 47

North 1/4 Corner Sec. 6 only T.24S. R.7W.
Set - 1 1/2" I. pipe and Brass Cap
BT's - 22 " Fir bears S.57°W. 35.6 feet
14" W. Fir bears S.22°E 7.6 feet

153

Stephen J. Flause, Deputy, Doug. Co. Surveyors Office
T. Plouff and S. Means
April 16, 1980
C.S. 61/6

Northwest corner of DLC #38.
Found - Garrett's 12" x 12" sandstone, Ren. #135A, which when
referenced out and removed from ground, we find to measure
14" x 14" x 16". Sandstone is marked with "X". Sandstone is at
corner of fences running east, west and south.
Search for but find no evidence of orig. 18" Oak BT.
A 28" now 30" DBH, D. Fir bears N.45°E., 7.0 ft. Has partially
healed double blaze with scribed "D" visible. Ren. #135A
We perpetuate position of corner at sandstone as accepted by Garrett.
We reference out sandstone and remove
Set - A 1" x 30" I.P. with brass cap marked "Douglas County Surveyor"
T23S R7W DLC 38 1980
We place sandstone on south edge of cap. Both cap and stone are
firmly set and protrude 0.1 ft. from ground.
New BT's - A 12" B. Oak bears N.87°E., 67.0 ft. scribed "NW DLC 38 CS BT"
on a double blaze.
A 24" B. Oak bears S.02°W., 109.9 ft. scribed "NW DLC 38 CS BT"
on a double blaze.
We tag trees with DCSO BT tags.

154

4/16/80

1/4 Corner for Secs. 34 and 35.
Found - 1961 BLM brass cap on 2 1/2" I.P. protruding 0.3 ft. from
ground and firmly set. Cap properly marked.
We make search for orig. evidence and evidence from Ren. #28. Area has been
logged and burned. We find none.
A 20" now 33" White fir bears N.27°E., 92.5 ft. (Rec. N.28°E.,
83.5 ft.) has fully healed single blaze. no scribing visible.
A 20" now 22" D. Fir bears N.72 1/2°W., 41.5 ft. (Rec. a W. Fir,
bears N.74 1/4°W., 41.6 ft.) fully healed single blaze, no
scribing visible.
Because monument shows no sign of having been disturbed, we assume record
bearing and distance to NE bearing tree is incorrect and leave cap at
same position.
We retag BLM's NE bearing tree with DCSO BT tag amrked with new bearing
and distance N.27°E., 92.5 ft.
A 10" D. Fir bears S.73°E., 58-2 ft. scribed "1/4 S35 CS BT"
on a double blaze.
A 8" D. Fir bears S.08°W., 33.5 ft. scribed "1/4 S34 CS BT" on a
double blaze.
NW bearing tree will be removed. No other trees available in this quadrant
We tag new trees with DCSO BT tags.

155

4/16/80

Les Roberts
For: International
Paper Company
Feb. 1980
M 84 - 57

North 1/4 Corner for Sec. 4 only, T.24-7
Found - A 5/8" Iron Rod. Ren. #149
32" Fir stump, S.12°E., 42.0 ft. BT.
Set - A 1 1/2" Iron pipe with International Paper Co. Brass Cap.
New BT - 20" White Fir, N.88°W., 20.8 ft. BT Scribed.

156

2/80