

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 23

T. S. R 7

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

C O N T - - -  
Doug. Co. Surveyors  
Office  
R.W. Smith - S.J.  
Flause  
3/31/87 C.S. 62/40

(1/4 Cor. for Secs. 21 & 28)  
of trunk at level)  
New BT - 15" dia. W. fir double blazed and scribed "1/4 S28 CS BT"  
bears S.41°W., 35.1 ft.  
Corner lies near the NE corner of a flat wooded bench at the SE corner  
of a logged area. (for sketch, see C.S. file)

169

3/31/87

Les Roberts  
For: International  
al Paper Company  
Feb. 15, 1987  
M 103 - 73  
C.S. 63/46

1/4 Corner for Sections 7 and 18  
No evidence of original corner found.  
Set - 3/4" x 30" alum. rod w/alum. cap stamped w/S-T-R and PLS #1039.  
(buried purple M.M. under 30" rod)  
New BTs-15" W. fir, N.47°W., 24.7 ft. (scribed/painted red)  
18" W. fir, S.27°E., 17.9 ft. (scribed/painted red)

170

2/15/87

*FD. OR 9-92 BY BECKLEY - M119-80*

North 1/4 Corner for Section 6 only.  
Found - 1962 County brass cap on a 1 1/4" O.D. iron pipe leaning 1.3 ft.  
southeast, protrudes 9" above ground. Per Ren. #100  
(No original bearing trees found. All bearings and distances taken to plumb  
position of brass cap/iron pipe)

171

Douglas County  
Surveyors Office  
Randall Smith  
Stephen J. Flause  
June 30, 1987  
C.S. 62/45

BTs - 16" now 29" dia. W. oak with a previously opened blaze (no  
scribing found) bears S.7°W., 79.2 ft. (agrees well with rec.)  
8" now 33" dia. W. oak with a fully healed single blaze bears  
S.21 1/2°E., 131.5 ft. (Rec. S.20°E., 130.0 ft. dist. is a face  
measurement) Ren. No. 27A  
20" now 24" dia. W. oak with a fully healed double blaze bears  
S.4°W., 62.3 ft. (agrees well with rec. Ren. #100)  
21" now 36" dia. D. fir with a fully healed single blaze bears  
S.33°E., 60.5 ft. (Rec. S.33°E., 59.8 ft. distance is a face  
measurement per Ren. #100)  
Set - Douglas County brass cap and iron pipe returned to plumb  
position. Protrudes. 9" above ground.  
Monument lies at the intersection of a east-west and south running  
fence lines.

6/30/87

Section Corner for Secs. 11, 12, 13 and 14  
Found - A 1962 2 1/2" dia. Doug. Co. Brass cap on a 1 3/8" O.D. x 36" long  
iron pipe, properly mkd., leaning North. Ren. #108  
Haines iron rod from Ren. #97, NOT FOUND.

172

(Bearings and distances taken to plumb positon at base of BC/IPO  
Orig. maple BT seen in Ren. #97 and #108 is NOT found.  
20" now 32" dia. W. fir with a fully healed single blaze, bears  
N.58°W., 44.2 ft. (agrees with record) Ren. #108  
42" now 48" dia. 60 ft. high burnt and dead cedar snag, with a  
burnt out double blaze, no scribing seen, bears S.58°W., 59.3 ft.  
Agrees with record. Ren. #108  
18" now 24" dia. 6 ft. high rotted maple snag, with a 10" maple  
growing out of east trunk, axe marks and illegible scribing  
seen, bears N.64 1/2°E., 125.4 ft. (Rec. N.66°E., 125.4 ft.)  
16" now 19" dia. 60 ft. high dead cedar snag with a fully healed  
upper blaze and a partially healed lower blaze, illegible  
scribing visible, bears S.22 1/2°E., 182.2 ft. (agrees with rec.)  
Set - Plumb position at base of 1962 DCSO BC/IP is set back in grojnd and  
now protrudes 7" above ground and is surrounded by a 2 1/2 ft. dia.  
mound of sandstone. The marks "RESET 1989" are added to BC.  
New BTs -9" dia. D. fir double blazed and scribed "T23S R7W S14 CS BT" bears  
S.08 1/2°W., 21.1 ft.  
13" dia. D. fir double blazed and scribed "T23S R7W S13 CS BT"  
bears S.41°E., 25.0 ft.  
10" dia. D. fir double blazed and scribed "T23S R7W S12 CS BT"  
bears N.27 1/2°E., 97.8 ft.

Douglas County  
Surveyors Office  
Randall Smith  
Stephen Flause  
July 5, 1989  
C.S. 64/1

7/5/89