

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 23 S. T. S. R. 7 W. R. W. W. M.

KERR-CHAPMAN CO., EUGENE, ORG. 91881

180

Ken Hoffine
For: Lone Rock Timber
C.S. 63/154-5
Feb. 1994

North 1/4 Corner for Section 1 only. See renewal # 122. T.22-7
Found - Haines T-Iron 1.5 ft. above ground.
BTs - 30" D.Fir stump bears S.2°E., 69.5 ft. No marks, (rec. S.1°E., 70.5 ft.)
10" D.Fir bears S.21°E., 14.3 ft. I scribe BT and tag tree.
Note - Ground on steep south slope approximately 40 ft. north of shallow bowl like head of draw. Clearcut to west of corner.

181

Clyde Mulkins
For: IP Timberlands
Jan. 4, 1994
M 118 - 61

1/4 Corner for Sections 25 & 36. See Renewal #38
BT's Found - 27" diam., Douglas Fir, with visible bark scribes, bears South, 5.9 ft.
Set - I.P.T.O Alum. mon. (3/4" x 36" Alum. rod and 3" Alum. cap stamped "LS 2006") At the corner between secs. 25 & 36.
New BT's - 13" diam., Douglas Fir, bears N.49°E., 15.4 ft., I scribe "1/4 S25 BT".
10" diam., Douglas Fir, bears N.69°W., 14.9 ft., I scribe "1/4 S25 BT".
14" diam., Douglas Fir, bears N.10°W., 11.4 ft., I scribe "1/4 S25 BT".
Fd. a windfall Douglas Fir noted by Kerr CS 40/190, N.20°E., 36 lks.

182

Douglas Co. Surveyors Office
Randall Smith & Stephen Flause
C.S. 64/64-12
12/13/95

See Renewal # 163

Sec. cor. of 20, 21, 28, & 29
Mon. Fd. - 3 1/4" dia. BLM brass cap on a 2 1/2" O.D. Iron pipe protruding 6" above ground. (1963)
5/8" I.R. protruding 3" above ground is found along northeasterly edge of BLM BC/IP (ren#45)
BT's Fd. - 10" now double trunked W.Oak, with a fully healed double blaze on 20" dia. southerly trunk, root crown of southerly trunk, bears N.11 1/2°W., 10.6'.
10" now 22" dia. W.Oak, with a fully healed double blaze, bears S.88°E., 72.6', root crown (goes to center of trunk).
Double trunked maple, 20" now 41" dia. Westerly trunk, with a fully healed blaze on westerly trunk, bears N.85°E., 123.4' to root crown of westerly trunk.
15" now down with a rotted approx 24" dia. rootwad, bears S.65 1/2°W., 124.1' (a small illegible scribe mark was found in down trunk)
New Bt's - 21" dia. W.Oak, double blazed and scribed "T23S R7W S29 CS BT", bears S.58°W., 184.7'.

FD. OK BY G. LANG, AUG. 1976 M 125-72

183

William Beckley
For: Anderson
Sept. 1992
M 119 - 80

1/4 Corner for Section 5 only See renewal # 31
Found - 5" x 8" Sandstone flush with ground marked "SC"
T iron post with 1" cap marked "Wilford Haines survey point Drain Or" bears West 0.30 ft. from true corner.
Fd.BTs- 24" B.Oak S.42°W., 8.58 ft. - good scar.
16" B.Oak S.73°E., 16.00 ft. - scar visible

184

NW Corner D.L.C. No. 52
Set - 5/8" x 30" iron rod with yellow plastic cap inscribed "UMPQUA 2417"
New Accessories -
14" Oak, N.01°15'43"E., 43.22 ft. scribed "NW DLC 52"
14" Oak, N.54°26'37"W., 53.20 ft. scribed "NW DLC 52"

185