

Douglas County Surveyor's Record of
Government Corners Renewed

23

T. S.

8

R. W. W. M.

COKE-CHAPMAN CO. EUGENE, ORE. 31881

James W. Byron, Deputy County Surveyor
April 23, 1956.
C. S. File No. 47/142.

$\frac{1}{4}$ corner to secs. 35 and 36. 1
Found-orig. stone set for $\frac{1}{4}$ corner mkd. $\frac{1}{4}$ W. face-checks dist. and bearing to now 26 inch Cedar with face burned-no scribing visible. Also found 60 inch Fir which bears N.48°E., 20.5 feet (record N.25° W., 20.5 feet)-scribe marks found on this BT.
Set an iron pipe with brass cap alongside orig. stone cor. & marked County Surveyors Office, 1956, $\frac{1}{4}$ S 35/36 T23S, R8W.
From which:
A 12 inch R. Fir bears S.50°E., 3.5 feet scribed $\frac{1}{4}$ S 36 CS BT.
A 14 inch R. Fir bears S.78°W., 24.8 feet scribed $\frac{1}{4}$ S 35 CS BT.

Fd. O.K. by
L. ROBERTS
MAR., 1982
M 91-74

$\frac{1}{4}$ corner to sec. 36, T23S, R 8 W., and sec. 31, T23S, R7W. 2
Found old sq. stake on ground under 3 foot log-checks bearings and distance to original BT, S.60°E., 16.5 feet, now snag & rotted-found "BT" scribed at base. The West BT is down and partly burned-no scribing visible-checks bearing and distance to stump.
Set an iron pipe with brass cap at north edge of log mkd. County Surveyors Office, 1956, $\frac{1}{4}$ S R8 | R7
36 | 31 T23S.
From which:
12 inch Fir bears N.37°W., 18.0 feet scribed $\frac{1}{4}$ S 36 CS BT.
6 inch Fir bears S.52°E., 16.8 feet scribed $\frac{1}{4}$ S 31 CS BT.

Fd. O.K. by
L. ROBERTS
MARCH, 1982
M 91-74

Meander corner common to Secs. 11 and 12. (S. side of River) 3
Original:
24 inch Oak bears S.29°E., 160 lks.; now 26 inch stump, burnt log on ground, face not cut out.
12 inch Oak bears S.4°W., 225 lks.; now 18 inch stump, BT scribe visible, log on ground, 11 scribe visible. Var. 21 $\frac{1}{2}$ °
Set a 1 $\frac{1}{2}$ inch x 36 inch galvanized iron pipe with a 3 inch bronze cap marked "OREGON STATE BOARD OF FORESTRY MC S11 S12 1957 RS 359," 34 inches in ground, and from which:
31 inch Maple bears S.44°W., 37.0 ft., scribed S11 MC BT RS 359.
18 inch Triple Myrtle bears N.54 $\frac{1}{2}$ °W., 75.6 ft.; scribed S11 MC BT.
Oregon State Board of Forestry metal location poster on 31 inch Maple BT.

Meander corner common to Secs. 11 and 12. (N. side of River) 4
No evidence of original corner found. Var. 20°36'E.
Reestablished corner by setting a 1 $\frac{1}{2}$ inch x 36 inch galvanized iron pipe with 3 inch bronze cap marked "OREGON STATE BOARD OF FORESTRY MC S11 S12 1957 RS 359," 34 inches in ground, and from which a:
32 inch Maple bears N.29°W., 17.7 ft., scribed S11 MC BT.
38 inch Oak bears N.70°E., 44.6 feet, scribed S12 MC BT RS 359.
Oregon State Board of Forestry metal location poster on 22 inch Oak, N.5°E., 45.8 feet.

Section corner to secs. 1, 2, 11 and 12. 5
Original:
18 inch Oak bears S.7°E., 490 lks., now 40 inches, inside rotted out, old face showing in bark and cast inside.
15 inch Oak bears S.0°15'W., 623 lks. now missing.
18 inch Ash bears N.88°W., 167 lks., now Missing, point falls in grain field. Var. 20°36'E.
Set a 1 $\frac{1}{2}$ inch x 36 inch galvanized iron pipe with 3 inch bronze cap marked "OREGON STATE BOARD OF FORESTRY T23S R8W S1 S2 S11 S12 1957 RS 359," 2 feet under ground, and from which a:
21 inch Oak S.0°15'E., 315.4 ft., scribed T23S R8W., S12 BT RS 359.
20 inch Oak S.52 $\frac{1}{2}$ °W., 330.4 feet, scribed T23S R8W., S11 BT.
Oregon State Board of Forestry metal poster on Original 18 inch Oak BT S7°E.

RE-ESTABLISHED CORNER NO. #124

Arnold G. Gibson, Assitant Engineer
Oregon State Board of Forestry
April 22, 1957

C. S. File No. 42/258. M 5 - 19