

Douglas County Surveyor's Record of
Government Corners Renewed

23 T. S. 8 R. W. W. M.

KONE-CHAPMAN CO., EUGENE, ORE. 21881

$\frac{1}{4}$ corner to secs. 1 and 12.

6

ORIGINAL:

15 inch Oak bears N.24°E., 276 lks., now 24 inches, exposed scribes
 $\frac{1}{4}$ S.

15 inch Oak bears N.86°W., 755 lks., now rotted stub in place, old
axe work visible. Var. 21 $\frac{1}{2}$ °

Set 1 $\frac{1}{2}$ inch x 36 inch galvanized iron pipe with 3 inch bronze cap marked
"OREGON STATE BOARD OF FORESTRY $\frac{1}{4}$ S1 S12 1957 RS 359," 28 inches in
ground, and from which a:

11 inch Oak bears S.31 $\frac{1}{2}$ °W., 44.0 ft., scribed $\frac{1}{4}$ S12 BT.

30 inch Fir bears N.81°E., 203.5 ft., scribed $\frac{1}{4}$ S1 BT RS 359.

Set 4 inch x 4 inch x 60 inch white painted Cedar post 1 foot NE of pipe.
Oregon State Board of Forestry metal location poster on 10 inch Oak,
N.19°W., 2.3 feet.

Northeast corner DLC No. 38 in Section 2.

Original:

Var. 21 $\frac{1}{2}$ °E. #109

Post (now 12 inch round post in place at fence corner) from which a:

20 inch Oak bears N.79°W., 1170 lks., now 32 inches, old face and
axe work visible.

24 inch Oak bears N.85°45'W., 1175 lks., now 30 inch stump remaining,
at 818.0 ft.

From which new trees:

28 inch Oak bears S.42 $\frac{1}{2}$ °E., 249.2 ft., scribed AP DLC 38 BT RS 359.

18 inch Oak bears N.74 $\frac{1}{2}$ °E., 198.3 ft., scribed AP S2 BT.

Oregon State Board of Forestry metal location poster on 4 inch x 4 inch
x 70 inch white painted Cedar post S.49 $\frac{1}{2}$ °E., 140.0 feet on W edge
County Road.

Northeast corner DLC No. 38 in Section 1.

8

Original:

Post missing.

12 inch Oak bears S.4°E., 665 lks., now missing, rotted root stubs
and logs in vicinity. Var. 20°36'E.

Set 1 $\frac{1}{2}$ inch x 36 inch galvanized iron pipe with 3 inch bronze cap
marked "OREGON STATE BOARD OF FORESTRY T23S R8W AP DLC 38 S1 1957
RS 359," 35 inches in ground, in fence line at angle point
(N.49 $\frac{1}{2}$ °W., and S.36 $\frac{1}{2}$ °E.,) and from which a:

14 inch Oak bears N.7°W., 35.3 feet, scribed AP S1 BT.

26 inch Fir bears N.53°W., 105.6 feet, scribed AP DLC 38 BT RS 359.

Center Concrete boxed spring bears N.61 $\frac{1}{2}$ °W., 75.4 feet.

Set 4 inch x 4 inch x 72 inch white painted Cedar post 1.5 feet NW of pipe.
Oregon State Board of Forestry metal location poster on 12 inch Ash,
N.47 $\frac{1}{2}$ °W., 25.7 feet.

Section Corner to Sections 25 & 36, T23S R8W, & Secs. 30 & 31, T23S R7W.

Found: Original 10" now 24" Fir Snag N.67°W. 64.7 ft. Open face, good
scribing.

Orig. 10" now 24" Fir Snag S.50°W. 85.8 ft. I open & find good
scribing.

Find what may be Orig. 12" now 30" Fir N.4°E. 104.3 ft. Shows
old scar. I do not open.

Find rotted stump for orig. S.E. BT.

Set Brass Cap at Corner marked $\frac{S25}{R8W}$ | $\frac{S30}{S36/S31}$ | T23S County Surveyor's
Office, 1957

New BTs: 7" R. Fir bears S.45°E. 16.6 ft. scribed T23S R7W S31 CS BT.

8" R. Fir bears S.32°W. 9.2 ft. scribed T23S R8W. S36 CS BT.

10" R. Fir bears N.43 $\frac{1}{2}$ °E. 13.6 ft. scribed T23S R7W S30 CS BT.

6" R. Fir bears N.67°W. 11.2 ft. scribed T23S R8W S25 CS BT.

Corner to Sections 3 & 10.

#10

Found - 3 Orig. BT's. & old Maple Stump that checks bearing & distance for
S. E. BT. Orig. 14" W. Fir, now 32" Shows old face, now rotted,
N.32°E. 49.5 ft. Orig. 40", now 56" Fir S.55°W. 44.9 ft.,
shows good scars, I do not open. Orig. 10", now 28" R. Fir N.68°W.
14.5 ft., shows scar, I do not open. I also find Rock set for
Closing Corner, checks good for bearing & I make distance about
4 ft. less than record.

-continued-

Arnold G. Gibson, Assistant Engineer
Oregon State Board of Forestry
April 22, 1957.
C. S. File No. 42/258. - M 5 - 19

James W. Byron
M. Godfrey
S. Blouw
Dec. 19, 1957
C. S. File No. 49/49

Fd. ax. by
ROBERTS
MAR. 1982
M 91-74