

Douglas County Surveyor's Record of
Government Corners Renewed

23 T. S. 8 R. W. W. M.

KOHE-CHAPMAN CO., EUGENE, ORE. 21801

James W. Byron, Deputy
Milo Godfrey
S. A. Bilow
C. Putnam
July 1, 1959
C. S. File No. 49/49

continued - - -

10

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959

$\frac{S3}{S10} | S11$ T.23S. R8W.

New BT's: 10" R.Fir bears N.77°W. 36.3 ft. scribed S 3 T23S R8W CS BT.
8" R.Fir bears S.72°W. 42.5 ft. scribed S10 T23S R8W CS BT.

Closing Corner to Sections 2 & 11.

Found - Stone as recorded and Orig. 10", now 31" R. Fir S. 4°E. 45.5 ft.,
shows good scars, I do not open.
No trace of Orig. N.W. BT.

Set Brass Cap alongside Corner Stone & Mark County Surveyor's Office, 1959

$\frac{S3}{S11} | S2$ T23S R8W

New BT's: 10" R.Fir bears S.31°E. 16.2 ft. scribed T23S R8W S11 CC CS BT.
15" R.Fir bears N.25°E. 42.8 ft. scribed T23S R8W S 2 CS CC BT.

RECORDED **CORNER NO #125** **#10A**

James W. Byron, Dept.
Milo Godfrey & C. Putnam
Sept. 1960
C.S. File No.
49/41

$\frac{T23S}{R8W} | \frac{S36}{S31} | R7W$

11

Found - Orig. 16", now 36" Fir S.65°W. 38.9 ft., previously opened,
shows good scribing "T24S".

Orig. N.E. & S.E., now rotted stumps only.

Orig. 14", now 30" Fir N.28°W. 72.6 ft., shows good scars.

Set Brass Cap at Corner Mkd; County Surveyor's Office, 1960

$\frac{T23S}{R8W} | \frac{S36}{S31} | R7W$ T24S

New BT's: 18" R.Fir bears N.72°E. 62.5 ft. scribed S31 T23S R7W CS BT.
12" R.Fir bears N.63°W. 53.6 ft. scribed S36 T23S R8W CS BT.

FD. OK. by:
L. ROBERTS
MAR. 1962
M 91-74

James W. Byron, Deputy County Surveyor
Milo Godfrey
Clote Putnam
Done For- J. H. Connon
Oct. 27, 1960
C. S. File No. 52/57
M 19 - 75

Section Corner to Sections 23 - 24 - 25 - 26.

Found - All Orig. BT's. N. W. & S.W. BT's. now down.

Orig. 18", now 34" Fir N. 5°E. 47.5 ft.

Orig. 10", now 15" Fir S.25°E. 24.4 ft. I open & find
good scribing "BT".

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960

$\frac{S23}{S26} | \frac{S24}{S25}$ T23S R8W

New BT's: 72" R.Fir bears S.71°W. 46.4 ft. scribed S26 T23S R8W CS BT.
24" R.Fir bears N.41½°W. 55.8 ft. scribed S23 T23S R8W CS BT.

FD. OK 2/81
L. ROBERTS
M 86-64

12

Section Corner to Sections 13 - 14 - 23 - 24.

Found - Four Orig. BT's. All check bearing & distance.

N. E. BT. shows good scribing on previously opened face.

Also find Stone at Corner as recorded.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960

$\frac{S14}{S23} | \frac{S13}{S24}$ T23S R8W

Rescribe, now Maple (18"), S.21°E. 31.7 ft. S24 T23S R8W CS BT.
Note - Top of Brass Cap leans 1.0 ft. to South.

FD. OK 2/81
L. ROBERTS
M 86-64

13

W. C. Sections 23 and 24.

W. C. is 7.5 ch. South of above section corner.

Found - Both BT's. as recorded by Whipple 1894. I open S. E. BT.
and find good scribing "C".

Corner Stone set by Whipple not found.*

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960
Wit. Cor. S23/S24 T23S R8W*

No new B.T's. scribed.

* FD. OK 2/81
L. ROBERTS
M 86-64

14

$\frac{1}{4}$ Corner S24/S19 T23S
R8W R7W

Found - Both Orig. BT's.: Orig. 12", now 24" Fir Stump N.70°W. 17.2 ft.

I open & find good scribing "B".

Orig. 12", now 24" Fir N. 3°E. 23.6 ft., shows good scar.

I do not open.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960

$\frac{1}{4} \frac{S24}{R8W} | \frac{S19}{R7W}$ T23S

FD. OK 2/81
L. ROBERTS
M 86-64

15

(continued over)