

Douglas County Surveyor's Record of
Government Corners Renewed

T. 23 S. T. S. R. 8 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

21

N. W. Cor. Sec. 6, T23-8W.
(E. Line Sec. 1, T23-9W.)
Found - 40" Fir Stump, badly burned, N.40°W. 27.1 ft., found scribing,
"S6 & W", at bottom edge of upper face. BT. scar compl. burned.
Stump Hole with Fir Roots S.30°W. 29.7 ft.
No trace of Dogwood to N.E., area has been logged & burned.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963

T23S	T22S	R9W	
	S 36		
R9W	S 1	S 6	T23S R8W

Rescribe - 40" Fir Stump N.40°W. 27.1 ft. Mkd: T23S R9W S1 CS BT.
New BT: 9" D.Fir S.70°E. 56.2 ft. Mkd: T23S R8W S6 CS BT.
No other live trees near.
Corner lies on West Slope approximately 300 feet West of ridge top.

22

Corner R9W S36/S31 R8W (N. Line Sec 6 T23-8W.)
Found - 1 1/2" Iron Pipe (Galv.) & Wooden Stake.
54" Fir N.65°W. 77.9 ft., old uproot, dead, found good bark scribing, "S36 T22S R9W B".
72" Fir N.70°E. 90.4 ft., old, dead, uproot, bark charred & covered with mud, no scribing found.
DID NOT SET BRASS CAP. - Iron Pipe in good condition.
New BT's: 9" D.Fir N.68°E. 45.8 ft. Mkd: T22S R8W S31 CS BT.
20" D.Fir N.66°W. 25.0 ft. Mkd: T22S R9W S36 CS BT.
15" D.Fir S.89°W. 30.4 ft. Mkd: T23S R8W S 6 CSBT.
Note - Corner lies on steep N. E. slope.
FOUND O.K. - VRT - FEB. 1967

23

Section Corner to Sections 26 - 27 - 34 - 35.
Found - Rock (Sandstone) approx. 14" x 12" x 10" with "X" on Top.
54" Red Cedar N.43°E. 9.2 ft. (to old face). Did not open.
Rotted Remains of Hemlock Stump S.36°W. 11.2 feet.
No trace of S. E. or N. W. Bearing Trees.
Set - Brass Cap alongside Rock Mkd: County Surveyor's Office, 1964

T23S	R8W	S27	S26
		S34	S35

Blaze & Rescribe - 54" Red Cedar N.43°E. 9.2 ft. (to old face) Mkd: "T23S R8W S26 CS BT".
New BT's: 16" Red Cedar S.16°E. 24.0 ft. Mkd: T23S R8W S35 CS BT.
62" Red Cedar S.24°W. 46.0 ft. Mkd: T23S R8W S34 CS BT.
No suitable trees near N. W. of Corner.
Corner lies on steep N. slope approx. 60 ft. South of Waggoner Creek
Jan. 22, 1964

24

Corner to Sections 35 and 36 only. (on N. Line T24-8W)
Found - 54" D. Fir N.5°W. 29.7 ft., opened & found scribing "3" & "8",
appeared to be made with pocket knife, ring count shows right age
63" D. Fir N.73 1/2°E. 35.0 ft, area on bark shows axe facing,
probably had been bark scribed, no scribing visible now.
58" D.Fir S.52°W. (not S.2°W) 21.1 ft. Opened some years ago,
fragmentary scribing visible, none legible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964

T23S	R8W	S35/S36
------	-----	---------

New BT's: 10" W. Fir N.20°E. 16.5 ft. Mkd: T23S R8W S36 CS BT.
9" D. Fir N.75°W. 7.0 ft. Mkd: T23S R8W S35 CS BT.

25

Corner to Sections 2 and 1 only, T24-8W. (on S. Line T23-8W)
Measured west 215.2 ft. (3.26 chs.) from cor. Secs. 35 & 36, T23-8W.,
as determined from old Bearing Trees. Found 4 BT's. facing this point.
BT's. bear no similarity to trees called for at this corner in gov't.
field notes. Tree found as follows:
22" D. Fir N.4°W. 11.4 ft., opened by BLM, old scribing visible on old face.
22" D.Fir S.69°E. 24.8 ft, opnd by BLM, scribing visible on old face.
(Ring count on these two trees show correct age.)
Small Fir Snag, 10" when mkd.) old face shows scribing "T24 R8W".
32" D.Fir N.32°E. 20.9 ft., shows very plain axe scar facing cor, not opend.
Set - At 215.2 ft. W. of Corner to Sections 35 and 36, Iron Pipe with
Brass Cap Mkd: County Surveyor's Office, 1964

T24S	R8W	S 2/S 1
------	-----	---------

New BT's: 14" D.Fir S.77 1/2°E. 21.7 ft. Mkd: T24S R8W S1 CS BT.
38" D.Fir S.37°W. 35.0 ft. Mkd: T24S R8W S2 CS BT.

Milo E. Godfrey, Deputy Co. Surv.
Vernon Tracy and Mike Stone
March 1963
C. S. File No. 52/14

Milo E. Godfrey
Wm. Stoffel & Mike Stone
Jan. 22, 1964
C.S. File No. 49/49

Milo E. Godfrey, Deputy
Mike Darby - Mike Stone
Jim Halterman
March 2, 1964
- C. S. File No. 49/49

FD. O.K. by:
L. ROBERTS
MARCH 1982
M 91-74