

Douglas County Surveyor's Record of
Government Corners Renewed

T. 23 S. T. S. R. 8 W. R. W. W. M.

$\frac{1}{4}$ Corner to Sections 27 and 28.

Found - Very old squared Post, badly rotted.

should be S. 66° E. 46
per M 92-3
5/18 AS

Orig. 50"?, now 50" Fir S. 66° W. 11.9 ft., shows old bark scribe " $\frac{1}{4}$ " & frag. scribe marks. Alive.

Orig. 50", now 56" Fir, West 2.6 ft., shows " $\frac{1}{4}$ SBT" bark scribe in poor condition. Alive.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T23S R8W
(Set at base of Office, 1966 $\frac{1}{4}$ S28/S27
Orig. BT. to West)

New BT's: 5" Hemlock S. 59° E. 7.2 ft. mkd. $\frac{1}{4}$ S 27 CS BT.

6" Hemlock S. 30° W. 13.2 ft. mkd. $\frac{1}{4}$ S 28 CS BT.

Note - This corner lies on N. E. slope in heavy timber approx. 150 ft. North of road, course S.W. & N.E.

Find. O.K. by
L. ROBERTS
MAR. 30, 1982
M 92-3

Sec. Corner to Sections 27 - 28 - 33 - 34.

Found - Orig. 36", now 42" Fir, N. 56° E. 11.2 ft. Alive, shows bark scribe in fair condition.

Orig. 30", now 40" Fir, S. 29° E. 13.9 ft. Alive, shows bark scribe "T23S S34". Rescribe "T23S R8W S34 CS BT".

Orig. 24"?, now 43" Fir, S. 52° W. 36.3 ft. Alive, bark scribed "T23S R8W S23". Rescribe "T23S R8W S33 CS BT".

No markings on perpendicular Rock N. 65° W. 28.4 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T23S R8W
S 28 | S 27
S 33 | S 34

Note - There are no small trees near this corner. Corner lies on very steep, east slope.

Sec. Cor. to Sections 32 & 33, only, T22-8W.

(N. Bdry. Sec. $\frac{1}{4}$, T23-8W.)

Found - 1962 G.L.O. Brass Cap at Cor., properly marked.

25" Fir, now 6' high stump, N. 52° E. 10.9 ft., scribe visible on pitched blaze.

18" W. Fir, now 6' high stump, N. 20 $\frac{1}{2}$ ° W. 48.2 ft., scribe visible on unhealed blaze.

New BT: 7" W. Fir N. 38° W. 121.5 ft. mkd. T22S R8W S32 CSBT.

No trees close to N.E. - Cor. lies in logged off unit 50' N. of new access road.

$\frac{1}{4}$ Corner to Sections 8 and 9.

Found - Orig. 10", now 18" Fir, S. 38° E. 17.2 ft., now down, open & fine " $\frac{1}{4}$ S" scribe & reverse.

Orig. 38", now 48" Fir, Alive, N. 19° W. 44.2 ft, fragmentary bark scribe on old bark blaze.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T23S R8W $\frac{1}{4}$ S 8/S 9

New BT's: 17" D. Fir S. 36° E. 30.1 ft. mkd. $\frac{1}{4}$ S 9 CS BT.

15" Chinquapin S. 66° W. 33.0 ft. mkd. $\frac{1}{4}$ S 8 CS BT.

Note - This corner lies on steep, W. slope in reprod. of small fir & hemlock.

$\frac{1}{4}$ Corner to Sections 9 and 16.

Found - Orig. 10", now 28" Fir, Alive, S. 31° E. 25.7 ft., prev. opened & shows " $\frac{1}{4}$ S" scribe on decaying face.

Orig. 6", now 18" Fir Snag with approx. 6 ft. of lower part buried in old slide, N. 3° E. 17.8 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T23S $\frac{1}{4}$ S 9
R8W $\frac{1}{4}$ S 16

New BT's: 14" Hemlock N. 67 $\frac{1}{2}$ ° W. 58.9 ft. mkd. $\frac{1}{4}$ S9 CS BT.

32" D. Fir S. 58° E. 16.4 ft. mkd. $\frac{1}{4}$ S.16 CS BT.

Note - This corner in bottom of ravine approx. 225 ft. East of top of ridge, course N.E.

47

48

49

50

Vernon "Ray" Tracy
Jack Heritage & E. West
December, 1966
C. S. File No. 54/12