

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 23 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97881

56

Sec. Cor. to Sections 28 - 29 - 32 - 33.

Found - Corner Stone 14"x12"x9" mkd. with 4 notches E. & 1 notch, S., firmly set.

Orig. 12", now 13" Fir Snag, N. 12° E. 9.2 ft., scribe, "T23S R8W S28" visible on unhealed blaze.

Orig. 10", now 20" Cedar, alive, S. 53° E. 24.4 ft., shows faint scar. (Rescribe "T23S R8W S33 CS BT")

Orig. 14", now 22" Fir, alive, S. 20° W. 13.9ft., shows fair scar. (Rescribe "T23S R8W S32 CS BT").

Orig. 4", now 6" Hemlock, alive, N. 39° W. 7.9 ft., shows scar, we open & fine "S29" scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967

T 23 S	R 8 W
S 29	S 28
S 32	S 33

New BT's: 14" Cedar N. 52° E. 41.3 ft. mkd. T23S R8W S28 CSBT.

6" Hemlock N. 79° W. 25.1 ft. mkd. T23S R8W S29 CS BT.

Note - This corner lies on N. slope 30 ft. N. of bench.

57

Wit. Corner of  $\frac{1}{4}$  Corner to Sections 29 and 28.

Found - " $\frac{1}{4}$ " "+" on nearly vertical Rock face.

Orig. 8" Fir, now 9"-10' high snag, S. 82° E. 4.6 ft., prev. opened & shows " $\frac{1}{4}$ " scribe. We chop lower scar & find "B".

Orig. 10", now 16" Fir, alive, N. 45° W. 5.9 ft. Do not open.

Impossible to set Brass Cap at exact corner point so

Set - Witness Corner 10 ft. North: T23 S R 8 W  
Brass Cap Mkd: County Surveyor's Office, 1967 W.C. 10 ft. S. to Cor.  $\frac{1}{4}$  S 29/S 28

New BT's: 13" D. Fir S. 64° E. 21.7 ft. mkd. W.C.  $\frac{1}{4}$  S28 CS BT.

15" D. Fir N. 65° W. 8.5 ft. mkd. W.C.  $\frac{1}{4}$  S29 CS BT.

Note - This corner lies 50 ft. S. of foot of bluff, 30' high and 50' N. of bottom of small draw.

Fd. by: L. R. BERTS  
MAR. 30, 1982  
M 92-3

Vernon "Ray" Tracy  
Jack Heritage & Elmer West  
January, 1967

C. S. File No. 54/12

58

$\frac{1}{4}$  Corner to Sections 27 and 26.

Found - Orig. 30", now 44" Fir, turned out & lying nearly face down, S. 56° E. 54.1 ft. Open & find "BT" scribe & reverse. We use center of stump hole.

Possible Orig. N.W. BT., down & slid out of position, nearly buried. We measure from corner south to creek, 195 ft., orig. call is 198 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967

T 23 S	R 8 W
$\frac{1}{4}$ S 27/S 26	

New BT's: 17" D. Fir S. 12° E. 16.5 ft. mkd.  $\frac{1}{4}$  S26 CS BT.

11" Cedar N. 62° W. 37.5 ft. mkd.  $\frac{1}{4}$  S27 CS BT.

Note - This corner lies on S.W. slope on new & old N-S blazed line.

59

Sec. Corner to Sections 31 & 32, T23-8W.

Found - 1963 Cadastral Brass Cap, properly Mkd.

Orig. 30" Hemlock, now burned stump, S. 16 $\frac{1}{2}$ ° E. 36.8 ft.

1963 5" Hemlock, dead & burned, N. 37° E. 66.7 ft., scribe vis.

1963 9" Hemlock N. 34 $\frac{1}{2}$ ° W. 37.0 ft., now burned stump, scribe visible.

New BT's: 6" Hemlock N. 27° E. 67.8 ft. mkd. T23S R8W S32 CS BT.

9" Hemlock N. 35 $\frac{1}{2}$ ° W. 90.4 ft. mkd. T23S R8W S31 CS BT.

Note - This corner lies on small bench on westerly slope of small, course S.E. in large logged-off unit.

60

$\frac{1}{4}$  Corner to Section 32 only, T23-8W.

Found - 1963 Cadastral Brass Cap, properly mkd. &  $\frac{1}{2}$ " I.P. alongside.

Orig. 60" Hemlock, now turned out stump, nearly face down, N. 29° W. 11.2 ft.

1963 40" Hemlock, alive, face burned, N. 36° W. 51.5 ft. (Rescribe " $\frac{1}{4}$  S32 CS BT".)

1963 6" Hemlock, down & dead, face burned, N. 53 $\frac{1}{2}$ ° W. 81.2 ft.

New BT; 5" Hemlock N. 36° W. 41.5 ft. mkd.  $\frac{1}{4}$  S 32 CS BT.

Note - This corner lies approx. 150 ft. west of small creek, course N.