Douglas County Surveyor's Record of Government Corners Renewed

T. 23 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

66

Sec. Corner to Sections 19 - 20 - 29 - 30.
Found - Orig. 9", now 15" Chinq. N. 58° E. 14.5 ft., now Snag, scribe "S3 8W 20" visible on unhealed blaze, face badly decayed.
Orig. 14", now 24" Chinq. S. 74° E. 17.8 ft. Alive, shows good scar. Do not open.
Orig. 9", now 16" Chinq. N. 53° W. 7.9 ft. Alive, blaze never healed. Tree now hollow.
No trace Original S. W. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967

T 23 S	R 8 W
S 19	S 20
S 30	S 29

New BT's: 5" W.Fir S. 45° E. 7.7 ft. mkd. S29 CS BT.
14" Chinquapin N. 83° W. 3.5 ft. mkd. T23S R8W S19 CS BT.
5" W.Fir N. 45° E. 19.3 ft. mkd. S20 CS BT.
6" D.Fir S. 60° W. 23.4 ft. mkd. S30 CS BT.
Note - This corner lies on very steep, S.W. slope.

— — — — — — — —

67

Cl. Corner to Sections 24 and 25, T23-9W.
Found - Orig. 48" D. Fir, now 63", S. 73½° W. 38.3 ft., slope dist., scribing:" T23 9W BT" bark scribed.
Orig. 12" Cedar, now 27", N. 50° W. 20.5 ft., slope dist., good faces.
Set - Brass Cap at Cor. Mkd. County Surveyor's Office 1967

R	T 23 S	R
9	S 24	8
W	S 25	W

Rescribd: 27" Cedar N. 50° W. 15.2 ft., level dist., "T23S R9W S24 CS BT."
New BT: 5" Maple S. 79½° W. 11.4 ft. mkd. T23S R9W S25 CC CS BT.
Note - Corner lies 60' N. of creek, course N. Corner set on top of 20 ft. bluff.

#129 RE-RENEWED. SEE CORNER NO.

— — — — — — — —

68

¼ Corner to Sections 10 & 11.
Found - Orig. 12" Cedar S. 78° E. 57.4 ft., alive, shows old scars, we open & find edges of old axe blaze & frag. scribe marks.
Orig. 30" Fir, now turned out & badly decayed, N. 76° W. 37.0 ft., no scribe found.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967 — T 23 S R 8 W ¼ S 10/S 11
New BT's: 7" Cedar S. 46° W. 44.2 ft. mkd. ¼ S10 CS BT.
20" Cedar S. 52° E. 22.3 ft. mkd. ¼ S11 CS BT.
Note - This corner lies 66 ft. N. of small creek, course S.W. & on S.E. slope of point of spur ridge.

— — — — — — — —

69

¼ Section 14 and 13.
Found - Orig. 20", now 30" Laurel, S. 65° E. 5.9 ft., Open on back side & find old reverse axe face. No scribe. Alive.
Orig. 20", now 46" Fir, S. 79° W. 42.9 ft. Open & find reverse axe notch & part of "B" scribe. BT. now hollow & badly decayed.
No trace of Stone called for at Corner.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967 — T 23 S R 8 W ¼ S 14/S 13
New BT's: 9" D.Fir N. 83° W. 10.8 ft. mkd. ¼ S14 CS BT.
6" D.Fir S. 25° W. 32.2 ft. mkd. ¼ S14 CS BT.
9" Laurel S. 59° E. 36.0 ft. mkd. ¼ S13 CS BT.
Note - This corner lies on steep, west slope, 25 ft. N. of top of ridge, course generally E. & W.

103

— — — — — — — —

70

Closing Corner Sections 11 and 14, T23S. R8W.
Found - Orig. 10", now 42" Fir, N. 89° W. 30.4 ft. Alive, shows good scars. Rescribe "T23S R8W S11 CC CS BT" in bark.
Orig. 20", now 40" Fir, S. 87½° E. 48.8 ft. Alive, shows good scars. We do not open.
Orig. 10", now 14" Dogwood, S. 20° W. 76.6 ft., now 7' high stub., prev. opened & shows "S R8W BT' in very poor condition.
No trace of stone called for.

(continued next page)

Vernon "Ray" Tracy
Jack Heritage - E. West
Frank Jones - C. Stone
January & February, 1967
C. S. File No. 54/12