

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 23 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

76

$\frac{1}{4}$  Corner to Section 34 only, T23=R8W.  
Found - Orig. 30", now 40" Fir, S. 17° E. 31.0 ft. Alive, shows good bark scribe " $\frac{1}{4}$ " S" & frag. "BT".  
Orig. 12", now 15" Laurel, N. 40° E. 7.9 ft. Open & find frag. reverse scribe. Alive.  
In excavating to Set new monument, we find sharpened end of very old cedar post.  
Set - Brass Cap at Cor. Mkd: County Surveyor's  $\frac{1}{4}$  S 34 T 23 S R 8 W  
Office, 1967 T 24 S  
New BT's: 6" D. Fir N. 73° E. 24.3 ft. mkd.  $\frac{1}{4}$  S 34 CS BT.  
24" Laurel N. 37° W. 31.2 ft. mkd.  $\frac{1}{4}$  S 34 CS BT.  
Note - This cor. lies 10 ft. W. of top of ridge, course S.E. and 176.6 ft. E. of the  $\frac{1}{4}$  Cor. of Sec. 3, T24-S8W, see below.

77

$\frac{1}{4}$  Corner to Section 3 only, T24-S8W.  
Found - Orig. 48", now 56" Fir, S. 59° W. 6.6 ft. Alive, shows good scars. We do not open.  
Orig. 18", now 26" Fir, N. 46° W. 25.7 ft. Alive. Open & find "4" scribe & reverse.  
Set - Brass Cap at Cor. Mkd: County Surveyor's  $\frac{1}{4}$  S 3 T 23 S R 8 W  
Office, 1967 T 24 S  
New BT's: 5" D. Fir S. 15 $\frac{1}{2}$ ° W. 38.6 ft. mkd.  $\frac{1}{4}$  S 3 CS BT.  
10" D. Fir S. 20° E. 47.5 ft. mkd.  $\frac{1}{4}$  S 3 CS BT.  
Note - This corner lies on steep, southerly slope & 176.6 ft. W. of the  $\frac{1}{4}$  corner of Sec. 34 only, see above.

78

$\frac{1}{4}$  Corner to Sections 16 and 21.  
Found - 4" x 4" Squared Post set in mound of broken sandstone, possible original corner stone.  
Orig. 30", now 40" Fir, N. 73° E. 93.1 ft., turned out, open & find "S" scribe and reverse.  
Orig. 16"?, now 70" Fir, burned remains of stump, S. 38° W. 12.5 ft., find old axe mark & possible scribe on burned blaze.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 23 S R 8 W  
(Set in Mound of Stone) Office 1967  $\frac{1}{4}$  S 16 S 21  
New BT's: 10" D. Fir N. 77° E. 50.6 ft., mkd.  $\frac{1}{4}$  S 21 CS BT.  
Marked: "+ E0" on Sandstone 5 ft. above ground on overhang, Sandstone Boulder 15' x 14' x 10' high S. 80° W. 3.9 ft.  
Note - This corner lies moderate S.E. slope in area of numerous small bluffs.

79

Section Corner to Sections 15 - 16 - 21 - 22.  
Found - Orig. 28", now 34" Fir Snag, N. 35° E. 4.6 ft., shows "T2 S R8W S15 BT", bark scribe in poor condition.  
Orig. 40", now 44" Fir Snag, S. 66° E. 12.5 ft., shows scar. Do not open.  
Orig. 8", now 24" Fir, Alive, N. 77° W. 23.1 ft., shows faint scar. Rescribe "T23S R8W S16 CS BT."  
Large Hole where SW. BT. once stood.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 23 S R 8 W  
Office 1967 S 16 S 15 S 21 S 22  
New BT's: 10" D. Fir S. 70° W. 16.7 ft. mkd. T23S R8W S21 CS BT.  
6" D. Fir. S. 20° W. 19.3 ft. mkd. T23S R8W S21 CS BT.  
5" W. Fir N. 49° E. 22.8 ft. mkd. S15 CS BT.  
No suitable tree to S.E.  
Note - Corner lies on steep, south slope approx. 4 chains N. of Mehl Ck.

FD. 5/86  
I. P. Co.  
TAGS ADDED  
as 6/3/37

80

N. West Corner Section 6.  
Found - 1963 Co. Surv. Brass Cap, See Ren. #21.  
Orig. 40" Fir Stump N. 40° W. 27.1 ft. Rescribed "T23SR8WS6 CS BT".  
9", now 12" D. Fir S. 70° E. 56.2 ft. Alive, scribe visible on nearly healed blaze.  
New BT's: 4" D. Fir N. 49° E. 26.5 ft. mkd. "CS BT".  
4" D. Fir N. 21° W. 115.5 ft. mkd. "CS BT".  
Note - This corner lies approx. 300 ft. W. of top of spur ridge on moderate west slope.

Vernon "Ray" Tracy  
Jack Heritage & E. West  
February, 1967  
C. S. File No. 54/12