

Douglas County Surveyor's Record of
Government Corners Renewed

T23 T. S. R. 8 R. W. W. M.

KOFF-CHAPMAN CO. EUGENE, ORE. 97401

110 ~~01~~

Clell Goodwin
Mary L Ladig
6/10/75
C.S. 57/30

West 1/4 corner of Sec. 31 only T23,R8
Found: Rotted Hemlock stump with scribed BT legible. Bears S38°E.,
4.6 ft. (scribe is on NE face of stump)
70' Fir with scar bears N 62°E., 46.2 ft. (call N.2°E.,
46.2 ft.)
New: I intersect call distances and match bearing to S E BT (no
sign of any other possible 70" Fir) and
Set: Brass cap on 1 1/2" Iron pipe stamped DOUGLAS CO. SURVEYOR

T 23 S
R | R
9 | 8
W | W
W 1/4 S 31

1975

and scribe a new BT

A 8" hemlock scribed T 23S R8W S 31 CS BT in a double blaze bears
S 63°., E 14.7 Ft. Compass Declination 20° 6-10-75

Jan 78

111

Forrest J. Hales
For: International
Paper Co.
October 23, 1978
M 74 - 26

Center 1/4 Corner for Section 25.
Set - 5/8" Iron rod
BT's - 8" D. Fir bears S.0 1/2° E., 6.0 ft.
12" W. Oak bears N. 12 1/2° W., 27.8 ft.
Trees marked "BT C 1/4 S25 453".

10/23/78

112

Les Roberts
For: International
Paper Co.
March 1979
M 76 - 21

1/4 Corner for Secs. 20 and 21.
Found - 3/4" Iron pipe and 12" x 10" x 6" stone.
28" Burned-out stump, N. 12°E., 39.3 ft.
Set - Drove 1 1/2" Iron pipe and brass cap over existing 3/4 iron pipe.

3/79

113

Les Roberts
Triangle Eng. Co.
For: International
Paper Co.
July 1979

Closing Cor. to Sec. 6, T.24S. R.7W. and Sec. 1, T.24S. R.8W.
Set - 1 1/2" I. pipe and brass cap at true intersection
BT's - 12" Fir bears S.62°W., 64.1 ft.
8" Fir bears S.55°E., 11.2 ft.
Note - See also Renewal #. 34.
Corner lies 2.28' S. of Co. Renewal #. 34.

RE-RENEWED, SEE CORNER NO. # 130

Center 1/4 Corner for Sec. 23
Set - 1 1/2" x 36" Iron pipe and brass cap
BT's - 16" Hemlock bears N.19°E., 14.6 ft. (scribed)
19" Fir, bears S.46°E., 43.8 ft. (scribed.)

2/13/81

114

Center 1/4 Corner for Section 24
Set - 1 1/2" x 36" Iron pipe and brass cap
BT's - 16" W. Fir, bears S.66°E., 26.8 ft. (scribed)
24" W. Fir, bears N.36°W., 39.1 ft. (scribed)

2/20/81

115

1/4 Corner for Sections 21 and 22
No evidence of original corner.
Set - 1 1/2" x 36" Iron pipe with brass cap at proportionate distance.
BT's - 18" Fir, bears S.64°W., 20.5 ft. (scribed)
24" Fir, bears N.59°E., 23.3 ft. (scribed)

1/26/81

116

1/4 Corner for Sections 15 and 22.
No evidence of original corner.
Set - 1 1/2" x 36" Iron pipe with brass cap at proportionate distance.
BT's - 44" Fir, bears S.18°W., 86.0 ft. (scribed)
36" Fir, bears N.77°W., 24.7 ft. (scribed)

1/26/81

117

Les Roberts, LS #1039
For: International Paper Company
Jan.-Feb. 1981

M86-66

M86-64

M 86 - 65

3/77

1-79