

Douglas County Surveyor's Record of
Government Corners Renewed

T 23

T. S. R 3

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

123

West 1/4 Corner for Section 2, only.

Set - 1 1/2" x 36" iron pipe and brass cap stamped S-T-R, Date and
P.L.S. No. 1039. (Incorrect corner bears S.0°09'37"W., 19.12 ft.)
13" W.Fir, S.39°E., 43.7 ft. (Scribed.)
44" Fir, N.4°E., 38.6 ft. (Scribed).

Note: I replaced incorrectly set pipe with 5/8" x 30" iron pin (buried
1.0 ft.) on 12/30/82.

124

Section corner for Secs. 1, 2, 11 and 12

CORNER REPORT ONLY.

Found - 1967 B.L.M. brass cap (buried 2.5 ft.)
1957 Oregon State Board of Forestry Brass cap bears N.2°45'W.,
2.08 ft. (buried 2.0 ft.) Ren. #5
38" oak snag, S.7°E., 322.5 ft. (no marks), 1860 BT.
25" Oak, S.53°W., 330.2 ft. (scar visible) 1957 BT.
30" oak, South, 314.4 ft. (scar visible) 1957 BT.

125

Closing Corner for Sections 2 and 11.

Found - 1959 Douglas County Brass Cap. Ren. #10A
42" fir, S.3°E., 43.8 ft. (scar vis.) 1894 BT.
22" fir, N.25°E., 43.4 ft. (scar vis.) 1959 CS BT.
8" fir, S.30°E., 15.8 ft. (scar vis.) 1959 CS BT.

Set - 1 1/2" x 36" iron pipe and brass cap at true intersection. Cap
stamped with S-T-R, date and PLS No. 1039.

Note - 1959 Douglas County brass cap bears N.80°13'00"W., 1.10 ft.
No new BTs set.

126

North 1/4 Corner for Section 2 only

No evidence found of original corner.

Set - 5/8" x 30" iron rod at proportionate distance. Rod has yellow
plastic cap marked "Roberts" L.S. 1039. Rod buried 1.0 ft.

New BTs-15" oak, S.57°E., 282.2 ft. (scribed)

18" oak, S.77°E., 270.8 ft. (scribed)

Note - Incorrect corner bears S.89°46'12"E., 0.89 ft. I removed incorrectly
set pin on 12/30/82.

127

Standard Corner for Sections 1 and 2.

No evidence found of original corner.

Set - 5/8" x 24" iron rod at proportionate distance. Buried 0.5 ft.. Rod
has yellow plastic cap marked "Roberts" L.S. 1039.

(Incorrect corner bears S.89°44'34"E., 1.69 ft.)

New BTs-24" oak, S.25°W., 58.4 ft. (scribed)

32" oak, S.62°E., 165.2 ft. (scribed.)

Note - I removed incorrectly set pin on 12/30/82.

10-12/82

128

1/4 Corner for Section 3 only.

Found - 1" I.P. with County brass cap marked "County Surveyors Office
T23S 1/4 S3 S2 R8W 1967 BLM 1967" Ren. #89

Orig. 12" cedar, now 44" with good scar, bears S.2°W., 38.3 ft.

Orig. 50" fir, now 59" with bark scribed 1/4 S visible, bears
S.64°E., 60.7 ft.

10" fir, per Ren. #89, now 13" with good scar, bears S.29°E.,
25.1 ft.

Since this corner is the 1/4 corner to Section 3 only, I "X" out the
S2 which was stamped on the cap in 1967.

A newly blazed line runs North and South from corner.

Les Roberts, L.S. #1039
For: International Paper Company
October-December 1982
M 90 - 29 C.S. 58/280

Gregory Quibell
Deputy- Douglas
Co. Surveyors
Office
John Powell
Randy Smith
Jan. 13, 1983
C.S. 62/7

N E X T P A G E